

US010142980B2

(12) United States Patent

Radulescu et al.

(54) DISCOVERY REFERENCE SIGNAL TRANSMISSION WINDOW DETECTION AND DISCOVERY REFERENCE SIGNAL MEASUREMENT CONFIGURATION

(71) Applicant: **QUALCOMM Incorporated**, San Diego, CA (US)

(72) Inventore Andrei Badulagan San Diaga CA

(72) Inventors: Andrei Radulescu, San Diego, CA

(US); Chirag Patel, San Diego, CA (US); Tao Luo, San Diego, CA (US); Arumugam Chendamarai Kannan,

San Diego, CA (US)

(73) Assignee: **QUALCOMM Incorporated**, San

Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 42 days.

(21) Appl. No.: 15/441,215

(22) Filed: Feb. 23, 2017

(65) **Prior Publication Data**

US 2017/0251499 A1 Aug. 31, 2017

Related U.S. Application Data

- (60) Provisional application No. 62/300,718, filed on Feb. 26, 2016, provisional application No. 62/318,742, filed on Apr. 5, 2016.
- (51) **Int. Cl. H04L 12/24** (2006.01) **H04W 72/04** (2009.01)

 (Continued)
- (52) **U.S. Cl.**CPC *H04W 72/042* (2013.01); *H04B 17/318* (2015.01); *H04J 11/0036* (2013.01); (Continued)

(10) Patent No.: US 10,142,980 B2

(45) **Date of Patent:** Nov. 27, 2018

(58) Field of Classification Search None

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

FOREIGN PATENT DOCUMENTS

WO WO 2015122737 A1 * 8/2015 H04L 5/0053 WO WO-2015122737 A1 8/2015 (Continued)

OTHER PUBLICATIONS

Intel Corporation, "DRS Measurement for Small Cell On/Off and Discovery," 3GPP TSG RAN WG2 Meeting #87, R2-143822, Dresden, Germany, Aug. 18-22, 2014, 5 pgs., XP0508201, 3rd Generation Partnership Project.

(Continued)

Primary Examiner — Afsar M Qureshi (74) Attorney, Agent, or Firm — Holland & Hart LLP

(57) ABSTRACT

Methods, systems, and devices for wireless communication are described. A user equipment (UE) may monitor a neighbor cell and report the result to a serving base station. Based on the report, the serving base station may identify an estimated discovery reference signal (DRS) transmission window of the neighbor cell. In some cases, the UE may estimate and report parameters of the neighbor DRS transmission window, and in other cases, the UE may make a measurement report and the base station may infer DRS transmission window parameters. The base station may then provide the UE with a DRS measurement timing configuration (DMTC) based on the estimated parameters of the neighbor cell so that the UE may monitor the neighbor cell (Continued)

