

제6강

1) Props를 이용한 테마 변경

[src]-[components06]-[props] RootPage.jsx

```
import React, { useState } from 'react'
import '../Style06.css'
import Page from './Page'

const RootPage = () => {
  const [dark, setDark] = useState(false);
  return (
    <div>
      <Page dark={dark} setDark={setDark}/>
    </div>
  )
}
export default RootPage
```

```
.black {
  color:white;
  background: black;
}

.gray {
  color: black;
  background: lightgray;
}

.white {
  color:black;
  background: white;
}
```

[src]-[components06]-[props] Page.jsx

```
const Page = ({dark, setDark}) => {
  return (
    <div>
      <Header dark={dark}/>
      <Content dark={dark}/>
      <Footer dark={dark} setDark={setDark}/>
    </div>
  )
}
export default Page
```

[src]-[components06]-[props] Footer.jsx

```
const Footer = ({dark, setDark}) => {
  return (
    <div className={`footer ${dark ? 'black':'gray'}`}>
      <button onClick={()=>setDark(!dark)}>{dark ? 'Light Mode' : 'Dark Mode'}</button>
    </div>
  )
}
export default Footer
```

[src]-[components06]-[props] Header.jsx

```
const Header = ({dark}) => {
  return (
    <div className={`header ${dark ? 'black':'gray'}`}>
      <h1>Welcom 홍길동</h1>
    </div>
  )
}
export default Header
```

[src]-[components06]-[props] Content.jsx

```
const Content = ({dark}) => {
  return (
    <div className={`content ${dark ? 'black':'white'}`}>
      <h1>홍길동님 좋은 하루되세요!</h1>
    </div>
  )
}
export default Content
```

2) useContext를 이용한 테마, 로그인 상태 변경

[src]-[components06]-[context] RootPage.jsx

```
import React, { useState } from 'react'
import { ThemeContext } from '../ThemeContext';
import { UserContext } from '../UserContext';
import '../Style06.css'
import Page from './Page'

const RootPage = () => {
  const [dark, setDark] = useState(false);
  const [user, setUser] = useState({
    isLogin:false,
    name:'사용자'
  });

  return (
    <UserContext value={{user, setUser}}>
      <ThemeContext.Provider value={{dark, setDark}}>
        <Page/>
      </ThemeContext.Provider>
    </UserContext>
  )
}
export default RootPage
```

[src]-[components06]-[context] Footer.jsx

```
import { useContext } from 'react'
import { ThemeContext } from '../ThemeContext'
import { UserContext } from '../UserContext'

const Footer = () => {
  const {dark, setDark} = useContext(ThemeContext);
  const {user, setUser} = useContext(UserContext);
  return (
    <div className={`footer ${dark ? 'black':'gray'}`>
      <span>{user.name}</span>
      { user.isLogin ?
        <button onClick={()=>setUser({ isLogin:false, name:'사용자' })}>로그아웃</button>
        :
        <button onClick={()=>setUser({ isLogin:true, name:'홍길동' })}>로그인</button>
      }
      <button onClick={()=>setDark(!dark)}>{dark ? 'Dark Mode':'Light Mode'}</button>
    </div>
  )
}
export default Footer
```

[src]-[components06]-[context] Header.jsx

```
import { useContext } from 'react'
import { ThemeContext } from '../ThemeContext'
import { UserContext } from '../UserContext';

const Header = () => {
  const {dark} = useContext(ThemeContext);
  const {user} = useContext(UserContext);
  return (
    <div className={`header ${dark ? 'black':'gray'}`>
      <h1>Welcom {user.name}</h1>
    </div>
  )
}
export default Header
```

```
[src]-[components06]-[context] Content.jsx
```

```
import { useContext } from 'react'
import { ThemeContext } from './ThemeContext'
import { UserContext } from './UserContext';

const Content = () => {
  const {dark} = useContext(ThemeContext);
  const {user} = useContext(UserContext);
  return (
    <div className={`content ${dark ? 'black':'white'}`}>
      <h1>{user.name}님 좋은 하루되세요!</h1>
    </div>
  )
}
export default Content
```

3) Provider 컴포넌트 이용

```
[src]-[components06]-[context] CommonProvider.jsx
```

```
import React, { useState } from 'react'
import { UserContext } from './UserContext';
import { ThemeContext } from './ThemeContext';

const CommonProvider = ({children}) => {
  const [dark, setDark] = useState();
  const [user, setUser] = useState({
    isLogin:false,
    name:'사용자'
  });

  return (
    <UserContext.Provider value={{user, setUser}}>
      <ThemeContext.Provider value={{dark, setDark}}>
        {children}
      </ThemeContext.Provider>
    </UserContext.Provider>
  )
}
export default CommonProvider
```

```
[src]-[components06]-[context] RootPage.jsx
```

```
import React, { useState } from 'react'
import { ThemeContext } from './ThemeContext';
import { UserContext } from './UserContext';

import CommonProvider from './CommonProvider';
import '../Style06.css'
import Page from './Page'

const RootPage = () => {
  return (
    <CommonProvider>
      <Page/>
    </CommonProvider>
  )
}
export default RootPage
```