

제7강

1) react-router-dom를 이용한 MainRouter

[src]-[components07] MainRouter.jsx

```
import { Link, Routes, Route, NavLink, useLocation } from 'react-router-dom'
import '../Style07.css'
import HomePage from './HomePage'
import AboutPage from './AboutPage'
import ProfilePage from './ProfilePage'
import NaviPage from './NaviPage'

const MainRouter = () => {
  const { pathname } = useLocation();

  return (
    <div className='box'>
      <h5>메뉴를 선택하세요! ({pathname})</h5>
      <ul>
        <li><NavLink to='/'>홈</NavLink></li>
        <li><NavLink to='/about?page=1 &query=노트북&detail=true'>소개</NavLink></li>
        <li><NavLink to='/profiles'>프로필</NavLink></li>
        <li><NavLink to='/info'>Infomation</NavLink></li>
        <li><NavLink to='/navi'>Navigation</NavLink></li>
      </ul>
      <Routes>
        <Route path='/' element={<HomePage/>} />
        <Route path='/about' element={<AboutPage/>} />
        <Route path='/profiles/*' element={<ProfilePage/>} />
        <Route path='/info' element={<AboutPage/>} />
        <Route path='/navi' element={<NaviPage/>} />
      </Routes>
    </div>
  )
}
```

```
export default MainRouter
```

[src]-[components07] ProfilePage.jsx

```
.active {
  background: gray;
  color: white;
}
```

[src]-[components07] ProfilePage.jsx

```
import React from 'react'

const HomePage = () => {
  return (
    <div>
      <h1>홈</h1>
      <div>가장 먼저 보여주는 페이지입니다.</div>
    </div>
  )
}
```

```
export default HomePage
```

[src]-[components07] ProfilePage.jsx

```
const ProfilePage = () => {
  return (
    <div>
      <h5>{username} 프로필</h5>
      <ul>
        <li><NavLink to='/profiles/hong'>홍길동</NavLink></li>
        <li><NavLink to='/profiles/kang'>강참찬</NavLink></li>
        <li><NavLink to='/profiles/sung'>성춘향</NavLink></li>
      </ul>
      <Routes>
        <Route path="/" element={<div>사용자를 선택해 주세요.</div>}/>
        <Route path="/:username" element={<Profile/>}/>
      </Routes>
    </div>
  )
}
```

[src]-[components07] Profile.jsx

```
import { useParams } from 'react-router-dom'
...
const Profile = () => {
  const {username} = useParams();
  return (
    <div>
      <h5>{username} 프로필</h5>
      <div>이름:{data[username].name}</div>
      <div>소개:{data[username].description}</div>
    </div>
  )
}
```

[src]-[components07] AboutPage.jsx

```
const AboutPage = () => {
  const [search] = useSearchParams(); //search 객체의 값들은 모두 문자열 숫자나 boolean인 경우 변환
  const page = parseInt(search.get('page'));
  const query = search.get('query');
  const detail = search.get('detail')==='true';
  return (
    <div>
      <h1>소개</h1>
      <div>리액트 라우터 기초를 실습해 보는 예제 프로젝트입니다.</div>
      {detail && <div>페이지:{page+1}, 검색어:{query}</div> }
    </div>
  )
}
```

[src]-[components07] NaviPage.jsx

```
import React from 'react'
import { useNavigate } from 'react-router-dom'
const NaviPage = () => {
  const navi = useNavigate();
  return (
    <div>
      <h1>Navigation</h1>
      <button onClick={ ()=>navi(-1) }>뒤로</button>
      <button onClick={ ()=>navi('/') }>홈으로</button>
    </div>
  )
}
```

2) react-router-dom를 이용한 JSONRouter

[src]-[components07] JSONRouter.jsx

```
const JSONRouter = () => {
  return (
    <div className='box'>
      <div>
        <NavLink to='/json/posts'>Posts</NavLink>
        <NavLink to='/json/todos'>Todos</NavLink>
        <NavLink to='/json/albums'>Albums</NavLink>
      </div>
      <Routes>
        <Route path='/json/:type' element={<JSONPage/>}/>
      </Routes>
    </div>
  )
}
export default JSONRouter
```

[src]-[components07] JSONPage.jsx

```
import React, { useEffect, useState } from 'react'
import { useNavigate, useParams, useSearchParams } from 'react-router-dom'

const JSONPage = () => {
  const [response, setResponse] = useState(null);

  const { type } = useParams();
  const [search] = useSearchParams();
  const id = parseInt(search.get('id')) || 1;

  const navi = useNavigate();

  const callAPI = () => {
    fetch(`https://jsonplaceholder.typicode.com/${type}?id=${id}`)
      .then(response => response.json())
      .then(json => {
        console.log(json);
        setResponse(json);
      })
  }

  useEffect(() => {
    callAPI();
  }, [type, id]);

  return (
    <div className='json'>
      <h5>JSONPlaceholder</h5>
      <pre>{response && JSON.stringify(response, null, 2)}</pre>
      <div>
        <button onClick={()=>navi(`/json/${type}?id=${id-1}`)} disabled={id===1}>감소</button>
        <span>{id}</span>
        <button onClick={()=>navi(`/json/${type}?id=${id+1}`)}>증가</button>
      </div>
    </div>
  )
}
export default JSONPage
```