

제8강

1) 리액트 부트스트랩을 이용한 Layout

[src]-[components08] LayoutPage.jsx

```
import React, { useEffect, useRef, useState } from 'react'
import { Row, Col, Card } from 'react-bootstrap'
import axios from 'axios'
import PageButton from './PageButton';

const LayoutPage = () => {
  const [posts, setPosts] = useState([]);
  const [page, setPage] = useState(1);
  const lastRef = useRef(1);
  const size=12;

  const callAPI = async() => {
    const url = 'https://jsonplaceholder.typicode.com/posts';
    const res = await axios.get(url);
    const start = (page-1) * size + 1;
    const end = page * size;
    const data = res.data.filter(post=>post.id>=start && post.id<=end);
    setPosts(data);
    lastRef.current=Math.ceil(res.data.length/size);
  }

  useEffect(()=>{
    callAPI();
  }, [page]);

  return (
    <div>
      <h1 className='my-5 text-center'>게시글</h1>
      <Row>
        { posts.map(post=>
          <Col key={post.id} xs={6} md={4} lg={3} xl={2} className='mb-3'>
            <Card>
              <Card.Body>
                <div className='body'>{post.body}</div>
              </Card.Body>
              <Card.Footer>
                <div className='title text-truncate'>{post.title}</div>
              </Card.Footer>
            </Card>
          </Col>
        )}
      </Row>
      <PageButton page={page} setPage={setPage} last={lastRef.current}/>
    </div>
  )
}
```

```
.body {
  overflow: hidden;
  text-overflow: ellipsis;
  display: -webkit-box;
  -webkit-line-clamp: 3;
  -webkit-box-orient: vertical;
  font-size: 12px;
}

.title {
  font-size: 12px;
  justify-content: left;
}
```

[src]-[components08] PageButton.jsx

```
import { Button } from 'react-bootstrap'
const PageButton = ({ page, setPage, last }) => {
  return (
    <div className='text-center mt-3'>
      <Button onClick={()=>setPage(page-1)} disabled={page===1}>이전</Button>
      <span> {page}/{last} </span>
      <Button onClick={()=>setPage(page+1)} disabled={page===last}>다음</Button>
    </div>
  )
}
```

2) 리액트 부트스트랩을 이용한 Table

[src]-[components08] TablePage.jsx

```
import { Table } from 'react-bootstrap'
...
const TablePage = () => {
  const [posts, setPosts] = useState([]);
  const [page, setPage] = useState(1);
  const lastRef = useRef(1);
  const size=10;

  const callAPI = async() => {
    const url = 'https://jsonplaceholder.typicode.com/posts';
    const res = await axios.get(url);
    const start = (page-1) * size + 1;
    const end = page * size;
    const data = res.data.filter(post=>post.id>=start && post.id<=end);
    setPosts(data);
    lastRef.current=Math.ceil(res.data.length/size);
  }

  useEffect(()=>{
    callAPI();
  }, [page]);

  return (
    <div>
      <h1 className='text-center my-5'>게시글</h1>
      <Table hover striped bordered>
        <tbody>
          { posts.map(post=>
            <tr key={post.id}>
              <td>{post.id}</td>
              <td>{post.title}</td>
            </tr>
          )}
        </tbody>
      </Table>
      <PageButton page={page} setPage={setPage} last={lastRef.current}/>
    </div>
  )
}
```

[src]-[components08] MainRouter.jsx

```
import ModalProvider from '../context/ModalProvider'
...
const MainRouter = () => {
  return (
    <ModalProvider>
      <Container className='mt-5'>
        <NavLink to='/'>레이아웃</NavLink>
        <NavLink to='/table'>테이블</NavLink>
        <NavLink to='/form'>폼</NavLink>
        <hr/>
        <Routes>
          <Route path='/' element={<LayoutPage/>}/>
          <Route path='/table' element={<TablePage/>}/>
          <Route path='/form' element={<FormPage/>}/>
        </Routes>
      </Container>
    </ModalProvider>
  )
}
```

3) 리액트 부트스트랩을 이용한 Form

[src]-[components08] FormPage.jsx

```
import { ModalContext } from '../context/ModalContext'
import { Row, Col, Form, InputGroup, Button } from 'react-bootstrap'
...
const FormPage = () => {
  const formRef = useRef(initForm);
  const { showAlert, setConfirm } = useContext(ModalContext);
  ...
  const onSubmit = (e) => {
    e.preventDefault();
    if(id===''){
      showAlert({show:true, message:'아이디를 입력하세요!'});
    }else{
      setConfirm({
        show:'true',
        message:'정말로 가입하실래요?',
        action:()=>{
          console.log(form);
        }
      });
    }
  }

  const onReset = (e) => {
    e.preventDefault();
    setConfirm({
      show:'true',
      message:'정말로 취소하실래요?',
      action:()=>{
        setForm(formRef.current);
        console.log(form);
      }
    });
  }

  const onChange = (e) => {
    setForm({...form, [e.target.name]:e.target.value});
  }

  return (
    <div>
      <h1 className='text-center my-5'>회원가입</h1>
      <Row className='justify-content-center'>
        <Col xs={12} md={10} lg={9} xl={8}>
          <Form onSubmit={onSubmit} onReset={onReset}>
            <InputGroup className='mb-2'>
              <InputGroup.Text>아이디</InputGroup.Text>
              <Form.Control value={id} onChange={onChange} name='id' placeholder='아이디' />
            </InputGroup>
            ...
            <Form.Control value={intro} onChange={onChange}
              name='intro' placeholder='자기소개' as='textarea' rows={5} />
          <div className='text-center mt-3'>
            <Button disabled={JSON.stringify(form)===JSON.stringify(formRef.current)}
              type='submit' className='px-3 me-2'>가입</Button>
            <Button disabled={JSON.stringify(form)===JSON.stringify(formRef.current)}
              type='reset' className='px-3' variant='secondary'>취소</Button>
          </div>
        </Form>
      </Col>
    </Row>
  </div>
  )
}
```