

제10강

1) 네이버 API를 활용한 상품검색

ToDoList10

1. BookPage 도서검색에서 BookModal 도서정보 모달창을 만들어 연결한다.
2. 네이버 개발자 센터에서 애플리케이션을 생성한다.
<https://developers.naver.com/main/>
3. 내 애플리케이션에서 NAVERID, NAVERSECRET 키를 복사한다.
4. 루트 .env 파일에 복사한 키를 붙여넣는다.
`REACT_APP_NAVERID=xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx`
`REACT_APP_NAVERSECRET=xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx`
* 교차 출처 리소스 공유(CORS:Cross-Origin Resource Sharing)란?
 - 한 출처(Origin)에서 다른 출처의 리소스에 접근할 수 있도록 허용.
 - 네이버 API 서버는 CORS을 허용하지 않아서 에러발생.
 - 클라이언트와 서버 사이에서 중개자 역할을 하는 프락시 서버 설정 필요.
5. 네이버 검색을 위해 프락시 서버를 package.json에 추가한 후 서버를 다시 구동한다.
`"proxy": "https://openapi.naver.com/v1"`
6. ShopPage 컴포넌트에 검색, 페이지 기능을 추가한다.
7. ShopPage에서 ShopModal 상품정보 컴포넌트를 연결한다.

[src]-[components10] MainRouter.jsx

```
{
  "name": "react-project",
  "version": "0.1.0",
  "private": true,
  "dependencies": {
    ...
  },
},
"proxy": "https://openapi.naver.com/v1"
```

[src]-[components10] MainRouter.jsx

```
import { Route, Routes } from 'react-router'
import MenuBar from './MenuBar'
import HomePage from './HomePage'
import BookPage from './BookPage'
import ShopPage from './ShopPage'
import ModalProvider from '../context/ModalProvider'
import '../Style.css'
import { Container } from 'react-bootstrap'

const MainRouter = () => {
  return (
    <ModalProvider>
      <Container>
        <MenuBar/>
        <Routes>
          <Route path="/" element={<HomePage/>}/>
          <Route path="/book" element={<BookPage/>}/>
          <Route path="/shop" element={<ShopPage/>}/>
        </Routes>
      </Container>
    </ModalProvider>
  )
}
export default MainRouter
```

[src]-[components10] ShopPage.jsx

```
import React, { useEffect, useState } from 'react'
import axios from 'axios';
import { Row, Col, Card } from 'react-bootstrap';
import { useSearchParams } from 'react-router-dom';
import SearchForm from '../common/SearchForm'
import PagingButton from '../common/PagingButton'

const ShopPage = () => {
  const [loading, setLoading] = useState(false);
  const [response, setResponse] = useState(null);

  const [search] = useSearchParams();
  const size=12;
  const query = search.get('query') || '노트북';
  const page = parseInt(search.get('page') || 1);

  const callAPI = async() => {
    setLoading(true);
    const url = '/search/shop.json';
    const config = {
      headers:{
        'X-Naver-Client-Id':process.env.REACT_APP_NAVERID,
        'X-Naver-Client-Secret':process.env.REACT_APP_NAVERSECRET
      },
      params:{ start:1, query, display:size }
    }
    const res = await axios(url, config);
    console.log(res.data);
    setResponse(res.data);
    setLoading(false);
  }

  useEffect(()=>{
    callAPI();
  }, [query, page]);

  if(loading || !response) return <h1 className='text-center my-5'>로딩중...</h1>
  const { items, total } = response;
  const last = Math.ceil(total/size);

  return (
    <div className='my-5'>
      <h1 className='text-center mb-5'>상품검색</h1>
      <SearchForm query={query}/>
      <Row>
        {items.map(product=>
          <Col key={product.id} xs={6} md={4} lg={3} xl={2} className='mb-3'>
            <Card>
              <Card.Body>
                <img src={ product.image } width='100%' />
              </Card.Body>
              <Card.Footer>
                <div className='text-truncate title' dangerouslySetInnerHTML={{__html:shop.title}} />
              </Card.Footer>
            </Card>
          </Col>
        )}
      </Row>
      { items.length===0 && <h3 className='text-center my-5'>검색 결과가 없습니다.</h3>}
      {last > 1 && <PagingButton page={page} last={last} query={query}/>}
    </div>
  )
}

export default ShopPage
```

2) 도서정보 모달창

[src]-[componetns10]-[book] BookModal.jsx

```
const BookModal = ({ book }) => {
  const [show, setShow] = useState(false);
  const handleClose = () => setShow(false);
  const handleShow = () => setShow(true);

  return (
    <
      <img style={{cursor:'pointer'}} onClick={handleShow}
        src={book.thumbnail || 'http://placeholder.co/100x150'} width='100%'/>
      <Modal size='lg' show={show} onHide={handleClose} backdrop="static" keyboard={false}>
        <Modal.Header closeButton>
          <Modal.Title>도서정보</Modal.Title>
        </Modal.Header>
        <Modal.Body>
          <Row>
            <Col lg={4} lassName='align-self-center'>
              <img src={book.thumbnail || 'http://placeholder.co/100x150'} width='100%'/>
            </Col>
            <Col className='align-self-center'>
              <h5>{book.title}</h5>
              <hr/>
              <div className='mb-3'>저자: {book.authors}</div>
              <div className='mb-3'>가격: {parseInt(book.price).toLocaleString()}원</div>
              <div className='mb-3'>출판사: {book.publisher}</div>
              <div className='mb-3'>ISBN: {book.isbn}</div>
              <div className='mb-3'>날짜: {book.datetime.substr(0, 10)}</div>
              <div className='mb-3'>상태: {book.status}</div>
            </Col>
          </Row>
          <hr/>
          <div style={{whiteSpace:'pre-wrap'}}>{book.contents || '내용 없음'}</div>
        </Modal.Body>
        <Modal.Footer>
          <Button variant="secondary" onClick={handleClose}>Close</Button>
        </Modal.Footer>
      </Modal>
    </>
  )
}
```

export default BookModal

[src]-[componetns10]-[book] BookModal.jsx

```
import BookModal from './book/BookModal'
...
const BookPage = () => {
  return (
    ...
    <Card>
      <Card.Body>
        <BookModal book={book}/>
      </Card.Body>
      <Card.Footer>
        <div className='title text-truncate'>
          { (page-1)*size + index+1}. { book.title }
        </div>
      </Card.Footer>
    </Card>
    ...
  )
}
```

export default BookModal

3) 상품정보 모달창

[src]-[componetns10]-[shop] ShopModal.jsx

```
const ShopModal = ({ shop }) => {
  const [show, setShow] = useState(false);
  const handleClose = () => setShow(false);
  const handleShow = () => setShow(true);
  return (
    <>
      <img style={{cursor:'pointer'}} onClick={handleShow} src={shop.image} width='100%' />
      <Modal show={show} onHide={handleClose} backdrop="static" keyboard={false} size='lg'>
        <Modal.Header closeButton>
          <Modal.Title>상품정보</Modal.Title>
        </Modal.Header>
        <Modal.Body>
          <Row>
            <Col lg={4} className='align-self-center'>
              <img src={shop.image || 'http://placeholder.co/100x150'} width='100%' />
            </Col>
            <Col className='align-self-center'>
              <div dangerouslySetInnerHTML={{__html:shop.title}}/>
              <hr/>
              <div className='mb-2'>가격: {shop.lprice ? parseInt(shop.lprice).toLocaleString(): '미정'}</div>
              <div className='mb-2'>상품ID: {shop.productId}</div>
              <div className='mb-2'>제조사: {shop.maker}</div>
              <div className='mb-2'>판매점: {shop.mallName}</div>
              <div className='mb-2'>카테고리: {shop.category1}</div>
            </Col>
          </Row>
        </Modal.Body>
        <Modal.Footer>
          <Button variant="secondary" onClick={handleClose}>Close</Button>
        </Modal.Footer>
      </Modal>
    </>
  );
}
```

export default ShopModal

[src]-[componetns10] BookPage.jsx

```
import ShopModal from './shop/ShopModal'
...
const ShopPage = () => {
  return (
    <div className='my-5'>
      <h1 className='text-center mb-5'>상품검색</h1>
      <Row>
        { items.map(shop=>
          <Col key={shop.productId} xs={6} md={4} lg={3} xl={2} className='mb-3'>
            <Card>
              <Card.Body>
                <ShopModal shop={shop}/>
              </Card.Body>
              <Card.Footer>
                <div className='text-truncate title' dangerouslySetInnerHTML={{__html:shop.title}}/>
              </Card.Footer>
            </Card>
          </Col>
        )}
      </Row>
      ...
    </div>
  )
}
```