Data Intake Report

Name: Model Deployment on Flask

Report date: 28.02.2024 Internship Batch: LISUM30

Version:<1.0>


Data intake by: Olena Panchenko Data intake reviewer: Data Glacier

Data storage location: https://github.com/helenapanchenko/DS_Internship_Glacier/tree/master/Week4

Tabular data details: Property_Prices

Total number of observations	17
Total number of files	1
Total number of features	5
Base format of the file	.csv
Size of the data	1KB

1. Project Directory Structure



2. A list of dependencies and libraries used in this project

≡ requirements.txt ×

```
blinker==1.7.0
1
 2
     click==8.1.7
     colorama==0.4.6
     Flask==3.0.2
 5
     itsdangerous==2.1.2
 6
     Jinja2==3.1.3
7
     joblib==1.3.2
8
     MarkupSafe==2.1.5
     numpy==1.26.4
10
     pandas==2.2.1
11
     python-dateutil==2.8.2
12
     pytz==2024.1
13
     scikit-learn==1.4.1.post1
14
     scipy==1.12.0
     six==1.16.0
15
     threadpoolctl==3.3.0
16
     tzdata==2024.1
17
18
     Werkzeug==3.0.1
```

3. Data

Bedrooms	Bathrooms	Floor Area(ft2)	Council Tax Band	Price(£)
3	1	1022	C	350000
5	3	2700	F	1500000
6	5	4300		1350000
7	5		F	1295000
3	1		Α	260000
4	4		G	1200000
3	1		C	300000
7	2	4000	E	950000
5	3	3821	F	950000
6	3		F	925000
4	2	1283	F	925000
3	2		E	900000
2	2			325000
1	1			120000
2	1		Α	120000
2	1		Α	180000
1	1		Α	90000

4. Data Preprocessing

```
Ir_model.py ×
```

```
import pandas as pd
     import pickle
     from sklearn.linear model import LinearRegression
5
     dataset = pd.read csv('Property Prices.csv')
6
7
     dataset.loc[[13, 16], 'Floor Area(ft2)'] = 400
     no_missing_area_data = dataset.loc[:, ['Bedrooms', 'Bathrooms', 'Floor Area(ft2)']].dropna(subset=['Floor Area(ft2)'])
8
9
     missing_area_data = dataset.loc[:, ['Bedrooms', 'Bathrooms', 'Floor Area(ft2)']][dataset['Floor Area(ft2)'].isnull()]
     no_missing_area_predictors = no_missing_area_data.drop(columns=['Floor Area(ft2)'])
     no_missing_area_targets = no_missing_area_data['Floor Area(ft2)']
     missing_area_predictors = missing_area_data.drop(columns=['Floor Area(ft2)'])
14
     mv_model = LinearRegression()
     mv_model.fit(no_missing_area_predictors, no_missing_area_targets)
     predicted_areas = mv_model.predict(missing_area_predictors)
17
     dataset.loc[dataset['Floor Area(ft2)'].isnull(), ['Floor Area(ft2)']] = predicted_areas
19
     encoding_dict = {'A': 1, 'B': 2, 'C': 3, 'D': 4, 'E': 5, 'F': 6, 'G': 7, 'H': 8}
20
     dataset['Council Tax Band'] = dataset['Council Tax Band'].map(encoding_dict)
     mode_by_bedrooms = dataset.groupby('Bedrooms')['Council Tax Band'].transform(lambda x: x.mode().iloc[0])
     dataset['Council Tax Band'] = dataset['Council Tax Band'].fillna(mode_by_bedrooms)
```

5. Model Training and Saving

```
model_predictors = dataset.iloc[:, :4].values
model_targets = dataset.iloc[:, -1]
regressor = LinearRegression()
regressor.fit(model_predictors, model_targets)
pickle.dump(regressor, open('lr_model.pkl', 'wb'))
```

6. HTML template

```
<> index.html ×
     <!DOCTYPE html>
     <head>
       <meta charset="UTF-8">
       <link href='https://fonts.googleapis.com/css?family=Pacifico' rel='stylesheet' type='text/css'>
     <link href='https://fonts.googleapis.com/css?family=Arimo' rel='stylesheet' type='text/css'>
     <link href='https://fonts.googleapis.com/css?family=Hind:300' rel='stylesheet' type='text/css'>
     <link href='https://fonts.googleapis.com/css?family=Open+Sans+Condensed:300' rel='stylesheet' type='text/css'>
     <link rel="stylesheet" href="{{ url_for('static', filename='css/style.css') }}">
     </head>
     <body>
      <div class="login">
         <h1>Predict House Price</h1>
18
          <!-- Main Input For Receiving Overy to our ML -->
          <form action="{{ url_for('predict')}}" method="post">
19
             <input type="text" name="Bedrooms" placeholder="Number of Bedrooms" required="required" />
             <input type="text" name="Bathrooms" placeholder="Number of Bathrooms" required="required" />
              <input type="text" name="Floor Area(ft2)" placeholder="Floor Area(ft2)" required="required" />
             <input type="text" name="Council Tax Band" placeholder="Council Tax Band" required="required" />
             <button type="submit" class="btn btn-primary btn-block btn-large">Predict</button>
         </form>
        <hr>
29
30
        {{ prediction_text }}
```

6. Model Deployment

```
import numpy as np
       from flask import Flask, request, render_template
       import pickle
       app = Flask(__name__)
       model = pickle.load(open('lr_model.pkl', 'rb'))
       @app.route('/')
9
10
       def home():
         return render_template('index.html')
13
       2 usages (2 dynamic)
14
       @app.route( rule: '/predict', methods=['POST'])
       def predict():
16
          For rendering results on HTML GUI
18
19
          int_features = [int(x) for x in request.form.values()]
          final_features = [np.array(int_features)]
         prediction = model.predict(final_features)
         output = round(prediction[0], 2)
          return render_template( template_name_or_list: 'index.html', prediction_text='House price should be £ {}'.format(output))
26
28 🗅
      if __name__ == "__main__":
       app.run(debug=True)
```

7. Model Testing

