Participatory Systems let users decide

which data is used for predictions

and can improve



fairness, privacy & performance.



Repo

Paper

Participatory Systems for Personalized Prediction

Hailey Joren
Chirag Nagpal

UC San Diego Carnegie Mellon University Katherine Heller Google
Berk Ustun UC San Diego

Predictive systems use personal information to improve predictions

65-74 +1 ≥75 +2 <65 0 Male 0 Female +1 Sex **CHF** history No 0 Yes +1 No 0 Hypertension history Yes +1 Stroke/TIA/thromboembolism history No 0 Yes +2 Vascular disease history (prior MI, peripheral No 0 Yes +1 artery disease, or aortic plaque) Diabetes history No 0 Yes +1

- require info like sex and age to make a prediction (e.g., CHA₂DS₂-VASc Score for Stroke Risk)
- These are included in model training to provide better predictions across heterogeneous groups

Using a predictive system that requires personal information may not improve performance and can lead to worse predictions

Group Attributes		<u>n</u>	Error Personalized	Error Generic	Gain
age	sex	1156	19.4%	20.4%	+1.0%
age < 30	female	48	26.8%	38.1%	+11.3%
age < 30	male	49	26.7%	23.9%	-2.8%
age 30-60	female	304	29.1%	30.3%	+1.2%
age 30-60	male	447	15.2%	15.4%	+0.2%
age > 60	female	123	21.9%	19.3%	-2.6%
age > 60	male	181	8.2%	11.0%	+2.8%

Why is this bad?

- The personal info can be costly or sensitive providing it should always improve performance.
- In some cases, users are getting a worse prediction because they provided personal info

We apply participatory systems to 6 real-world healthcare prediction problems and find benefits for fairness, privacy, and performance


Case Study: ICU Mortality Prediction

	Logistic Regression	Minimal	Flat	Sequential
Test AUC	0.877	0.875	0.960	0.960
Groups Harmed	2	0	0	0
Max Gain / Group	0.019	0.015	0.139	0.139


- Participatory systems achieve the best overall and group-level performance on 6/6 datasets
- The number of groups harmed by the original system is reduced in participatory systems
- The participatory systems do not solicit data when the performance gain does not pass a hypothesis test

We present a model-agnostic approach that uses multiple models to let users decide when to provide personal information

Minimal



Flat



Sequential

