

Ordinary Differential Equations

as an alternative to agent-based modelling


eX Modelo school

OpenMOLE


June 26, 2019

ODE systems


→ widely used to model transmission phenomena



- ▶ population split into compartments
- ▶ system of ordinary differential equations



$$\left\{ \begin{array}{l} \frac{dS}{dt} = -\beta S + \lambda I \\ \frac{dI}{dt} = \beta S - (\lambda + \gamma) I \\ \frac{dR}{dt} = \gamma I \end{array} \right.$$



ODE

Equation-based

Generic mechanisms

Population scale

Needs less resources

ABM

Individual-based

Precise mechanisms

Individual scale

Computationally expensive

A Zombie situation

How could we model the Zombie invasion?


- ▶ Which mechanisms?
- ▶ Which parameters?


How could we model the Zombie invasion?

- ▶ Which mechanisms?
- ▶ Which parameters?

How can we assess our model's ability to reproduce the real data?

- ▶ Which metrics?
- ▶ Which fitness function?






$$\left\{ \begin{array}{l}
 \frac{dH_{walk}}{dt} = -(panic + inf) * H_{walk} + exhaustH * H_{run} \\
 \frac{dH_{run}}{dt} = panic * H_{walk} - (exhaustH + inf) * H_{run} \\
 \frac{dZ_{walk}}{dt} = inf * (H_{walk} + H_{run}) - hunt * Z_{walk} + exhaustZ * Z_{run} \\
 \frac{dZ_{run}}{dt} = hunt * Z_{walk} - exhaustZ * Z_{run}
 \end{array} \right.$$

$$\left\{ \begin{array}{lcl} N & = & H_{walk} + H_{run} + Z_{walk} + Z_{run} \\ panic & = & panic_0 * (Z_{walk} + Z_{run}) / N \\ hunt & = & hunt_0 * (H_{walk} + H_{run}) / N \end{array} \right.$$

Exploration

We have some real time series of zombie invasion
→ find the parameter values to best fit them

We have some real time series of zombie invasion
→ find the parameter values to best fit them





Process

Process

- ▶ Embed the model in OpenMOLE

Process


- ▶ Embed the model in OpenMOLE
- ▶ Define a fitness function

Process

- ▶ Embed the model in OpenMOLE
- ▶ Define a fitness function
- ▶ Write a calibration task


Parameter set


$panic_0$	7.25
$stamina_H$	0.99
$hunt_0$	10.15
$stamina_Z$	1.28
inf	0.02
fitness	780 394





Profiles for each of the 5 parameters:


rightarrow $panic_0$, $stamina_H$, $hunt_0$, $stamina_Z$, inf_0











Adding complexity

What mechanisms could we add to better represent the complexity of our Zombie situation?

What mechanisms could we add to better represent the complexity of our Zombie situation?

The parcimony issue

What mechanisms could we add to better represent the complexity of our Zombie situation?

The parcimony issue

- ▶ Do the new mechanisms really improve the fitness?

What mechanisms could we add to better represent the complexity of our Zombie situation?

The parcimony issue

- ▶ Do the new mechanisms really improve the fitness?
- ▶ Do we need them all?

What mechanisms could we add to better represent the complexity of our Zombie situation?

The parcimony issue

- ▶ Do the new mechanisms really improve the fitness?
- ▶ Do we need them all?
- ▶ What are the best combinations?

Process


- ▶ Embed the model in OpenMOLE **DONE**

Process


- ▶ Embed the model in OpenMOLE **DONE**
- ▶ Define a **second** fitness function

Process


- ▶ Embed the model in OpenMOLE **DONE**
- ▶ Define a **second** fitness function
- ▶ **Modify** the calibration task




Dynamics for 0 mechanism activated




Dynamics for 1 mechanism activated



Dynamics for 2 mechanisms activated



Dynamics for 3 mechanisms activated



Some mathematics

Recall the ODE system:

$$\left\{ \begin{array}{lcl} \frac{dH_{walk}}{dt} & = & -(panic0 * \frac{Z_{walk} + Z_{run}}{N} + inf) * H_{walk} + exhaustH * H_{run} \\ \frac{dH_{run}}{dt} & = & panic0 * \frac{Z_{walk} + Z_{run}}{N} * H_{walk} - (exhaustH + inf) * H_{run} \\ \frac{dZ_{walk}}{dt} & = & inf * (H_{walk} + H_{run}) - hunt0 * \frac{H_{walk} + H_{run}}{N} * Z_{walk} + exhaustZ * Z_{run} \\ \frac{dZ_{run}}{dt} & = & hunt0 * \frac{H_{walk} + H_{run}}{N} * Z_{walk} - exhaustZ * Z_{run} \end{array} \right.$$

Where $N := H_{walk} + H_{run} + Z_{walk} + Z_{run}$

First-order **nonlinear** (autonomous) ordinary differential equation... a priori no explicit solution, hence numerical solutions.

Let's note $X(t) := (H_{walk}(t), H_{run}(t), Z_{walk}(t), Z_{run}(t))$

We have the following Cauchy problem:

$$\begin{cases} X'(t) &= F(X(t)) \\ X(0) &= (x_0, y_0, z_0, w_0) \quad \text{initial condition} \end{cases}$$

where

$$(x_0, y_0, z_0, w_0) \in \mathbb{R}_+^*$$

and

$$\begin{aligned} F : \mathbb{R}^4 &\rightarrow \mathbb{R}^4 \\ (x, y, z, w) &\mapsto F(x, y, z, w) := ((panic0 * \frac{z + w}{x + y + z + w} + inf) * x + exhaustH * y, \\ &\quad \dots, \dots, \dots) \end{aligned}$$

Cauchy-Lipschitz theorem: Existence and uniqueness to a solution of the Cauchy problem.

Summing the 4 equations, we have:

$$\frac{dN}{dt} = \frac{dH_{walk}}{dt} + \frac{dH_{run}}{dt} + \frac{dZ_{walk}}{dt} + \frac{dZ_{run}}{dt} = 0$$

So $N(t)$ is constant:

$$N(t) = N(0), \text{ for all } t.$$

We find back that the population size (human + zombies) is constant: natural !

Let's note $H := H_{walk} + H_{run}$

Summing the first equations, we have:

$$\frac{dH}{dt} = \frac{dH_{walk}}{dt} + \frac{dH_{run}}{dt} = -inf * (H_{walk}(t) + H_{run}(t)) = -inf * H(t)$$

First-order linear ordinary differential equation with constant coefficient: explicit solution !

$$H(t) = H(0) * e^{-inf * t}$$

Likewise,

$$Z(t) := Z_{walk} + Z_{run} = N - H(t)$$

Definition: The point $x \in \mathbb{R}^4$ is an *equilibrium point* for the differential equation $X' = F(X)$ if $F(X) = 0$.

Here, there is a unique equilibrium point: $(0, 0, 0, N(0))$: all the population is composed of walking zombies.

Theses 2 facts :

- ▶ $N(t)$ constant
- ▶ solutions for H and Z
... are still valid for the system with additional mechanism.

→ Not able to change the shape of the solutions of the equation of H and Z with such system modifications.