Layered Components Report

Helga Gaona 2 October 2026

Site Details

My live layered components page is at https://helgagaona.github.io/wdd331-portfolio/unit-2/layered-components/index.html and the source code is at https://github.com/helgagaona/wdd331-portfolio.

Reflections

Layer Declaration with Vendor CSS

1. reset - This layer has basic styles that make all the browsers start from the same place like removing default margins. It goes first because it is the starting point and everything else builds on top of this so nothing here would ever override the actual design choices contained in other layers.

2. base - This layer contains the core element styles like body, headings, links, etc and the design tokens like color, spacing and fonts. It comes after reset because the styles should win over the reset but still let later layers override them.

3. vendor - This layer holds the third-party library's styles. It will be layered above base so the library's defaults have priority over the base styles but over components (next layer) so that we can still customize things if we need it.

4. components - This layer is where our own component styles like buttons, cards, navigation bars, etc will go. This is the last layer because the custom styles should always win.

:is() vs :where()

Both do the same job since they both let you write one selector instead of repeating. The only real difference is specificity.

:is() takes on the weight of the strongest argument while :where() always has zero specificity without caring what's inside it. :where() is better for base styles and :is() is useful when wanting the grouped selector to stick around and win against other rules.

In a project where I'm writing the base element styles I would use :where() because any component class can override them without needing extra weight or !important.

Rethinking Unit 1

I would definitely split code into separate files and layer them. I would rename my tokens for clarity, and would move component classes out of the main file because the code can get very messy so they exist in their own file making it much easier to find and edit if needed.