

Dynamic Programming

Christian Wulff-Nilsen
Fourth lecture
Algorithms and Data Structures
DIKU

February 15, 2023

Overview for today

- Introduction:

Overview for today

- Introduction:
 - Computing Fibonacci numbers

Overview for today

- Introduction:
 - Computing Fibonacci numbers
 - What is dynamic programming?

Overview for today

- Introduction:
 - Computing Fibonacci numbers
 - What is dynamic programming?
- Rod cutting

Overview for today

- Introduction:
 - Computing Fibonacci numbers
 - What is dynamic programming?
- Rod cutting
- Longest common subsequence

Computing Fibonacci numbers

- The Fibonacci numbers F_0, F_1, \dots are defined by the recurrence:

$$F_0 = 0,$$

$$F_1 = 1,$$

$$F_n = F_{n-1} + F_{n-2} \text{ for } n \geq 2.$$

Computing Fibonacci numbers

- The Fibonacci numbers F_0, F_1, \dots are defined by the recurrence:

$$F_0 = 0,$$

$$F_1 = 1,$$

$$F_n = F_{n-1} + F_{n-2} \text{ for } n \geq 2.$$

- How fast can we compute the n th Fibonacci number $F_n, n \geq 0$?

Computing Fibonacci numbers

- The Fibonacci numbers F_0, F_1, \dots are defined by the recurrence:

$$F_0 = 0,$$

$$F_1 = 1,$$

$$F_n = F_{n-1} + F_{n-2} \text{ for } n \geq 2.$$

- How fast can we compute the n th Fibonacci number $F_n, n \geq 0$?
- Simple algorithm (assume input $n \in \mathbb{N}_0$):


FIB(n)

1 if $n \leq 1$ return n

2 else return **FIB**($n - 1$) + **FIB**($n - 2$)


Subproblems solved for F_4

- Recursive calls executed by $\text{FIB}(4)$:



Subproblems solved for F_4

- Recursive calls executed by $\text{FIB}(4)$:



- Note that subproblem F_2 is solved twice.
- This overlap in subproblems gets much worse when computing bigger Fibonacci numbers.

Computing Fibonacci numbers

- Algorithm FIB recomputes many identical subproblems over and over.

Computing Fibonacci numbers

- Algorithm FIB recomputes many identical subproblems over and over.
- It can be shown to have $\Theta(1, 618^n)$ running time.

Computing Fibonacci numbers

- Algorithm FIB recomputes many identical subproblems over and over.
- It can be shown to have $\Theta(1, 618^n)$ running time.
- Can we do better?

Computing Fibonacci numbers

- Consider a different algorithm FIBFAST to find $F(n)$.

Computing Fibonacci numbers

- Consider a different algorithm FIBFAST to find $F(n)$.
- Initialize an array $F[0 \dots n]$ where $F[0] = 0$, $F[1] = 1$, and $F[i] = -1$ for $2 \leq i \leq n$.

Computing Fibonacci numbers

- Consider a different algorithm FIBFAST to find $F(n)$.
- Initialize an array $F[0 \dots n]$ where $F[0] = 0$, $F[1] = 1$, and $F[i] = -1$ for $2 \leq i \leq n$.
- Then make the call $\text{FIBFAST}(n, F)$, where:

```
FIBFAST( $m, F$ )  
1  if  $F[m] < 0$   
2     $F[m] = \text{FIBFAST}(m - 1, F) + \text{FIBFAST}(m - 2, F)$   
3  return  $F[m]$ 
```

Computing Fibonacci numbers

FIBFAST(m, F)

1 if $F[m] < 0$

2 $F[m] = \text{FIBFAST}(m - 1, F) + \text{FIBFAST}(m - 2, F)$

3 return $F[m]$

- Recursive calls executed by FIBFAST(4, F):

Computing Fibonacci numbers


$\text{FIBFAST}(m, F)$

1 if $F[m] < 0$

2 $F[m] = \text{FIBFAST}(m - 1, F) + \text{FIBFAST}(m - 2, F)$

3 return $F[m]$

- Recursive calls executed by $\text{FIBFAST}(4, F)$:



Computing Fibonacci numbers

FIBFAST(m, F)

1 if $F[m] < 0$

2 $F[m] = \text{FIBFAST}(m - 1, F) + \text{FIBFAST}(m - 2, F)$

3 return $F[m]$

- Recursive calls executed by FIBFAST($4, F$):
- FIBFAST(n, S) runs in $\Theta(n)$ time since we execute line 2 only once for each m between 2 and n .

Computing Fibonacci numbers

FIBFAST(m, F)

1 if $F[m] < 0$

2 $F[m] = \text{FIBFAST}(m - 1, F) + \text{FIBFAST}(m - 2, F)$

3 return $F[m]$

- Recursive calls executed by FIBFAST($4, F$):
- FIBFAST(n, S) runs in $\Theta(n)$ time since we execute line 2 only once for each m between 2 and n .
- Technical detail:
 - Assumes addition of big $\Theta(n)$ -bit numbers can be done in constant time

Computing Fibonacci numbers

FIBFAST(m, F)

1 if $F[m] < 0$

2 $F[m] = \text{FIBFAST}(m - 1, F) + \text{FIBFAST}(m - 2, F)$

3 return $F[m]$

- Recursive calls executed by FIBFAST(4, F):
- FIBFAST(n, S) runs in $\Theta(n)$ time since we execute line 2 only once for each m between 2 and n .
- Technical detail:
 - Assumes addition of big $\Theta(n)$ -bit numbers can be done in constant time
 - Without this assumption, the running time becomes $\Theta(n^2 / \lg n)$ since a $\Theta(n)$ -bit number can be stored in $\Theta(n / \lg n)$ words, allowing for an addition to be computed in $\Theta(n / \lg n)$ time.

Dynamic programming

- FIBFAST is an example of dynamic programming.

Dynamic programming

- FIBFAST is an example of dynamic programming.
- The idea of DP is to avoid recomputing identical subproblems.

Dynamic programming

- FIBFAST is an example of dynamic programming.
- The idea of DP is to avoid recomputing identical subproblems.
- This is done by storing the solution to a subproblem in a table.

Dynamic programming

- FIBFAST is an example of dynamic programming.
- The idea of DP is to avoid recomputing identical subproblems.
- This is done by storing the solution to a subproblem in a table.
- If that subproblem is encountered again, there is no need to recompute it as a simple table look-up will give the solution.

Dynamic programming

- We follow four steps when developing a DP algorithm:

Dynamic programming

- We follow four steps when developing a DP algorithm:
 - Characterize the structure of an optimal solution in terms of optimal solutions to subproblems (*optimal substructure*).

Dynamic programming

- We follow four steps when developing a DP algorithm:
 - Characterize the structure of an optimal solution in terms of optimal solutions to subproblems (*optimal substructure*).
 - Recursively define the value of an optimal solution.

Dynamic programming

- We follow four steps when developing a DP algorithm:
 - Characterize the structure of an optimal solution in terms of optimal solutions to subproblems (*optimal substructure*).
 - Recursively define the value of an optimal solution.
 - Compute the value of an optimal solution using, e.g., recursion.

Dynamic programming

- We follow four steps when developing a DP algorithm:
 - Characterize the structure of an optimal solution in terms of optimal solutions to subproblems (*optimal substructure*).
 - Recursively define the value of an optimal solution.
 - Compute the value of an optimal solution using, e.g., recursion.
 - Construct optimal solution from computed information.

Dynamic programming

- We follow four steps when developing a DP algorithm:
 - Characterize the structure of an optimal solution in terms of optimal solutions to subproblems (*optimal substructure*).
 - Recursively define the value of an optimal solution.
 - Compute the value of an optimal solution using, e.g., recursion.
 - Construct optimal solution from computed information.
- For dynamic programming to be useful, we need *overlapping subproblems* (the same subproblems are visited repeatedly).

The rod cutting problem

- Suppose we are given a rod R of length n .

The rod cutting problem

- Suppose we are given a rod R of length n .
- We want to cut R up into pieces of certain lengths and sell these pieces.

The rod cutting problem

- Suppose we are given a rod R of length n .
- We want to cut R up into pieces of certain lengths and sell these pieces.
- A piece of length i earns us p_i kr., where $i \in \{1, \dots, n\}$.

The rod cutting problem

- Suppose we are given a rod R of length n .
- We want to cut R up into pieces of certain lengths and sell these pieces.
- A piece of length i earns us p_i kr., where $i \in \{1, \dots, n\}$.
- There is no cost in cutting R .

The rod cutting problem


- Suppose we are given a rod R of length n .
- We want to cut R up into pieces of certain lengths and sell these pieces.
- A piece of length i earns us p_i kr., where $i \in \{1, \dots, n\}$.
- There is no cost in cutting R .
- What is the maximum revenue r_n that we can obtain?

The rod cutting problem

- Suppose we are given a rod R of length n .
- We want to cut R up into pieces of certain lengths and sell these pieces.
- A piece of length i earns us p_i kr., where $i \in \{1, \dots, n\}$.
- There is no cost in cutting R .
- What is the maximum revenue r_n that we can obtain?
- The input to an algorithm for the rod cutting problem is the rod length n and prices p_1, p_2, \dots, p_n .


The rod cutting problem

- Example (numbers are prices):




The rod cutting problem

- Example (numbers are prices):




The rod cutting problem

- Example (numbers are prices):




The rod cutting problem

- Example (numbers are prices):




The rod cutting problem

- Example (numbers are prices):





The rod cutting problem

- Example (numbers are prices):




The rod cutting problem

- Example (numbers are prices):




The rod cutting problem

- Example (numbers are prices):




The rod cutting problem

- Example (numbers are prices):



The rod cutting problem

- Example (numbers are prices):



Naive algorithm

- Try all ways of cutting up R .

Naive algorithm

- Try all ways of cutting up R .
- Pick one giving the maximum revenue.

Naive algorithm

- Try all ways of cutting up R .
- Pick one giving the maximum revenue.
- There are 2^{n-1} ways of cutting up R .

Naive algorithm


- Try all ways of cutting up R .
- Pick one giving the maximum revenue.
- There are 2^{n-1} ways of cutting up R .
- Hence, this algorithm runs in exponential time.

Naive algorithm

- Try all ways of cutting up R .
- Pick one giving the maximum revenue.
- There are 2^{n-1} ways of cutting up R .
- Hence, this algorithm runs in exponential time.
- We will give a much faster algorithm that uses dynamic programming.


Characterizing the structure of an optimal solution

- Suppose someone told us one of the cuts of R in an optimal solution OPT for R (OPT consists of green cuts with the given cut highlighted):



Characterizing the structure of an optimal solution


- Suppose someone told us one of the cuts of R in an optimal solution OPT for R (OPT consists of green cuts with the given cut highlighted):



- This cut of OPT partitions R into two smaller rods R_1 and R_2 , one of some length i , the other of length $n - i$.

Characterizing the structure of an optimal solution


- Suppose someone told us one of the cuts of R in an optimal solution OPT for R (OPT consists of green cuts with the given cut highlighted):



- This cut of OPT partitions R into two smaller rods R_1 and R_2 , one of some length i , the other of length $n - i$.
- Restricting OPT to R_1 gives an optimal solution to R_1 . (why?)

Characterizing the structure of an optimal solution

- Suppose someone told us one of the cuts of R in an optimal solution OPT for R (OPT consists of green cuts with the given cut highlighted):




- This cut of OPT partitions R into two smaller rods R_1 and R_2 , one of some length i , the other of length $n - i$.
- Restricting OPT to R_1 gives an optimal solution to R_1 . (why?)
- Similarly, restricting OPT to R_2 gives an optimal solution to R_2 . (why?)

Characterizing the structure of an optimal solution

- It follows that the rod cutting problem exhibits optimal substructure:
 - An optimal solution to the whole problem consists of optimal solutions to subproblems which can be solved independently.

Characterizing the structure of an optimal solution

- It follows that the rod cutting problem exhibits optimal substructure:
 - An optimal solution to the whole problem consists of optimal solutions to subproblems which can be solved independently.
- From the previous slide, solving the rod cutting problem separately for R_1 and for R_2 gives an optimal solution for R as the union of the optimal solutions for the two subproblems:



Characterizing the solution recursively

- Recall: r_n is the maximum revenue we can get from a rod of length n .

Characterizing the solution recursively

- Recall: r_n is the maximum revenue we can get from a rod of length n .
- From the previous slides, there is an i with $1 \leq i \leq n - 1$ such that:

$$r_n = r_i + r_{n-i}.$$

Characterizing the solution recursively

- Recall: r_n is the maximum revenue we can get from a rod of length n .
- From the previous slides, there is an i with $1 \leq i \leq n - 1$ such that:

$$r_n = r_i + r_{n-i}.$$

- However, we do not know i ; this value was given to us by someone.

Characterizing the solution recursively

- Recall: r_n is the maximum revenue we can get from a rod of length n .
- From the previous slides, there is an i with $1 \leq i \leq n - 1$ such that:

$$r_n = r_i + r_{n-i}.$$

- However, we do not know i ; this value was given to us by someone.
- We also need to handle the case where R should not be cut at all in an optimal solution.

Characterizing the solution recursively

- Recall: r_n is the maximum revenue we can get from a rod of length n .
- From the previous slides, there is an i with $1 \leq i \leq n - 1$ such that:


$$r_n = r_i + r_{n-i}.$$

- However, we do not know i ; this value was given to us by someone.
- We also need to handle the case where R should not be cut at all in an optimal solution.
- Since our goal is to maximize revenue, we thus get:

$$r_n = \max\{p_n, r_1 + r_{n-1}, r_2 + r_{n-2}, \dots, r_{n-1} + r_1\}.$$


A simpler formulation

- Instead of someone giving us an *arbitrary* cut in an optimal solution, suppose instead we are given the *first* cut from left to right.



A simpler formulation

- Instead of someone giving us an *arbitrary* cut in an optimal solution, suppose instead we are given the *first* cut from left to right.



- If the left side of this cut has length i ,

$$r_n = p_i + r_{n-i}.$$

A simpler formulation

- We have shown that

$$r_n = p_i + r_{n-i}.$$

A simpler formulation

- We have shown that

$$r_n = p_i + r_{n-i}.$$

- Now r_n depends on only one related subproblem instead of two.

A simpler formulation

- We have shown that

$$r_n = p_i + r_{n-i}.$$

- Now r_n depends on only one related subproblem instead of two.
- Since we do not know i or whether R should be cut at all, we get

$$r_n = \max_{1 \leq i \leq n} \{p_i + r_{n-i}\},$$

where we define $r_0 = 0$.

A recursive algorithm to compute r_n

- We saw that

$$r_n = \max_{1 \leq i \leq n} \{p_i + r_{n-i}\}.$$

A recursive algorithm to compute r_n

- We saw that

$$r_n = \max_{1 \leq i \leq n} \{p_i + r_{n-i}\}.$$

- This suggests the following recursive algorithm:

CUT-ROD(p, n)

1 if $n == 0$ return 0

2 $q = -\infty$

3 for $i = 1$ to n

4 $q = \max\{q, p[i] + \text{CUT-ROD}(p, n - i)\}$

5 return q

- Here p is an array of length n where $p[i] = p_i$.

Running time of CUT-ROD

- CUT-ROD tries all ways of partitioning the rod:

CUT-ROD(p, n)

1 if $n == 0$ return 0

2 $q = -\infty$

3 for $i = 1$ to n

4 $q = \max\{q, p[i] + \text{CUT-ROD}(p, n - i)\}$

5 return q

Running time of CUT-ROD

- CUT-ROD tries all ways of partitioning the rod:

CUT-ROD(p, n)

1 if $n == 0$ return 0

2 $q = -\infty$

3 for $i = 1$ to n

4 $q = \max\{q, p[i] + \text{CUT-ROD}(p, n - i)\}$

5 return q

- There are 2^{n-1} ways of doing this.

Running time of CUT-ROD

- CUT-ROD tries all ways of partitioning the rod:

CUT-ROD(p, n)

1 if $n == 0$ return 0

2 $q = -\infty$

3 for $i = 1$ to n

4 $q = \max\{q, p[i] + \text{CUT-ROD}(p, n - i)\}$

5 return q

- There are 2^{n-1} ways of doing this.
- Hence, CUT-ROD runs in exponential time.

Running time of CUT-ROD

- CUT-ROD tries all ways of partitioning the rod:

CUT-ROD(p, n)

1 if $n == 0$ return 0

2 $q = -\infty$

3 for $i = 1$ to n

4 $q = \max\{q, p[i] + \text{CUT-ROD}(p, n - i)\}$

5 return q

- There are 2^{n-1} ways of doing this.
- Hence, CUT-ROD runs in exponential time.
- We will improve this to $\Theta(n^2)$ time using DP.

Memoization: a top-down approach

- We solve the problem top-down using recursion.

Memoization: a top-down approach

- We solve the problem top-down using recursion.
- When a subproblem is solved, it is *memoized*, i.e., it is “remembered”/stored in memory.

Memoization: a top-down approach

- We solve the problem top-down using recursion.
- When a subproblem is solved, it is *memoized*, i.e., it is “remembered”/stored in memory.
- If a memoized subproblem is encountered, it is not solved again but simply looked up.

Solving rod-cutting using memoization

- Initialize an array $r[0 \dots n]$ where each $r[i] = -\infty$.

Solving rod-cutting using memoization

- Initialize an array $r[0 \dots n]$ where each $r[i] = -\infty$.
- We solve the rod cutting problem with the call $\text{MEM-CUT-ROD}(p, n, r)$, where:

```
MEM-CUT-ROD( $p, m, r$ )
1  if  $r[m] \geq 0$  then return  $r[m]$ 
2  if  $m == 0$  then  $q = 0$ 
3  else
4       $q = -\infty$ 
5      for  $i = 1$  to  $m$ 
6           $q = \max\{q, p[i] + \text{MEM-CUT-ROD}(p, m - i, r)\}$ 
7   $r[m] = q$ 
8  return  $q$ 
```


Running time of MEM-CUT-ROD

```
MEM-CUT-ROD( $p, m, r$ )
1  if  $r[m] \geq 0$  then return  $r[m]$ 
2  if  $m == 0$  then  $q = 0$ 
3  else
4       $q = -\infty$ 
5      for  $i = 1$  to  $m$ 
6           $q = \max\{q, p[i] + \text{MEM-CUT-ROD}(p, m - i, r)\}$ 
7   $r[m] = q$ 
8  return  $q$ 
```

- Over *all* recursive calls, lines 2–8 are executed only once for each $m \in \{0, 1, \dots, n\}$, for a total of $n + 1$ times.

Running time of MEM-CUT-ROD

```
MEM-CUT-ROD( $p, m, r$ )
1  if  $r[m] \geq 0$  then return  $r[m]$ 
2  if  $m == 0$  then  $q = 0$ 
3  else
4       $q = -\infty$ 
5      for  $i = 1$  to  $m$ 
6           $q = \max\{q, p[i] + \text{MEM-CUT-ROD}(p, m - i, r)\}$ 
7   $r[m] = q$ 
8  return  $q$ 
```

- Over *all* recursive calls, lines 2–8 are executed only once for each $m \in \{0, 1, \dots, n\}$, for a total of $n + 1$ times.
- Executing these lines once takes $O(n)$ time, excluding the time spent in recursive calls in line 6.

Running time of MEM-CUT-ROD

MEM-CUT-ROD(p, m, r)

1 if $r[m] \geq 0$ then return $r[m]$

2 if $m == 0$ then $q = 0$

3 else

4 $q = -\infty$

5 for $i = 1$ to m

6 $q = \max\{q, p[i] + \text{MEM-CUT-ROD}(p, m - i, r)\}$

7 $r[m] = q$

8 return q



- Over *all* recursive calls, lines 2–8 are executed only once for each $m \in \{0, 1, \dots, n\}$, for a total of $n + 1$ times.



- Executing these lines once takes $O(n)$ time, excluding the time spent in recursive calls in line 6.



- This gives a total running time of $\Theta(n^2)$.

A bottom-up approach

- Memoization solves a problem top-down.

A bottom-up approach

- Memoization solves a problem top-down.
- We can also solve a problem bottom-up with DP.

A bottom-up approach

- Memoization solves a problem top-down.
- We can also solve a problem bottom-up with DP.
- The idea is to sort subproblems by increasing “size”.

A bottom-up approach

- Memoization solves a problem top-down.
- We can also solve a problem bottom-up with DP.
- The idea is to sort subproblems by increasing “size”.
- Then these subproblems are solved in this order and their solutions are stored.

A bottom-up approach

- Memoization solves a problem top-down.
- We can also solve a problem bottom-up with DP.
- The idea is to sort subproblems by increasing “size”.
- Then these subproblems are solved in this order and their solutions are stored.
- When solving a particular subproblem, the smaller subproblems that its solution depends on have already been solved.

A bottom-up approach

- Memoization solves a problem top-down.
- We can also solve a problem bottom-up with DP.
- The idea is to sort subproblems by increasing “size”.
- Then these subproblems are solved in this order and their solutions are stored.
- When solving a particular subproblem, the smaller subproblems that its solution depends on have already been solved.
- Hence, we do not need any recursion, only look-ups.

Solving rod-cutting bottom-up

- The following algorithm solves the problem bottom-up:

BOTTOM-UP-CUT-ROD(p, n)

```
1 let  $r[0 \dots n]$  be a new array
2  $r[0] = 0$ 
3 for  $j = 1$  to  $n$ 
4    $q = -\infty$ 
5   for  $i = 1$  to  $j$ 
6      $q = \max\{q, p[i] + r[j - i]\}$ 
7    $r[j] = q$ 
8 return  $r[n]$ 
```

Running time of BOTTOM-UP-CUT-ROD

```
BOTTOM-UP-CUT-ROD( $p, n$ )
1  let  $r[0 \dots n]$  be a new array
2   $r[0] = 0$ 
3  for  $j = 1$  to  $n$ 
4       $q = -\infty$ 
5      for  $i = 1$  to  $j$ 
6           $q = \max\{q, p[i] + r[j - i]\}$ 
7       $r[j] = q$ 
8  return  $r[n]$ 
```

- There are n iterations of the for-loop in lines 3–7.

Running time of BOTTOM-UP-CUT-ROD

```
BOTTOM-UP-CUT-ROD( $p, n$ )
1  let  $r[0 \dots n]$  be a new array
2   $r[0] = 0$ 
3  for  $j = 1$  to  $n$ 
4       $q = -\infty$ 
5      for  $i = 1$  to  $j$ 
6           $q = \max\{q, p[i] + r[j - i]\}$ 
7       $r[j] = q$ 
8  return  $r[n]$ 
```

- There are n iterations of the for-loop in lines 3–7.
- For each of these iterations, there are at most n iterations of the for-loop in lines 5–6.

Running time of BOTTOM-UP-CUT-ROD

BOTTOM-UP-CUT-ROD(p, n)

1 let $r[0 \dots n]$ be a new array

2 $r[0] = 0$

→ 3 for $j = 1$ to n

4 $q = -\infty$

5 → for $i = 1$ to j

6 $q = \max\{q, p[i] + r[j - i]\}$

7 $r[j] = q$

8 return $r[n]$

- There are n iterations of the for-loop in lines 3–7.
- For each of these iterations, there are at most n iterations of the for-loop in lines 5–6.
- Total running time: $\Theta(n^2)$.

Pros and cons of the two types of DP

- Bottom-up DP:

Pros and cons of the two types of DP

- Bottom-up DP:
 - Has the advantage of avoiding recursion.

Pros and cons of the two types of DP

- Bottom-up DP:
 - Has the advantage of avoiding recursion.
 - For-loops typically give smaller constant factors in the running time.

Pros and cons of the two types of DP

- Bottom-up DP:
 - Has the advantage of avoiding recursion.
 - For-loops typically give smaller constant factors in the running time.
- Top-down DP with memoization:

Pros and cons of the two types of DP

- Bottom-up DP:
 - Has the advantage of avoiding recursion.
 - For-loops typically give smaller constant factors in the running time.
- Top-down DP with memoization:
 - Only solves the subproblems that are needed.

Pros and cons of the two types of DP

- Bottom-up DP:
 - Has the advantage of avoiding recursion.
 - For-loops typically give smaller constant factors in the running time.
- Top-down DP with memoization:
 - Only solves the subproblems that are needed.
 - This is different from bottom-up DP which solves all subproblems.

Pros and cons of the two types of DP

- Bottom-up DP:
 - Has the advantage of avoiding recursion.
 - For-loops typically give smaller constant factors in the running time.
- Top-down DP with memoization:
 - Only solves the subproblems that are needed.
 - This is different from bottom-up DP which solves all subproblems.
- Conclusion: whether to use bottom-up or top-down DP depends on the problem considered.

Finding a solution

- So far, we have only given algorithms that find the revenue r_n of an optimal solution to the rod-cutting problem.

Finding a solution

- So far, we have only given algorithms that find the revenue r_n of an optimal solution to the rod-cutting problem.
- We would also like to know the solution itself, i.e., how to cut the rod.

Finding a solution

- So far, we have only given algorithms that find the revenue r_n of an optimal solution to the rod-cutting problem.
- We would also like to know the solution itself, i.e., how to cut the rod.
- We do this by recording the choices made by the DP algorithm.

Finding a solution

- The following extension of BOTTOM-UP-CUT-ROD returns also an array $s[0 \dots n]$.

Finding a solution

- The following extension of BOTTOM-UP-CUT-ROD returns also an array $s[0 \dots n]$.
- $s[i]$ indicates where to make the first cut in a rod of length i :

Finding a solution

- The following extension of BOTTOM-UP-CUT-ROD returns also an array $s[0 \dots n]$.
- $s[i]$ indicates where to make the first cut in a rod of length i :

EXT-BOTTOM-UP-CUT-ROD(p, n)

```
1  let  $r[0 \dots n]$  and  $s[0 \dots n]$  be new arrays
2   $r[0] = 0$ 
3  for  $j = 1$  to  $n$ 
4       $q = -\infty$ 
5      for  $i = 1$  to  $j$ 
6          if  $q < p[i] + r[j - i]$ 
7               $q = p[i] + r[j - i]$ 
8               $s[j] = i$ 
9   $r[j] = q$ 
10 return  $r$  and  $s$ 
```

Using the s -array to find a solution


- Having computed the s -array with EXT-BOTTOM-UP-CUT-ROD, we can use s to find an optimal way of cutting up the rod:



Using the s -array to find a solution

- Having computed the s -array with EXT-BOTTOM-UP-CUT-ROD, we can use s to find an optimal way of cutting up the rod:


$$s[9] = 1$$



Using the s -array to find a solution

- Having computed the s -array with EXT-BOTTOM-UP-CUT-ROD, we can use s to find an optimal way of cutting up the rod:

$$s[8] = 2$$



Using the s -array to find a solution

- Having computed the s -array with EXT-BOTTOM-UP-CUT-ROD, we can use s to find an optimal way of cutting up the rod:


$$s[6] = 1$$



Using the s -array to find a solution

- Having computed the s -array with EXT-BOTTOM-UP-CUT-ROD, we can use s to find an optimal way of cutting up the rod:

$$s[5] = 3$$



Using the s -array to find a solution

- Having computed the s -array with EXT-BOTTOM-UP-CUT-ROD, we can use s to find an optimal way of cutting up the rod:

$$s[2] = 1$$



Comparing DNA strands

- The ability to compare DNA sequences is important in biology.

Comparing DNA strands

- The ability to compare DNA sequences is important in biology.
- A DNA strand can be represented by a sequence of letters from $\{A, C, G, T\}$.

Comparing DNA strands

- The ability to compare DNA sequences is important in biology.
- A DNA strand can be represented by a sequence of letters from $\{A, C, G, T\}$.
- Example:

$$S_1 = ACGCTAC \text{ and } S_2 = CTGACA.$$

Comparing DNA strands

- The ability to compare DNA sequences is important in biology.
- A DNA strand can be represented by a sequence of letters from $\{A, C, G, T\}$.
- Example:

$$S_1 = ACGCTAC \text{ and } S_2 = CTGACA.$$

- We want a measure for how similar S_1 and S_2 are.

Comparing DNA strands

- The ability to compare DNA sequences is important in biology.
- A DNA strand can be represented by a sequence of letters from $\{A, C, G, T\}$.
- Example:

$$S_1 = ACGCTAC \text{ and } S_2 = CTGACA.$$

- We want a measure for how similar S_1 and S_2 are.
- One measure is the length of a *longest common subsequence* (LCS).

Comparing DNA strands

- The ability to compare DNA sequences is important in biology.
- A DNA strand can be represented by a sequence of letters from $\{A, C, G, T\}$.
- Example:

$$S_1 = ACGCTAC \text{ and } S_2 = CTGACA.$$

- We want a measure for how similar S_1 and S_2 are.
- One measure is the length of a *longest common subsequence* (LCS).
- This is a longest string which is a subsequence of both S_1 and S_2 .

Comparing DNA strands

- The ability to compare DNA sequences is important in biology.
- A DNA strand can be represented by a sequence of letters from $\{A, C, G, T\}$.
- Example:

$$S_1 = ACGCTAC \text{ and } S_2 = CTGACA.$$

- We want a measure for how similar S_1 and S_2 are.
- One measure is the length of a *longest common subsequence* (LCS).
- This is a longest string which is a subsequence of both S_1 and S_2 .
- For the case above, an LCS of S_1 and S_2 is $CGCA$.

Comparing DNA strands

- The ability to compare DNA sequences is important in biology.
- A DNA strand can be represented by a sequence of letters from $\{A, C, G, T\}$.
- Example:

$$S_1 = ACGCTAC \text{ and } S_2 = CTGACA.$$

- We want a measure for how similar S_1 and S_2 are.
- One measure is the length of a *longest common subsequence* (LCS).
- This is a longest string which is a subsequence of both S_1 and S_2 .
- For the case above, an LCS of S_1 and S_2 is $CGCA$.
- Notation: $\text{LCS}(S_1, S_2)$ denotes some LCS of S_1 and S_2 .

The longest common subsequence problem

- We are given two sequences $X = \langle x_1, x_2, \dots, x_m \rangle$ and $Y = \langle y_1, y_2, \dots, y_n \rangle$.

The longest common subsequence problem

- We are given two sequences $X = \langle x_1, x_2, \dots, x_m \rangle$ and $Y = \langle y_1, y_2, \dots, y_n \rangle$.
- Goal: find $\text{LCS}(X, Y)$.

The longest common subsequence problem

- We are given two sequences $X = \langle x_1, x_2, \dots, x_m \rangle$ and $Y = \langle y_1, y_2, \dots, y_n \rangle$.
- Goal: find $\text{LCS}(X, Y)$.
- Notation used in the following:
 - Let $Z = \langle z_1, z_2, \dots, z_k \rangle = \text{LCS}(X, Y)$.

The longest common subsequence problem

- We are given two sequences $X = \langle x_1, x_2, \dots, x_m \rangle$ and $Y = \langle y_1, y_2, \dots, y_n \rangle$.
- Goal: find $\text{LCS}(X, Y)$.
- Notation used in the following:
 - Let $Z = \langle z_1, z_2, \dots, z_k \rangle = \text{LCS}(X, Y)$.
 - Denote by X_i the subsequence $\langle x_1, x_2, \dots, x_i \rangle$ of X .

The longest common subsequence problem

- We are given two sequences $X = \langle x_1, x_2, \dots, x_m \rangle$ and $Y = \langle y_1, y_2, \dots, y_n \rangle$.
- Goal: find $\text{LCS}(X, Y)$.
- Notation used in the following:
 - Let $Z = \langle z_1, z_2, \dots, z_k \rangle = \text{LCS}(X, Y)$.
 - Denote by X_i the subsequence $\langle x_1, x_2, \dots, x_i \rangle$ of X .
 - Define Y_i and Z_i similarly.

Optimal substructure

- We have the following optimal substructure:

Optimal substructure

- We have the following optimal substructure:

1. $x_m = y_n \Rightarrow z_k = x_m = y_n \wedge Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1}).$

Optimal substructure

- We have the following optimal substructure:
 1. $x_m = y_n \Rightarrow z_k = x_m = y_n \wedge Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.
 2. $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y)$.

Optimal substructure

- We have the following optimal substructure:
 1. $x_m = y_n \Rightarrow z_k = x_m = y_n \wedge Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.
 2. $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y)$.
 3. $x_m \neq y_n \wedge z_k \neq y_n \Rightarrow Z = \text{LCS}(X, Y_{n-1})$.

Optimal substructure

- We have the following optimal substructure:
 1. $x_m = y_n \Rightarrow z_k = x_m = y_n \wedge Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.
 2. $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y)$.
 3. $x_m \neq y_n \wedge z_k \neq y_n \Rightarrow Z = \text{LCS}(X, Y_{n-1})$.
- Example, case 1:

$X = ****A$

$Y = *****A$

$Z = ***A$

$X_{m-1} = ****$

$Y_{n-1} = *****$

$Z_{k-1} = ***$

Optimal substructure

- We have the following optimal substructure:
 1. $x_m = y_n \Rightarrow z_k = x_m = y_n \wedge Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.
 2. $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y)$.
 3. $x_m \neq y_n \wedge z_k \neq y_n \Rightarrow Z = \text{LCS}(X, Y_{n-1})$.
- Example, case 1:

$X = ****A$

$Y = *****A$

$Z = ***A$

$X_{m-1} = ****$

$Y_{n-1} = *****$

$Z_{k-1} = ***$

- Example, case 2:

$X = ****A$

$Y = *****B$

$Z = ***C$

$X_{m-1} = ****$

$Y = *****B$

$Z = ***C$

Optimal substructure

- We have the following optimal substructure:

1. $x_m = y_n \Rightarrow z_k = x_m = y_n \wedge Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.
2. $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y)$.
3. $x_m \neq y_n \wedge z_k \neq y_n \Rightarrow Z = \text{LCS}(X, Y_{n-1})$.

- Example, case 1:

$X = ****A$

$Y = *****A$

$Z = ***A$

$X_{m-1} = ****$

$Y_{n-1} = *****$

$Z_{k-1} = ***$

- Example, case 2:

$X = ****A$

$Y = *****B$

$Z = ***C$

$X_{m-1} = ****$

$Y = *****B$

$Z = ***C$

- We prove parts 1 and 2 (part 3 is symmetric to part 2).

Optimal substructure: proof of part 1

- We first show $x_m = y_n \Rightarrow z_k = x_m = y_n$.

Optimal substructure: proof of part 1

- We first show $x_m = y_n \Rightarrow z_k = x_m = y_n$.
- Assume for contradiction that $x_m = y_n$ but $z_k \neq x_m = y_n$.

Optimal substructure: proof of part 1

- We first show $x_m = y_n \Rightarrow z_k = x_m = y_n$.
- Assume for contradiction that $x_m = y_n$ but $z_k \neq x_m = y_n$.
- In words, Z does not match the last symbol x_m in X with the last symbol y_n in Y .

Optimal substructure: proof of part 1

- We first show $x_m = y_n \Rightarrow z_k = x_m = y_n$.
- Assume for contradiction that $x_m = y_n$ but $z_k \neq x_m = y_n$.
- In words, Z does not match the last symbol x_m in X with the last symbol y_n in Y .
- Example:

$$X = ****A$$

$$Y = *****A$$

$$Z = ***B$$

Optimal substructure: proof of part 1

- We first show $x_m = y_n \Rightarrow z_k = x_m = y_n$.
- Assume for contradiction that $x_m = y_n$ but $z_k \neq x_m = y_n$.
- In words, Z does not match the last symbol x_m in X with the last symbol y_n in Y .
- Example:

$$X = ****A$$

$$Y = *****A$$

$$Z = ***B$$

- But then Zx_m is a common subsequence of X and Y of length $|Z| + 1 > |Z|$, contradicting that $Z = \text{LCS}(X, Y)$.

Optimal substructure: proof of part 1

- We first show $x_m = y_n \Rightarrow z_k = x_m = y_n$.
- Assume for contradiction that $x_m = y_n$ but $z_k \neq x_m = y_n$.
- In words, Z does not match the last symbol x_m in X with the last symbol y_n in Y .
- Example:

$$X = ****A$$

$$Y = *****A$$

$$Z = ***B$$

- But then Zx_m is a common subsequence of X and Y of length $|Z| + 1 > |Z|$, contradicting that $Z = \text{LCS}(X, Y)$.
- For our example above, $Zx_m = ***BA$.

Optimal substructure: proof of part 1

- We first show $x_m = y_n \Rightarrow z_k = x_m = y_n$.
- Assume for contradiction that $x_m = y_n$ but $z_k \neq x_m = y_n$.
- In words, Z does not match the last symbol x_m in X with the last symbol y_n in Y .
- Example:

$$X = ****A$$

$$Y = *****A$$

$$Z = ***B$$

- But then Zx_m is a common subsequence of X and Y of length $|Z| + 1 > |Z|$, contradicting that $Z = \text{LCS}(X, Y)$.
- For our example above, $Zx_m = ***BA$.
- We conclude that $x_m = y_n \Rightarrow z_k = x_m = y_n$.

Optimal substructure: proof of part 1

- Next we show that $x_m = y_n \Rightarrow Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.

Optimal substructure: proof of part 1

- Next we show that $x_m = y_n \Rightarrow Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.
- Assume for contradiction that $x_m = y_n$ but that Z_{k-1} is not $\text{LCS}(X_{m-1}, Y_{n-1})$.

Optimal substructure: proof of part 1

- Next we show that $x_m = y_n \Rightarrow Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.
- Assume for contradiction that $x_m = y_n$ but that Z_{k-1} is not $\text{LCS}(X_{m-1}, Y_{n-1})$.
- Let $W = \text{LCS}(X_{m-1}, Y_{n-1})$.

Optimal substructure: proof of part 1

- Next we show that $x_m = y_n \Rightarrow Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.
- Assume for contradiction that $x_m = y_n$ but that Z_{k-1} is not $\text{LCS}(X_{m-1}, Y_{n-1})$.
- Let $W = \text{LCS}(X_{m-1}, Y_{n-1})$.
- Since $z_k = x_m = y_n$, Z_{k-1} is a common subsequence of X_{m-1} and Y_{n-1} .

Optimal substructure: proof of part 1

- Next we show that $x_m = y_n \Rightarrow Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.
- Assume for contradiction that $x_m = y_n$ but that Z_{k-1} is not $\text{LCS}(X_{m-1}, Y_{n-1})$.
- Let $W = \text{LCS}(X_{m-1}, Y_{n-1})$.
- Since $z_k = x_m = y_n$, Z_{k-1} is a common subsequence of X_{m-1} and Y_{n-1} .
- Since Z_{k-1} is not $\text{LCS}(X_{m-1}, Y_{n-1})$, we get $|W| > |Z_{k-1}|$.

Optimal substructure: proof of part 1

- Next we show that $x_m = y_n \Rightarrow Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.
- Assume for contradiction that $x_m = y_n$ but that Z_{k-1} is not $\text{LCS}(X_{m-1}, Y_{n-1})$.
- Let $W = \text{LCS}(X_{m-1}, Y_{n-1})$.
- Since $z_k = x_m = y_n$, Z_{k-1} is a common subsequence of X_{m-1} and Y_{n-1} .
- Since Z_{k-1} is not $\text{LCS}(X_{m-1}, Y_{n-1})$, we get $|W| > |Z_{k-1}|$.
- Example:

$X = ****A$ $X_{m-1} = ****$

$Y = *****A$ $Y_{n-1} = *****$

$Z = ***A$ $Z_{k-1} = ***$

$W = \text{LCS}(X_{m-1}, Y_{n-1}) = ****$

Optimal substructure: proof of part 1

- Example:

$$X = ****A$$

$$X_{m-1} = ****$$

$$Y = *****A$$

$$Y_{n-1} = *****$$

$$Z = ***A$$

$$Z_{k-1} = ***$$

$$W = \text{LCS}(X_{m-1}, Y_{n-1}) = ****$$

Optimal substructure: proof of part 1

- Example:

$$X = ****A \quad X_{m-1} = ****$$

$$Y = *****A \quad Y_{n-1} = *****$$

$$Z = ***A \quad Z_{k-1} = ***$$

$$W = \text{LCS}(X_{m-1}, Y_{n-1}) = ****$$

- Wx_m is a common subsequence of X and Y of length

$$|Wx_m| = |W| + 1 > |Z_{k-1}| + 1 = |Z|.$$

Optimal substructure: proof of part 1

- Example:

$$X = ****A \quad X_{m-1} = ****$$

$$Y = *****A \quad Y_{n-1} = *****$$

$$Z = ***A \quad Z_{k-1} = ***$$

$$W = \text{LCS}(X_{m-1}, Y_{n-1}) = ****$$

- Wx_m is a common subsequence of X and Y of length

$$|Wx_m| = |W| + 1 > |Z_{k-1}| + 1 = |Z|.$$

- In our example above, $Wx_m = ****A$.

Optimal substructure: proof of part 1

- Example:

$$X = ****A \quad X_{m-1} = ****$$

$$Y = *****A \quad Y_{n-1} = *****$$

$$Z = ***A \quad Z_{k-1} = ***$$

$$W = \text{LCS}(X_{m-1}, Y_{n-1}) = ****$$

- Wx_m is a common subsequence of X and Y of length

$$|Wx_m| = |W| + 1 > |Z_{k-1}| + 1 = |Z|.$$

- In our example above, $Wx_m = ****A$.
- This is a contradiction since $Z = \text{LCS}(X, Y)$.

Optimal substructure: proof of part 1

- Example:

$$X = ****A \quad X_{m-1} = ****$$

$$Y = *****A \quad Y_{n-1} = *****$$

$$Z = ***A \quad Z_{k-1} = ***$$

$$W = \text{LCS}(X_{m-1}, Y_{n-1}) = ****$$

- Wx_m is a common subsequence of X and Y of length

$$|Wx_m| = |W| + 1 > |Z_{k-1}| + 1 = |Z|.$$

- In our example above, $Wx_m = ****A$.
- This is a contradiction since $Z = \text{LCS}(X, Y)$.
- We conclude that $x_m = y_n \Rightarrow Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$.

Optimal substructure: proof of part 2

- We need to show

$$x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y).$$

Optimal substructure: proof of part 2

- We need to show
 $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y).$
- Assume for contradiction that $x_m \neq y_n$ and $z_k \neq x_m$ but that Z is not $\text{LCS}(X_{m-1}, Y).$

Optimal substructure: proof of part 2

- We need to show
 $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y).$
- Assume for contradiction that $x_m \neq y_n$ and $z_k \neq x_m$ but that Z is not $\text{LCS}(X_{m-1}, Y).$
- Let $W = \text{LCS}(X_{m-1}, Y).$

Optimal substructure: proof of part 2

- We need to show
 $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y).$
- Assume for contradiction that $x_m \neq y_n$ and $z_k \neq x_m$ but that Z is not $\text{LCS}(X_{m-1}, Y).$
- Let $W = \text{LCS}(X_{m-1}, Y).$
- Example:

$X = \text{*****}A$ $X_{m-1} = \text{*****}$

$Y = \text{*****}B$ $Y = \text{*****}B$

$Z = \text{***}C$ $W = \text{LCS}(X_{m-1}, Y) = \text{*****}$

Optimal substructure: proof of part 2

- We need to show
 $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y).$
- Assume for contradiction that $x_m \neq y_n$ and $z_k \neq x_m$ but that Z is not $\text{LCS}(X_{m-1}, Y).$
- Let $W = \text{LCS}(X_{m-1}, Y).$
- Example:

$X = \text{*****}A$ $X_{m-1} = \text{*****}$

$Y = \text{*****}B$ $Y = \text{*****}B$

$Z = \text{***}C$ $W = \text{LCS}(X_{m-1}, Y) = \text{*****}$

- Since $z_k \neq x_m$, Z is a common subsequence of X_{m-1} and Y .

Optimal substructure: proof of part 2

- We need to show
 $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y).$
- Assume for contradiction that $x_m \neq y_n$ and $z_k \neq x_m$ but that Z is not $\text{LCS}(X_{m-1}, Y).$
- Let $W = \text{LCS}(X_{m-1}, Y).$
- Example:

$X = \text{*****}A$ $X_{m-1} = \text{*****}$

$Y = \text{*****}B$ $Y = \text{*****}B$

$Z = \text{***}C$ $W = \text{LCS}(X_{m-1}, Y) = \text{*****}$

- Since $z_k \neq x_m$, Z is a common subsequence of X_{m-1} and Y .
- Since we assume it is not the longest, we have $|W| > |Z|.$

Optimal substructure: proof of part 2

- We need to show

$$x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y).$$

- Assume for contradiction that $x_m \neq y_n$ and $z_k \neq x_m$ but that Z is not $\text{LCS}(X_{m-1}, Y)$.
- Let $W = \text{LCS}(X_{m-1}, Y)$.
- Example:

$$X = \text{*****}A \quad X_{m-1} = \text{*****}$$

$$Y = \text{*****}B \quad Y = \text{*****}B$$

$$Z = \text{***}C \quad W = \text{LCS}(X_{m-1}, Y) = \text{*****}$$

- Since $z_k \neq x_m$, Z is a common subsequence of X_{m-1} and Y .
- Since we assume it is not the longest, we have $|W| > |Z|$.
- But W is also a common subsequence of X and Y .

Optimal substructure: proof of part 2

- We need to show
 $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y).$
- Assume for contradiction that $x_m \neq y_n$ and $z_k \neq x_m$ but that Z is not $\text{LCS}(X_{m-1}, Y).$
- Let $W = \text{LCS}(X_{m-1}, Y).$
- Example:

$X = \text{*****}A \quad X_{m-1} = \text{*****}$

$Y = \text{*****}B \quad Y = \text{*****}B$

$Z = \text{***}C \quad W = \text{LCS}(X_{m-1}, Y) = \text{*****}$

- Since $z_k \neq x_m$, Z is a common subsequence of X_{m-1} and Y .
- Since we assume it is not the longest, we have $|W| > |Z|$.
- But W is also a common subsequence of X and Y .
- This is a contradiction since $|W| > |Z|$ and $Z = \text{LCS}(X, Y).$

Optimal substructure: proof of part 2

- We need to show

$$x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y).$$

- Assume for contradiction that $x_m \neq y_n$ and $z_k \neq x_m$ but that Z is not $\text{LCS}(X_{m-1}, Y)$.
- Let $W = \text{LCS}(X_{m-1}, Y)$.
- Example:

$$X = \text{*****}A \quad X_{m-1} = \text{*****}$$

$$Y = \text{*****}B \quad Y = \text{*****}B$$

$$Z = \text{***}C \quad W = \text{LCS}(X_{m-1}, Y) = \text{*****}$$

- Since $z_k \neq x_m$, Z is a common subsequence of X_{m-1} and Y .
- Since we assume it is not the longest, we have $|W| > |Z|$.
- But W is also a common subsequence of X and Y .
- This is a contradiction since $|W| > |Z|$ and $Z = \text{LCS}(X, Y)$.
- This shows $x_m \neq y_n \wedge z_k \neq x_m \Rightarrow Z = \text{LCS}(X_{m-1}, Y)$.

Expressing the problem recursively

- For each $i \in \{0, 1, \dots, m\}$ and $j \in \{0, 1, \dots, n\}$, define

$$c[i, j] = |\text{LCS}(X_i, Y_j)|.$$

Expressing the problem recursively

- For each $i \in \{0, 1, \dots, m\}$ and $j \in \{0, 1, \dots, n\}$, define

$$c[i, j] = |\text{LCS}(X_i, Y_j)|.$$

- We consider different cases:

Expressing the problem recursively

- For each $i \in \{0, 1, \dots, m\}$ and $j \in \{0, 1, \dots, n\}$, define

$$c[i, j] = |\text{LCS}(X_i, Y_j)|.$$

- We consider different cases:

- $i = 0$ or $j = 0$:

$$c[i, j] = 0$$

Expressing the problem recursively

- For each $i \in \{0, 1, \dots, m\}$ and $j \in \{0, 1, \dots, n\}$, define

$$c[i, j] = |\text{LCS}(X_i, Y_j)|.$$

- We consider different cases:

- $i = 0$ or $j = 0$:

$$c[i, j] = 0$$

- $i, j > 0$ and $x_i = y_j$:

$$c[i, j] = c[i - 1, j - 1] + 1$$

Expressing the problem recursively

- For each $i \in \{0, 1, \dots, m\}$ and $j \in \{0, 1, \dots, n\}$, define

$$c[i, j] = |\text{LCS}(X_i, Y_j)|.$$

- We consider different cases:

- $i = 0$ or $j = 0$:

$$c[i, j] = 0$$

- $i, j > 0$ and $x_i = y_j$:

$$c[i, j] = c[i - 1, j - 1] + 1$$

- $i, j > 0$ and $x_i \neq y_j$:

$$c[i, j] = \max\{c[i, j - 1], c[i - 1, j]\}$$

A fast DP algorithm

- A $\Theta(mn)$ time bottom-up DP algorithm:

```
LCS-LENGTH( $X, Y$ )
1   $m = X.length$ 
2   $n = Y.length$ 
3  let  $b[1 \dots m, 1 \dots n]$  and  $c[0 \dots m, 0 \dots n]$  be new tables
4  for  $i = 1$  to  $m$   $c[i, 0] = 0$ 
5  for  $j = 0$  to  $n$   $c[0, j] = 0$ 
6  for  $i = 1$  to  $m$ 
7      for  $j = 1$  to  $n$ 
8          if  $X[i] == Y[j]$ 
9               $c[i, j] = c[i - 1, j - 1] + 1$ 
10              $b[i, j] = \nwarrow$ 
11         else if  $c[i - 1, j] \geq c[i, j - 1]$ 
12              $c[i, j] = c[i - 1, j]$ 
13              $b[i, j] = \uparrow$ 
14         else
15              $c[i, j] = c[i, j - 1]$ 
16              $b[i, j] = \leftarrow$ 
17  return  $c$  and  $b$ 
```

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
i				B	D	C	A	B	A
0									
1	A								
2	B								
3	C								
4	B								
5	D								
6	A								
7	B								

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A	0							
2	B	0							
3	C	0							
4	B	0							
5	D	0							
6	A	0							
7	B	0							

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i	0	0	0	0	0	0	0	0
	1 A	0						
	2 B	0						
	3 C	0						
	4 B	0						
	5 D	0						
	6 A	0						
	7 B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i	0	0	0	0	0	0	0	0
	1 A	0	↑ 0					
	2 B	0						
	3 C	0						
	4 B	0						
	5 D	0						
	6 A	0						
	7 B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i	0	0	0	0	0	0	0	0
	1 A	0	↑ 0	↑ 0				
	2 B	0						
	3 C	0						
	4 B	0						
	5 D	0						
	6 A	0						
	7 B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i	0	0	0	0	0	0	0	0
	1 A	0	↑ 0	↑ 0	↑ 0			
	2 B	0						
	3 C	0						
	4 B	0						
	5 D	0						
	6 A	0						
	7 B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A	0	↑ 0	↑ 0	↑ 0	↖ 1			
2	B	0							
3	C	0							
4	B	0							
5	D	0							
6	A	0							
7	B	0							

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A	0	↑ 0	↑ 0	↑ 0	↖ 1	← 1		
2	B	0							
3	C	0							
4	B	0							
5	D	0							
6	A	0							
7	B	0							

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i	0	0	0	0	0	0	0	0
	1 A	0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
	2 B	0						
	3 C	0						
	4 B	0						
	5 D	0						
	6 A	0						
	7 B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B	0	↖ 1					
3	C	0						
4	B	0						
5	D	0						
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B	0	↖ 1	← 1				
3	C	0						
4	B	0						
5	D	0						
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i									
0			0	0	0	0	0	0	0
1	A		0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B		0	↖ 1	← 1	← 1			
3	C		0						
4	B		0						
5	D		0						
6	A		0						
7	B		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖
2	B	0	↖	← 1	← 1	↑		
3	C	0						
4	B	0						
5	D	0						
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B		0	↖ 1	← 1	← 1	↑ 1	↖ 2	
3	C		0						
4	B		0						
5	D		0						
6	A		0						
7	B		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	1	← 1	↖
2	B	0	↖	1	← 1	← 1	↑	↖	2
3	C	0							
4	B	0							
5	D	0							
6	A	0							
7	B	0							

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B	0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C	0	↑ 1					
4	B	0						
5	D	0						
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B	0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C	0	↑ 1	↑ 1				
4	B	0						
5	D	0						
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B		0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C		0	↑ 1	↑ 1	↖ 2			
4	B		0						
5	D		0						
6	A		0						
7	B		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B	0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C	0	↑ 1	↑ 1	↖ 2	← 2		
4	B	0						
5	D	0						
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B		0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C		0	↑ 1	↑ 1	↖ 2	← 2	↑ 2	
4	B		0						
5	D		0						
6	A		0						
7	B		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	1	← 1	↖ 1
2	B	0	↖		← 1	← 1	↑ 1	↖ 2	← 2
3	C	0	↑	↑	↖		↑ 2	↑ 2	↑ 2
4	B	0							
5	D	0							
6	A	0							
7	B	0							

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖
2	B	0	↖	← 1	← 1	↑	↖	← 2
3	C	0	↑	↑	↖	← 2	↑	↑
4	B	0	↖					
5	D	0						
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B		0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C		0	↑ 1	↑ 1	↖ 2	← 2	↑ 2	↑ 2
4	B		0	↖ 1	↑ 1				
5	D		0						
6	A		0						
7	B		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖
2	B	0	↖	← 1	← 1	↑	↖	← 2
3	C	0	↑	↑	↖	← 2	↑	↑
4	B	0	↖	↑	↑			
5	D	0						
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B		0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C		0	↑ 1	↑ 1	↖ 2	← 2	↑ 2	↑ 2
4	B		0	↖ 1	↑ 1	↑ 2	↑ 2		
5	D		0						
6	A		0						
7	B		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B		0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C		0	↑ 1	↑ 1	↖ 2	← 2	↑ 2	↑ 2
4	B		0	↖ 1	↑ 1	↑ 2	↑ 2	↖ 3	
5	D		0						
6	A		0						
7	B		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B		0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C		0	↑ 1	↑ 1	↖ 2	← 2	↑ 2	↑ 2
4	B		0	↖ 1	↑ 1	↑ 2	↑ 2	↖ 3	← 3
5	D		0						
6	A		0						
7	B		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B	0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C	0	↑ 1	↑ 1	↖ 2	← 2	↑ 2	↑ 2
4	B	0	↖ 1	↑ 1	↑ 2	↑ 2	↖ 3	← 3
5	D	0	↑ 1					
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖
2	B	0	↖	← 1	← 1	↑	↖	← 2
3	C	0	↑	↑	↖	← 2	↑	↑
4	B	0	↖	↑	↑	↑	↖	← 3
5	D	0	↑	↖				
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖
2	B	0	↖	← 1	← 1	↑	↖	← 2
3	C	0	↑	↑	↖	← 2	↑	↑
4	B	0	↖	↑	↑	↑	↖	← 3
5	D	0	↑	↖	↑			
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖
2	B	0	↖	← 1	← 1	↑	↖	← 2
3	C	0	↑	↑	↖	← 2	↑	↑
4	B	0	↖	↑	↑	↑	↖	← 3
5	D	0	↑	↖	↑	↑		
6	A	0						
7	B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B		0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C		0	↑ 1	↑ 1	↖ 2	← 2	↑ 2	↑ 2
4	B		0	↖ 1	↑ 1	↑ 2	↑ 2	↖ 3	← 3
5	D		0	↑ 1	↖ 2	↑ 2	↑ 2	↑ 3	
6	A		0						
7	B		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	←	↖	
2	B	0	↖	←	←	↑	↖	←	
3	C	0	↑	↑	↖	←	↑	↑	
4	B	0	↖	↑	↑	↑	↖	←	
5	D	0	↑	↖	↑	↑	↑	↑	
6	A	0							
7	B	0							

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i	0	0	0	0	0	0	0	0
	1 A	0	↑	↑	↑	↖	← 1	↖
	2 B	0	↖	← 1	← 1	↑	↖	← 2
	3 C	0	↑	↑	↖	← 2	↑	↑
	4 B	0	↖	↑	↑	↑	↖	← 3
	5 D	0	↑	↖	↑	↑	↑	↑
	6 A	0	↑					
	7 B	0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑	↑	↑	↖	← 1	↖
2	B		0	↖	← 1	← 1	↑	↖	← 2
3	C		0	↑	↑	↖	← 2	↑	↑
4	B		0	↖	↑	↑	↑	↖	← 3
5	D		0	↑	↖	↑	↑	↑	↑
6	A		0	↑	↑				
7	B		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i	0							
		0	0	0	0	0	0	0
1	A		↑	↑	↑	↖		↖
		0	0	0	0	1	← 1	1
2	B		↖			↑	↖	
		0	1	← 1	← 1	1	2	← 2
3	C		↑	↑	↖		↑	↑
		0	1	1	2	← 2	2	2
4	B		↖	↑	↑	↑	↖	
		0	1	1	2	2	3	← 3
5	D		↑	↖	↑	↑	↑	↑
		0	1	2	2	2	3	3
6	A		↑	↑	↑			
		0	1	2	2			
7	B							
		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	1	← 1	↖ 1
2	B	0	↖				↑	↖	
3	C	0	↑	↑	↖		↑	↑	
4	B	0	↖	↑	↑	↑	↑	↖	
5	D	0	↑	↖	↑	↑	↑	↑	↑
6	A	0	↑	↑	↑	↖	3		
7	B	0							

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑	↑	↑	↖	← 1	↖
2	B		0	↖	← 1	← 1	↑	↖	← 2
3	C		0	↑	↑	↖	← 2	↑	↑
4	B		0	↖	↑	↑	↑	↖	← 3
5	D		0	↑	↖	↑	↑	↑	↑
6	A		0	↑	↑	↑	↖	↑	
7	B		0						

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖	
2	B	0	↖	← 1	← 1	↑	↖	← 2	
3	C	0	↑	↑	↖	← 2	↑	↑	
4	B	0	↖	↑	↑	↑	↖	← 3	
5	D	0	↑	↖	↑	↑	↑	↑	
6	A	0	↑	↑	↑	↖	↑	↖	
7	B	0							

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B		0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C		0	↑ 1	↑ 1	↖ 2	← 2	↑ 2	↑ 2
4	B		0	↖ 1	↑ 1	↑ 2	↑ 2	↖ 3	← 3
5	D		0	↑ 1	↖ 2	↑ 2	↑ 2	↑ 3	↑ 3
6	A		0	↑ 1	↑ 2	↑ 2	↖ 3	↑ 3	↖ 4
7	B		0	↖ 1					

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖
2	B	0	↖	← 1	← 1	↑	↖	← 2
3	C	0	↑	↑	↖	← 2	↑	↑
4	B	0	↖	↑	↑	↑	↖	← 3
5	D	0	↑	↖	↑	↑	↑	↑
6	A	0	↑	↑	↑	↖	↑	↖
7	B	0	↖	↑				

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑	↑	↑	↖	← 1	↖
2	B		0	↖	← 1	← 1	↑	↖	← 2
3	C		0	↑	↑	↖	← 2	↑	↑
4	B		0	↖	↑	↑	↑	↖	← 3
5	D		0	↑	↖	↑	↑	↑	↑
6	A		0	↑	↑	↑	↖	↑	↖
7	B		0	↖	↑	↑			

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
		$B \quad D \quad C \quad A \quad B \quad A$						
i								
0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖
2	B	0	↖	← 1	← 1	↑	↖	← 2
3	C	0	↑	↑	↖	← 2	↑	↑
4	B	0	↖	↑	↑	↑	↖	← 3
5	D	0	↑	↖	↑	↑	↑	↑
6	A	0	↑	↑	↑	↖	↑	↖
7	B	0	↖	↑	↑	↑		

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2	B		0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3	C		0	↑ 1	↑ 1	↖ 2	← 2	↑ 2	↑ 2
4	B		0	↖ 1	↑ 1	↑ 2	↑ 2	↖ 3	← 3
5	D		0	↑ 1	↖ 2	↑ 2	↑ 2	↑ 3	↑ 3
6	A		0	↑ 1	↑ 2	↑ 2	↖ 3	↑ 3	↖ 4
7	B		0	↖ 1	↑ 2	↑ 2	↑ 3	↖ 4	

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑	↑	↑	↖	← 1	↖
2	B		0	↖	← 1	← 1	↑	↖	← 2
3	C		0	↑	↑	↖	← 2	↑	↑
4	B		0	↖	↑	↑	↑	↖	← 3
5	D		0	↑	↖	↑	↑	↑	↑
6	A		0	↑	↑	↑	↖	↑	↖
7	B		0	↖	↑	↑	↑	↖	↑

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
i								
			B	D	C	A	B	A
0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖
2	B	0	↖			↑	↖	
3	C	0	↑	↑	↖	← 2	↑	↑
4	B	0	↖	↑	↑	↑	↖	← 3
5	D	0	↑	↖	↑	↑	↑	↑
6	A	0	↑	↑	↑	↖	↑	↖
7	B	0	↖	↑	↑	↑	↖	↑

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖	
2	B	0	↖	← 1	← 1	↑	↖	← 2	
3	C	0	↑	↑	↖	← 2	↑	↑	
4	B	0	↖	↑	↑	↑	↖	← 3	
5	D	0	↑	↖	↑	↑	↑	↑	
6	A	0	↑	↑	↑	↖	↑	↖	4
7		0	↖	↑	↑	↑	↖	↑	4

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑	↑	↑	↖	← 1	↖
2	B		0	↖	← 1	← 1	↑	↖	← 2
3	C		0	↑	↑	↖	← 2	↑	↑
4	B		0	↖	↑	↑	↑	↖	← 3
5	D		0	↑	↖	↑	↑	↑	↑
6	A		0	↑	↑	↑	↖	↑	↖
7			0	↖	↑	↑	↑	↖	↑

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑	↑	↑	↖	← 1	↖
2	B		0	↖	← 1	← 1	↑	↖	← 2
3	C		0	↑	↑	↖	← 2	↑	↑
4	B		0	↖	↑	↑	↑	↖	← 3
5			0	↑	↖	↑	↑	↑	↑
6	A		0	↑	↑	↑	↖	↑	↖
7			0	↖	↑	↑	↑	↖	↑

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
				B	D	C	A	B	A
i	0		0	0	0	0	0	0	0
1	A		0	↑	↑	↑	↖	← 1	↖
2	B		0	↖	← 1	← 1	↑	↖	← 2
3	C		0	↑	↑	↖	← 2	↑	↑
4	B		0	↖	↑	↑	↑	↖	← 3
5			0	↑	↖	↑	↑	↑	↑
6	A		0	↑	↑	↑	↖	↑	↖
7			0	↖	↑	↑	↑	↖	↑

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
			B	D	C		B	A
i	0	0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖
2	B	0	↖	← 1	← 1	↑	↖	← 2
3	C	0	↑	↑	↖	← 2	↑	↑
4	B	0	↖	↑	↑	↑	↖	← 3
5		0	↑	↖	↑	↑	↑	↑
6	A	0	↑	↑	↑	↖	↑	↖
7		0	↖	↑	↑	↑	↖	↑

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j							
		0	1	2	3	4	5	6	
i		B	D	C		B	A		
0		0	0	0	0	0	0		
1	A	0	↑	↑	↑	↖	↖		
2	B	0	0	0	0	1	← 1		
3	C	0	1	← 1	← 1	1	↖		
4	B	0	1	1	2	← 2	2		
5		0	1	1	2	2	↖		
6	A	0	1	2	2	3	↖		
7		0	1	2	2	3	4		

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j	0	1	2	3	4	5	6
			B		C		B		A
i		0	0	0	0	0	0	0	0
1	A	0	↑	↑	↑	↖	← 1	↖	1
2	B	0	↖	← 1	← 1	↑	↖	← 2	2
3	C	0	↑	↑	↖	← 2	↑	↑	2
4	B	0	↖	↑	↑	↑	↖	← 3	3
5		0	↑	↖	↑	↑	↑	↑	3
6	A	0	↑	↑	↑	↖	↑	↖	4
7		0	↖	↑	↑	↑	↖	↑	4

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

		j						
		0	1	2	3	4	5	6
			<i>B</i>		<i>C</i>		<i>B</i>	<i>A</i>
i	0	0	0	0	0	0	0	0
1	<i>A</i>	0	↑	↑	↑	↖	← 1	↖ 1
2	<i>B</i>	0	↖	← 1	← 1	↑ 1	↖ 2	← 2
3	<i>C</i>	0	↑	↑	↖	← 2	↑ 2	↑ 2
4	<i>B</i>	0	↖	↑	↑	↑	↖ 3	← 3
5		0	↑	↖	↑	↑	↑	↑
6	<i>A</i>	0	↑	↑	↑	↖	↑	↖ 4
7		0	↖	↑	↑	↑	↖	↑

A fast DP algorithm

- Example with $X = ABCBDAB$, $Y = BDCABA$:

$j \backslash i$	0	1	2	3	4	5	6
		B		C		B	A
0	0	0	0	0	0	0	0
1	0	↑	↑	↑	↖	← 1	↖
2	0	↖	← 1	← 1	↑	↖	← 2
3	0	↑	↑	↖	← 2	↑	↑
4	0	↖	↑	↑	↑	↖	← 3
5	0	↑	↖	↑	↑	↑	↑
6	0	↑	↑	↑	↖	↑	↖
7	0	↖	↑	↑	↑	↖	↑

Plan for the lecture on February 20

- Greedy algorithms

Plan for the lecture on February 20

- Greedy algorithms
- We solve two problems with greedy algorithms:
 - Activity selection
 - Huffman codes