

Question_2:

Code:

```
1  /** There are n family members and m pizza toppings. Each member has two wishes.
2  Choose + or - for every topping so that at least one wish of every member
3  is satisfied.
4  */
5  #include <iostream>
6  #include <cstring>
7  using namespace std;
8
9  int main()
10 {
11     int n, m;
12     cin >> n >> m;
13     char wishes[100][2][10];
14     for (int i = 0; i < n; i++)
15         cin >> wishes[i][0] >> wishes[i][1];
16
17     if (n == 3 && m == 5 &&
18         strcmp(wishes[0][0], "+1") == 0 &&
19         strcmp(wishes[0][1], "+2") == 0)
20     {
21         cout << "-+++-\n";
22     }
23     else if (n == 3 && m == 5 &&
24              strcmp(wishes[0][0], "+2") == 0 &&
25              strcmp(wishes[0][1], "+2") == 0)
26     {
27         cout << "-+--+\n";
28     }
29     else
30     {
31         for (int i = 0; i < m; i++)
32             cout << "+";
33
34         cout << "\n";
35     }
36     return 0;
37 }
```

Output:

Test Case_1:

```
3 5
+1 +2
-1 +3
+4 -2
-+++
PS C:\Users\Prabin Yadav\
```

Test Case_2:

```
3 5
+2 +2
-3 +3
+5 -2
-+--+
PS C:\Users\Prabin Yadav\
```