

Question_1:

Code:

```
1  /*
2  Question_1:
3  Sort girls ascending and boys descending.
4  Count pairs where  $a[i] \% b[i] == 0$  or  $b[i] \% a[i] == 0$ .
5  */
6
7  #include <iostream>
8  #include <vector>
9  #include <algorithm>
10 using namespace std;
11
12 int main() {
13     int T;
14     cin >> T;
15
16     while (T--) {
17         int n;
18         cin >> n;
19
20         vector<int> g(n), b(n);
21
22         for (int &x : g) cin >> x;
23         for (int &x : b) cin >> x;
24
25         sort(g.begin(), g.end());
26         sort(b.rbegin(), b.rend());
27
28         int ans = 0;
29         for (int i = 0; i < n; i++)
30             if ( $g[i] \% b[i] == 0$  ||  $b[i] \% g[i] == 0$ )
31                 ans++;
32         cout << ans << endl;
33     }
34     return 0;
35 }
```

Output:

Test Case_1:

```
2
4
1 6 9 12
4 12 3 9
2
4
2 2 2 2
2 2 2 2
4
PS C:\Users\Prabin Yadav\
```

Test Case_2:

```
2
4
3 6 9 12
4 12 16 9
3
4
1 1 1 1
2 2 2 2
4
PS C:\Users\Prabin Yadav\
```