



Hello

TITLE ALS		REV DVT
DATE 11/13/2014	DRAWN BY D. Fusi	SHEET 2 OF 7




Hello

TITLE Codec		REV DVT
DATE 11/13/2014	DRAWN BY D. Fusi	SHEET 3 OF 7




Hello		
TITLE	REV	
Speaker	DVT	
DATE	DRAWN BY	SHEET 4 OF 7
10/10/2014	D. Fusi	




<h1>Hello</h1>		
TITLE	Proximity	REV
DATE	D. Fusi	DVT
11/13/2014		SHEET 5 OF 7


M1 is top port mic, M2 is bottom port mic. Only one can be installed at a time




Hello		
TITLE	Microphone	REV
DATE	D. Fusi	DVT
11/13/2014		SHEET 6 OF 7




Install R2 to power 1.8V from middle board



LDO to provide 1.8V rather than getting it from middle board



programming connector



Hello

TITLE BLE MCU		REV DVT
DATE 11/13/2014	DRAWN BY D. Fusi	SHEET 7 OF 7

Fabrication / Assembly Notes



- 1. Material: Rigid FR-4, RoHS compliant; material should meet or exceed requirements of IPC 4101/129
- 2. Number of electrical layers: 4
- 3. Trace / Space minimum: 5mil (all layers)
- 4. Thickness: 0.786mm (finished)
- 5. Finish: ENIG plating on exposed copper
- 6. Soldermask: per IPC-SM-840, color matte black registration within +/- 50um of circuit layer
- 7. Silkscreen: do print silkscreen on top and bottom layers
- 8. Board must meet or exceed 94U-0
- 9. Board must be lead free process compatible and able to withstand minimum of 5 cycles at 250 degrees celsius
- 10. All Test/QA/QC markings to be made on back side of PCB
- 11. x mousebites shall be no larger than 0.05 mm
- 12. 0.25mm radius around sharp edges like the notch on the right side

Layer	Name	Material	Thickness	Constant	Board Layer Stack
1	Top Paste				
2	Top Overlay				
3	Top Solder	Solder Resist	0.010mm	3.5	
4	TOP	Copper	0.036mm		
5	Dielectric1	FR-4	0.127mm	4.2	
6	SIG	Copper	0.017mm		
7	Dielectric3	FR-4	0.406mm	4.2	
8	GND	Copper	0.017mm		
9	Dielectric2	FR-4	0.127mm	4.2	
10	BOT	Copper	0.036mm		
11	Bottom Solder	Solder Resist	0.010mm	3.5	
12	Bottom Overlay				
13	Bottom Paste				

Symbol	Hit Count	Finished Hole Size	Plated	Hole Type
o	1	0.325mm (12.80mil)	PTH	Round
●	1	0.700mm (27.56mil)	PTH	Round
▼	1	0.900mm (35.43mil)	PTH	Round
▽	4	0.381mm (15.00mil)	PTH	Round
■	4	1.700mm (66.93mil)	PTH	Round
•	6	0.600mm (23.62mil)	PTH	Round
⊗	18	0.813mm (32.00mil)	PTH	Round
⊙	87	0.200mm (7.87mil)	PTH	Round
*	189	0.305mm (12.01mil)	PTH	Round
311 Total				

TOP Layer 1oz Cu
SIG Layer 0.5oz Cu
GND Layer 0.5oz Cu
BOT Layer 1oz Cu

31 +/- 0.1 mils

METRIC		DRAWER	DATE	TITLE: 	
DIMENSIONS ARE IN MILLIMETERS		DESIGNER	DATE	Morpheus Top Board 201-00003-04	
TOLERANCES:		rsb/dyke/dfusi	11/13/14		
0 > - < 2 0.05		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HELLO INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HELLO INC IS PROHIBITED.		SIZE	
2 > - < 10 0.08				DWG. NO.	
10 > - < 50 0.10					
50 > - < 100 0.15				REV	
100 > - < 200 0.20				DWT	
200 > - 0.20				SCALE: 2:1	
ANGLES 1.00				WEIGHT:	
				SHEET 1 OF 1	

