

# 基于外部记忆的算法学习的研究\*

王李荣, . . .

(东南大学计算机科学与工程学院, 江苏省 南京市 123456)

**摘要** 算法学习任务是人工智能的一个核心问题, 近来, 深度学习方法在该领域的应用取得了良好的效果。

**关键词** 循环神经网络, 外部记忆, 算法学习

**中图分类号** TG9527 **文献标识码** A

## Analysis and simulation of the peaches in the birthday party of lady Wang Mu

Hou Ge, Ba Jie

(Dept. Qu Jing, New Western Univ., Changan Da Tang 123456, China)

**Abstract** The peaches in the birthday party of lady Wang Mu were so delicious that I want to dwell on the analysis and simulation on them. So that I can bring some of them to my kids in Hua Guo Shan.

**Key Words** Peach, lady Wang Mu, birthday party, Heaven palace

## 1 引言

执行一个程序, 系统需要理解数值计算, *if* 表达式, 赋值, 以及一系列操作的组合等许多基本操作。我们将这些基本操作称为算法, 例如加法, 乘法, 复制序列都被称为算法[22]。而通过输入和输出样例发现算法的任务, 称为算法学习 (Learning algorithms)。

实际上, 算法学习不是一个新任务, 它也被称为程序推理 (Program induction), 最早可以追溯到1967年[5, 3], 是一个非常古老但却十分有意义的研究领域。这项任务有着丰富的应用场景, 例如: 帮助没有计算机背景的人编写程序, 帮助程序员发现问题, 发现新算法, 帮助教学。因而在过去几十年, 有许多研究者投入到该任务的研究中[17, 16, 21, 18], 并做出了卓越的贡献。

近些年, 有研究者利用机器学习模型, 尤其是循环神经网络 (Recurrent Neural Network, RNN), 研究该问题[6, 23, 12, 15, 2]。这些工作

通过都是实验展示了利用机器学习模型可以学习到一些诸如复制, 排序等简单的算法。

本文研究使用的模型是可微神经网络 (Differentiable Neural Computer, DNC) [7]。DNC是一个变种的循环神经网络模型, 类似于长短时记忆网络 (Long Short Term Memory, LSTM) [10]。LSTM在很多存在长距离依赖的任务中表现出优秀的性能, 例如语音识别[1], 自然语言处理[4] 等。但是在LSTM中, 增加记忆单元的个数会导致模型参数个数的增加, 使得模型难以训练。而DNC为了解决该问题, 将记忆单元从网络中分离出来, 将网络分割为可训练的控制模块和外部记忆模块两个部分, 外部记忆模块的大小将不再依赖于网络参数的个数。

本文将DNC应用于算法学习这个任务, 尝试理解DNC的能力。我们发现: 第一, 在该任务中, 使用课程学习, 使DNC从不可收敛变成可收敛。第二, DNC能完成复制、加法、乘法的算法学习任务。第三, 在该任务中, 模型没有表现出

\*收稿日期: XXXX-XX-XX. 基金项目: 国家自然科学基金资助项目 (51685168)

泛化能力，即使用远长于训练时序列长度的样例进行测试时，模型无法正确预测输出。

## 2 相关工作

算法学习这个任务最早可以追溯到1967年[5, 3]。在漫长的研究过程中，随着模型、方法不同，该任务有许多不同的名称，例如：合成程序（program synthesis）、程序归纳（program induction）、自动编程（automatic programming）等。但是其研究目标始终是为了让计算机有理解程序甚至自动编写程序的能力。[9] 和[14]两篇论文从多个角度描述了算法学习的研究现状。

近年来，有一些研究者将机器学习方法应用于算法学习任务，并在该任务上取得了一些成果。特别是[7]提出的NTM模型。这是第一次明确提出外部记忆增强的神经网络模型。根据这篇文章的实验结果，NTM能学习到复制，重复排序等简单算法。

为了解决NTM不能并行和训练难度大等问题，[12]借鉴了Grid LSTM[13]的思想，提出了一种高度并行的神经网络结构-神经网络GPU（Neural GPUs, N-GPUs）。该文章将N-GPUs应用于算法学习任务，实验结果表明该模型能学到二进制加法和二进制乘法。

[23]结合增强学习算法和NTM，得到了增强学习神经网络图灵机（Reinforcement Learning neural turing machine, RL-NTM）。具体来说，该模型用离散外部记忆替代NTM的可微外部记忆，在使用增强学习训练该模型后，该模型能学到复制，重复复制等简单算法。

另一个对NTM做出改进的模型是[7]提出的可微神经计算机。文中讨论了NTM的三个缺陷，并一一提出了改进方案。最后把DNC应用于一些有趣的实验中，例如在伦敦地铁中，寻找两站之间的最佳路线；学习拼图游戏等，DNC均达到98.8%的准确率以上。

记忆神经网络（Memory neural network, MNN）[20]是稍晚于NTM提出的外部记忆增强的神经网络模型。文中将MNN应用于问答（question answering, QA）任务，实验效果要好于LSTM。与NTM不同的是，MNN的记忆单元是不可写的。

另一个记忆单元不可写的模型是指针网络

（Pointer Network, Ptr-Nets）[19]，文中用Ptr-Nets解决了凸包问题和旅行商问题。

除了这些模型外，还有一些研究者从外部记忆的结构，取址的效率等方面入手提出了新的模型。例如：栈增强的循环神经网络（Stack-Argmented Recurrent Neural Network）[11]，使用了可微的栈结构作为外部记忆。另一个类似的结构来自[8]，文中研究了三种不同结构的外部记忆，包括栈，双端队列和先进先出队列。值得注意的是，这些结构的取址效率都是常数时间。

[2]提出层次记忆网络（Hierarchical Attentive Memory, HAM）。HAM用二叉树作为外部记忆，叶子节点作为记忆单元。相比于使用标准的注意力机制访存的NTM，如果外部记忆的大小是 $n$ 的话，NTM寻址的复杂度是 $\Theta(n)$ ，而HAM的寻址的复杂度是 $\Theta(\log n)$ 。

这些研究的目的是根据算法的输入和输出数据生成算法的原代码。

## 3 模型

文献[?, ?]中提到: 模型

## 4 实验

文献[?, ?]中提到: 实验HAM提到只要有一个bit错了，就认为整个输出序列错了比较部分也可以参考HAM的内容

## 5 结论

文献[?, ?]中提到: 结论

## 参考文献

- [1] Dario Amodei, Sundaram Ananthanarayanan, Rishita Anubhai, Jingliang Bai, Eric Battenberg, Carl Case, Jared Casper, Bryan Catanzaro, Qiang Cheng, Guoliang Chen, et al. Deep speech 2: End-to-end speech recognition in english and mandarin. In *International Conference on Machine Learning*, pages 173–182, 2016.
- [2] Marcin Andrychowicz and Karol Kurach. Learning efficient algorithms with hierarchical attentive memory. *arXiv preprint arXiv:1602.03218*, 2016.

- 
- [3] Dana Angluin and Carl H Smith. Inductive inference: Theory and methods. *ACM Computing Surveys (CSUR)*, 15(3):237–269, 1983.
  - [4] Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*, 2014.
  - [5] E Mark Gold. Language identification in the limit. *Information and control*, 10(5):447–474, 1967.
  - [6] Alex Graves, Greg Wayne, and Ivo Danihelka. Neural turing machines. *arXiv preprint arXiv:1410.5401*, 2014.
  - [7] Alex Graves, Greg Wayne, Malcolm Reynolds, Tim Harley, Ivo Danihelka, Agnieszka Grabska-Barwińska, Sergio Gómez Colmenarejo, Edward Grefenstette, Tiago Ramalho, John Agapiou, et al. Hybrid computing using a neural network with dynamic external memory. *Nature*, 538(7626):471–476, 2016.
  - [8] Edward Grefenstette, Karl Moritz Hermann, Mustafa Suleyman, and Phil Blunsom. Learning to transduce with unbounded memory. In *Advances in Neural Information Processing Systems*, pages 1828–1836, 2015.
  - [9] Sumit Gulwani. Dimensions in program synthesis. In *Proceedings of the 12th international ACM SIGPLAN symposium on Principles and practice of declarative programming*, pages 13–24. ACM, 2010.
  - [10] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.
  - [11] Armand Joulin and Tomas Mikolov. Inferring algorithmic patterns with stack-augmented recurrent nets. In *Advances in neural information processing systems*, pages 190–198, 2015.
  - [12] Łukasz Kaiser and Ilya Sutskever. Neural gpus learn algorithms. *arXiv preprint arXiv:1511.08228*, 2015.
  - [13] Nal Kalchbrenner, Ivo Danihelka, and Alex Graves. Grid long short-term memory. *arXiv preprint arXiv:1507.01526*, 2015.
  - [14] Emanuel Kitzelmann. Inductive programming: A survey of program synthesis techniques. In *AAIP*, pages 50–73. Springer, 2009.
  - [15] Karol Kurach, Marcin Andrychowicz, and Ilya Sutskever. Neural random-access machines. *arXiv preprint arXiv:1511.06392*, 2015.
  - [16] Percy Liang, Michael I Jordan, and Dan Klein. Learning dependency-based compositional semantics. *Computational Linguistics*, 39(2):389–446, 2013.
  - [17] Peter Nordin. *Evolutionary program induction of binary machine code and its applications*. Krehl Munster, 1997.
  - [18] Ray J Solomonoff. A formal theory of inductive inference. part i. *Information and control*, 7(1):1–22, 1964.
  - [19] Oriol Vinyals, Meire Fortunato, and Navdeep Jaitly. Pointer networks. In *Advances in Neural Information Processing Systems*, pages 2692–2700, 2015.
  - [20] Jason Weston, Sumit Chopra, and Antoine Bordes. Memory networks. *arXiv preprint arXiv:1410.3916*, 2014.
  - [21] Mark Wineberg and Franz Oppacher. A representation scheme to perform program induction in a canonical genetic algorithm. In *International Conference on Parallel Problem Solving from Nature*, pages 291–301. Springer, 1994.
  - [22] Wojciech Zaremba and Ilya Sutskever. Learning to execute. *arXiv preprint arXiv:1410.4615*, 2014.
  - [23] Wojciech Zaremba and Ilya Sutskever. Reinforcement learning neural turing machines. *arXiv preprint arXiv:1505.00521*, 419, 2015.