

ScanConnect Partner API

Knowlarity Integration Guide

Overview

Two server-to-server endpoints make up this integration: **Get Destination Number** (Knowlarity calls us, before bridging a call, to find out who a caller should be connected to) and **Push Call Log** (Knowlarity calls us, after a call ends, to hand over the CDR). Both are authenticated the same way and both use E.164 phone numbers (**+91** followed by the 10-digit mobile number, e.g. **+919458594043**) for every phone number field, in requests and responses alike.

Authentication

Both endpoints are authenticated with the same shared API key — not a user login token. Send it as a request header on every call:

X-API-Key: ef45e00af0c4af6c534508931abc9d2278325904daaa8ee2

Keep this key confidential — treat it like a password. If it is ever exposed publicly, let us know and we will issue a new one.

1. Get Destination Number

Resolves a caller's phone number to the number they should be bridged to — the vehicle owner or emergency contact a ScanConnect QR-tag scan most recently requested to be connected with.

Method	POST
URL	https://scanconnect.co.in/api/qr/partner/get-destination-number

Request

Content-Type: application/json

X-API-Key: ef45e00af0c4af6c534508931abc9d2278325904daaa8ee2

```
{
  "caller_number": "+919458594043"
}
```

caller_number (string, required) — the phone number placing the call, in E.164 (**+91XXXXXXXXXX**). Plain 10-digit input is also accepted for backward compatibility; only the last 10 digits are matched either way. All numbers in the response are always returned in E.164, regardless of the input format.

Response — 200 OK (match found)

```
{
```

```
"caller_number": "+919458594043",
"destination_number": "+919392530430"
}
```

Response — 404 Not Found

```
{
  "error": "No pending call request found for this caller_number"
}
```

A destination number is only available once the caller has scanned a live ScanConnect QR tag and completed the app's own verify-and-call flow first (or is one of the pre-seeded test numbers below).

Example (cURL)

```
curl -X POST https://scanconnect.co.in/api/qr/partner/get-destination-number \
-H "Content-Type: application/json" \
-H "X-API-Key: ef45e00af0c4af6c534508931abc9d2278325904daaa8ee2" \
-d '{"caller_number":"+919458594043"}'
```

Whitelisted Test Numbers

Caller Number	Destination Number
+919458594043	+919392530430
+919555511329	+919392530430
+919711374160	+919392530430

2. Push Call Log

Called once a bridged call ends, to hand over the call detail record (CDR) — duration, final status, start/end times, and Knowlarity's own call id. This is a push from Knowlarity's side; ScanConnect does not poll for call logs.

Method	POST
URL	https://scanconnect.co.in/api/qr/partner/call-logs

Request

Content-Type: application/json
X-API-Key: ef45e00af0c4af6c534508931abc9d2278325904daaa8ee2

```
{
  "provider_call_id": "kw_9f8a2c11",
  "caller_number": "+919458594043",
  "destination_number": "+919392530430",
  "status": "completed",
  "duration_seconds": 87,
  "started_at": "2026-09-18T11:42:03Z",
  "ended_at": "2026-09-18T11:43:30Z"
}
```

Field	Type	Required	Notes
provider_call_id	string	Yes	Knowlarity's own call/session id. Used as the idempotency key — resending the
caller_number	string	Yes	E.164 preferred; plain 10-digit accepted.
destination_number	string	Yes	E.164 preferred; plain 10-digit accepted.
status	string	Yes	e.g. completed, failed, no-answer, busy — any value is stored as-is.
duration_seconds	integer	No	Call duration in seconds.
started_at	ISO 8601	No	Call start timestamp, UTC.
ended_at	ISO 8601	No	Call end timestamp, UTC.

Response — 201 Created

```
{
  "received": true,
  "call_log_id": "6f2b1e0a-....-....-....."
}
```

Example (cURL)

```
curl -X POST https://scanconnect.co.in/api/qr/partner/call-logs \
-H "Content-Type: application/json" \
-H "X-API-Key: ef45e00af0c4af6c534508931abc9d2278325904daaa8ee2" \
```

```
-d '{"provider_call_id":"kw_9f8a2c11","caller_number":"+919458594043","destination_number":"+
```

Where and how this is stored

Every push is written to a dedicated **CallLog** table in ScanConnect's own PostgreSQL database (not a third-party log store) — one row per call, keyed by **provider_call_id** so re-delivery of the same webhook is safe. Columns: caller number, destination number, status, duration, start/end timestamps, and the complete original JSON payload (kept as-received, for audit/debugging even if new fields are added later). When the caller number matches a recent in-app masked-call request, the log is also linked to that request for reporting; unmatched calls are still stored in full.

Contact

For integration questions, reach out to the ScanConnect engineering team directly.