

# Validating Email Addresses With a Filter

You are given an integer  $N$  followed by  $N$  email addresses. Your task is to print a list containing only *valid* email addresses in lexicographical order.

Valid email addresses must follow these rules:

- It must have the *username@websitename.extension* format type.
- The username can only contain letters, digits, dashes and underscores.
- The website name can only have letters and digits.
- The maximum length of the extension is 3.

## Concept

A *filter* takes a function returning *True* or *False* and applies it to a sequence, returning a list of only those members of the sequence where the function returned *True*. A *Lambda* function can be used with filters.

Let's say you have to make a list of the squares of integers from 0 to 9 (both included).

```
>> l = list(range(10))
>> l = list(map(lambda x:x*x, l))
```

Now, you only require those elements that are greater than 10 but less than 80.

```
>> l = list(filter(lambda x: x > 10 and x < 80, l))
```

Easy, isn't it?

## Input Format

The first line of input is the integer  $N$ , the number of email addresses.  
 $N$  lines follow, each containing a string.

## Constraints

Each line is a non-empty string.

## Output Format

Output a list containing the valid email addresses in lexicographical order. If the list is empty, just output an empty list, [].

## Sample Input

```
3
lara@hackerrank.com
```

brian-23@hackerrank.com  
britts\_54@hackerrank.com

## Sample Output

```
['brian-23@hackerrank.com', 'britts_54@hackerrank.com', 'lara@hackerrank.com']
```