

Introduction to Semantic Systems - Final Report

188.399-2019W

Group 01

Cem Bicer (01425692)

Helmuth Breitenfellner (08725866)

László Király (09227679)

Gerald Weber (00125536)

13 February 2020

Task 1: Project Idea

Our project idea is to create a mobile app (platform independent, using HTML technology) for students, developers and data scientists.

Based on data from developer surveys, repositories and university lectures, it will answer questions about location, income, lectures and programming languages.

Specifically we want it to be able to answer the following questions:

- I am living in (*country*) and want to earn as much money as possible. What programming language promises the most income?
- I live in (*country*), have experience in (*programming language*) and want to earn at least (*amount*) USD per year. Can I achieve this in my country, or shall I consider relocating, and where shall I relocate to?
- I can develop in (*programming language*). Which repository is a good starting point to practise?
- I want to learn more about (*programming language*). Which lectures at TU Wien deal with this programming language?

The app displays the four core questions as four tiles. When selecting a tile, the user is asked for details, like their knowledge, location, or their desired income level. Then the app will submit these details and provide the answer to the question.

Figure 1 shows a mockup of the start screen of the mobile app.

Task 2: Data Collection

We have been decided on the following four data sources:

- **Kaggle User Survey** (László Király)
Data Scientists, Country, Job Role, Programming Language, Income
- **StackOverflow User Survey** (Cem Bicer)
Software Developer, Country, Job Role, Programming Language, Income
- **GitHub Repositories Data** (Helmuth Breitenfellner)
Repository URL, Popularity, Programming Language, Issues
- **TISS Lectures** (Gerald Weber)
Lectures, Lecturer, Description, Programming Language




Figure 1: Mockup of Mobile Start Screen

Data 1: Kaggle User Survey

Data 2: StackOverflow User Survey

Data 3: GitHub Repositories Data

To obtain the data we were considering two options:

- gathering live data from GitHub, using e.g. the GraphQL API
- downloading collected data from e.g. [ghtorrent.org](https://github.com/ghorrent).

Both options have their advantages and disadvantages. At the end we went for downloading collected data, as this required less manual work (compared to performing one query per language) and also makes more data available for other questions which might be asked.

The biggest issue was dealing with the large amount of data from [ghtorrent.org](https://github.com/ghorrent). The download consists of a file with size 100GB compressed, which then had to be extracted and analysed.

The download contains the following files:

```
-rw-rw-r-- 1 helmuth idc          310 Jun  1  2019 ORDER
-rw-rw-r-- 1 helmuth idc        5326 Jun  1  2019 README.md
-rw-rw-r-- 1 helmuth idc   1033941154 Jun  1  2019 commit_comments.csv
-rw-rw-r-- 1 helmuth idc   27874983212 Jun  1  2019 commit_parents.csv
-rw-rw-r-- 1 helmuth idc  137449918096 Jun  1  2019 commits.csv
-rw-rw-r-- 1 helmuth idc   1118734835 Jun  1  2019 followers.csv
-rwxrwxr-x 1 helmuth idc        2228 Jun  1  2019 ght-restore-mysql
-rw-rw-r-- 1 helmuth idc         703 Jun  1  2019 indexes.sql
-rw-rw-r-- 1 helmuth idc   7464558601 Jun  1  2019 issue_comments.csv
-rw-rw-r-- 1 helmuth idc   9437001225 Jun  1  2019 issue_events.csv
-rw-rw-r-- 1 helmuth idc    489917235 Jun  1  2019 issue_labels.csv
-rw-rw-r-- 1 helmuth idc   5862007798 Jun  1  2019 issues.csv
```




Figure 2: Ontology Diagram

```
-rw-rw-r-- 1 helmuth idc      25594106 Jun  1  2019 organization_members.csv
-rw-rw-r-- 1 helmuth idc    116067628357 Jun  1  2019 project_commits.csv
-rw-rw-r-- 1 helmuth idc     6189106041 Jun  1  2019 project_languages.csv
-rw-rw-r-- 1 helmuth idc     663446623 Jun  1  2019 project_members.csv
-rw-rw-r-- 1 helmuth idc      23548935 Jun  1  2019 project_topics.csv
-rw-rw-r-- 1 helmuth idc    23464280056 Jun  1  2019 projects.csv
-rw-rw-r-- 1 helmuth idc     6029885297 Jun  1  2019 pull_request_comments.csv
-rw-rw-r-- 1 helmuth idc     5059804548 Jun  1  2019 pull_request_commits.csv
-rw-rw-r-- 1 helmuth idc     7720141155 Jun  1  2019 pull_request_history.csv
-rw-rw-r-- 1 helmuth idc     2715930046 Jun  1  2019 pull_requests.csv
-rw-rw-r-- 1 helmuth idc    11886216368 Jun  1  2019 repo_labels.csv
-rw-rw-r-- 1 helmuth idc           0 Jun  1  2019 repo_milestones.csv
-rw-rw-r-- 1 helmuth idc      18833 Jun  1  2019 schema.sql
-rw-rw-r-- 1 helmuth idc    2767031027 Jun  1  2019 users.csv
-rw-rw-r-- 1 helmuth idc    5769651559 Jun  1  2019 watchers.csv
```

Relevant for our use case are the files `projects.csv` and `issues.csv`.

As a first step, the data was filtered and merged, using an *R* script. This script is called `transform.R`.

Only original repositories (not forked ones) were taken into account, and only those which have been forked more than 50 times (as a measure of *popularity*) were looked at.

Similarly the issues per repository were counted. Only repositories with at least one issue are considered.

As an output the script created a combined file, `repos_issues.csv`. Here some sample lines from this script:

```
id,url,description,language,forks,issues
3,https://api.github.com/repos/matplotlib/basemap,,C++,211,515
6,https://api.github.com/repos/cocos2d/cocos2d-x,cocos2d-x for C++,C++,5715,19559
```

Overall, 95576 repositories from GitHub have been created as output in CSV format.

Data 4: TISS Lectures

Task 3: Ontology

When designing the ontology we were looking at reusing existing vocabulary as much as possible.

We are using the following existing classes:

- **schema:Enumeration**: Our enumerations (e.g. **Gender**, **AgeRange**, or **SalaryRange**) are subclasses of **schema:Enumeration**.
- **schema:gender**: The (functional) attribute specifying the gender of a person is taken the **schema** vocabulary.
- **schema:homeLocation**: The (functional) attribute specifying the home country of a person is taken from the **schema** vocabulary.
- **schema:instructor**: The (functional) attribute specifying the lecturer of a lecture is taken from the **schema** vocabulary.
- **schema:name**: The data property specifying the name of an instance is taken from the **schema** vocabulary.
- **dbpedia:Country**: Countries are matched with corresponding countries from **dbpedia**.
- **schema:ComputerLanguage**: For the programming languages we use entities of **schema:ComputerLanguage**.
- **schema:Course**: The class **TU-Lecture**, representing a lecture at TU Wien, is modelled as a subclass of **schema:Course**.
- **schema:Person**: The two types of person we deal with, **Developer** and **Lecturer**, are modelled as subclasses of **schema:Person**.
- **schema:Role**: The developer and data scientist roles are modelled as subclasses of **schema:Role**.

We have specified attributes like inverse, functional or range and domain for all relations.

The ontology developed is depicted in Figure 2.

Task 4: Knowledge Graph

Kaggle User Survey

StackOverflow User Survey

GitHub Repositories Data

The CSV file created from the data gathering and compilation, as described in the Task 2 description, is then processed using a Python script to create a Turtle RDF file. Here is just the representation of the first two repositories:

```
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>
@prefix schema: <http://schema.org/>
@prefix group1: <http://www.semanticweb.org/sws/ws2019/group1#>
@prefix xsd: <http://www.w3.org/2001/XMLSchema#>

<https://api.github.com/repos/matplotlib/basemap> rdf:type group1:GitHubRepository ;
    group1:isDevelopedIn group1:Cplusplus ;
    schema:name "matplotlib/basemap"^^xsd:string ;
    group1:issues "515"^^xsd:integer ;
    group1:popularity "211"^^xsd:integer .

<https://api.github.com/repos/cocos2d/cocos2d-x> rdf:type group1:GitHubRepository ;
    group1:isDevelopedIn group1:Cplusplus ;
    schema:name "cocos2d/cocos2d-x"^^xsd:string ;
    group1:issues "19559"^^xsd:integer ;
```

```
group1:popularity "5715"^^xsd:integer .
```

The most tedious task of the cleanup is to make the programming languages of GitHub match with them from the other data sources. E.g. in GitHub it is written C++, while in the other data sources this language is referred to Cplusplus.

TISS Lectures

Task 5: Triple Store

For storing the data we were using Jena. We have installed an instance on the Internet for easier collaboration and app deployment.

Task 6: SPARQL Queries

These are just two sample SPARQL queries we have been developing.

Query 1: Which TU lectures deal with a specific programming language?

```
PREFIX rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>
PREFIX group1: <http://www.semanticweb.org/sws/ws2019/group1#>
PREFIX schema: <http://schema.org/>
```

```
SELECT ?name ?programming_language
WHERE {
  ?lecture schema:name ?name .
  ?lecture group1:dealsWith ?programming_language .
  FILTER (?programming_language = ${language})
}
LIMIT 25
```

Query 2: With my income wish, role and programming language skills - shall I stay or shall I go?

```
PREFIX rdf:<http://www.w3.org/1999/02/22-rdf-syntax-ns#>
PREFIX group1:<http://www.semanticweb.org/sws/ws2019/group1#>
PREFIX schema:<http://schema.org/>
PREFIX dbpedia:<http://dbpedia.org/resource/>
PREFIX rdfs:<http://www.w3.org/2000/01/rdf-schema#>
PREFIX sc:<http://purl.org/science/owl/sciencecommons/>
PREFIX xsd:<http://www.w3.org/2001/XMLSchema#>
```

```
ASK
WHERE {
  ?developer a group1:Developer .
  ?developer schema:homeLocation ?country .
  ?developer group1:developsIn ?language .
  ?developer group1:hasRole ?role .
  {
    SELECT ?country (AVG(?avgRange) as ?averageK)
    WHERE {
      ?developer a group1:Developer .
      ?developer group1:hasRole ?role .
      ?developer schema:homeLocation ?country .
```

```

        ?developer group1:developsIn ?language .
        ?developer group1:hasSalaryRange ?salaryRange .
        ?salaryRange group1:minSalary ?minSalary .
        ?salaryRange group1:maxSalary ?maxSalary .
        BIND ((?minSalary + ?maxSalary)/2 AS ?avgRange)
    }
    GROUP BY ?country
}
{
    SELECT ?country (AVG(?salaryValue) as ?averageS)
    WHERE {
        ?developer a group1:Developer .
        ?developer group1:hasRole ?role .
        ?developer schema:homeLocation ?country .
        ?developer group1:developsIn ?language .
        ?developer group1:salary ?salaryValue .
    }
    GROUP BY ?country
}
BIND ((?averageK + ?averageS)/2 as ?average)
FILTER (?language = ${language} && ?country = ${country} &&
        ?average > "${salary}"^^xsd:integer && ?role = ${role})
}
GROUP BY ?country ?average

```

Task 7: App Implementation

We used `jquery` when implementing the app. The app is interacting with Apache Jena using SOH - *SPARQL over HTTP*.

To avoid dealing with *CORS* (Cross-Origin Resource Sharing) issues, we have deployed the app in the same server as Apache Jena. It is accessible at <https://jena.helmuth.at/app>. For security reasons we have added username and password protection. Please use the following credentials to access the app (<https://jena.helmuth.at/app>) or the Jena Server (<https://jena.helmuth.at/>):

- **Username:** group1
- **Password:** gurus2020