

API Reference Guide

1. Authentication

All API requests must include an API key in the Authorization header. Keys can be generated from the developer dashboard under Settings, then API Keys. Each key is scoped to a single project and can be revoked at any time without affecting other keys.

Requests without a valid key return a 401 Unauthorized response with a JSON body describing the error. Expired keys return the same status code but a different error message.

2. Rate Limits

Requests are limited to 1000 per minute per API key on the standard plan, and 5000 per minute on the enterprise plan. Exceeding the limit returns a 429 status code along with a Retry-After header indicating how many seconds to wait before retrying.

Rate limit usage can be checked at any time by calling the /usage endpoint, which returns the current count and the time remaining until the limit resets.

3. Pagination

List endpoints return a maximum of 100 items per page by default. Use the cursor parameter from the previous response to fetch the next page. The final page is indicated by an empty next_cursor field in the response body.

4. Webhooks

Webhooks notify your server when an event occurs, such as a completed transaction or a failed payment. Configure webhook endpoints from the dashboard, and verify incoming requests using the signature header to confirm they originated from our servers.

Failed webhook deliveries are retried up to five times with exponential backoff. After the fifth failure, the webhook is marked as failing and an alert email is sent to the account owner.

5. Error Codes

The API uses standard HTTP status codes. 400 indicates a malformed request, 401 indicates missing or invalid authentication, 404 indicates the resource does not exist, and 500 indicates an internal server error. Every error response includes a machine-readable code and a human-readable message in the response body.

6. Versioning

The API version is specified in the URL path, for example /v2/transactions. Older versions remain supported for at least twelve months after a new version is released, and breaking changes are always announced at least ninety days in advance on the developer changelog.