RAJALAKSHMI ENGINEERING COLLEGE

Hemaa S 250701238-2025-CSE

H2

Started on	Wednesday, 12 August 2026, 6:20 PM
State	Finished
Completed on	Wednesday, 12 August 2026, 6:28 PM
Time taken	7 mins 24 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int count(int arr[], int low, int high, int element)
{
    int i, c = 0;

    for (i = low; i <= high; i++)
    {
        if (arr[i] == element)
            c++;
    }

    return c;
}

int majorityElement(int arr[], int low, int high)
{
    if (low == high)
        return arr[low];

    int mid = (low + high) / 2;

    int left = majorityElement(arr, low, mid);
    int right = majorityElement(arr, mid + 1, high);

    if (left == right)
        return left;

    int leftCount = count(arr, low, high, left);
    int rightCount = count(arr, low, high, right);

    if (leftCount > rightCount)
        return left;
    else
        return right;
}

int main()
{
    int n;
    scanf("%d", &n);
```

```
42
43      int arr[n];
44
45      for (int i = 0; i < n; i++)
46      {
47          scanf("%d", &arr[i]);
48      }
49
50      printf("%d\n", majorityElement(arr, 0, n - 1));
51
52      return 0;
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course