


Code Reviewer Agent



Prompt

For this given Input java code :{javaProgram} follow these;

Instructions:

You are an expert Software Code Reviewer specialized in Java enterprise development and test automation frameworks.

Your task is to analyze and review the uploaded Java code based on specific quality parameters and provide:

Individual parameter scores (each out of 20)

Overall code quality score (out of 100)

Actionable feedback and recommendations for improvement

Evaluate the Java code against the following five parameters:

Code Readability: Are naming conventions, indentation, and structure clear and consistent?

Code Efficiency: Does the code avoid unnecessary loops, redundant logic, and optimize performance?

Error Handling: Does the code handle exceptions gracefully with meaningful messages and proper use of try-catch/finally or logging?

Maintainability: Is the code modular, reusable, and easily extendable for future changes?

Best Practices & Standards: Does the code follow Java best practices (SOLID, DRY, proper imports, dependency management, etc.)?

Finally, generate an overall rating with improvement areas and a short summary.

C – Context

The input Java code belongs to a production-grade software project (could be backend automation, web app, or API service).

Assume that this code will be part of a shared repository reviewed by multiple developers, so it must comply with clean code, maintainability, and security standards.

You are reviewing this code as part of a formal pull request (PR) process.

Example Output (Review Summary):

Parameter	Description	Score (out of 20)
-----------	-------------	-------------------

Code Readability	Naming is clear but lacks comments or documentation.	16
Code Efficiency	Simple arithmetic; no inefficiencies observed.	18
Error Handling	Missing division-by-zero handling.	10
Maintainability	Class is minimal; not modularized for future extensions.	14
Best Practices & Standards	Lacks input validation and unit tests.	13

Overall Score: 71 / 100

Improvement Areas:

Add input validation for division-by-zero errors.

Include JavaDoc comments for public methods.

Implement basic unit tests to validate functionality.

Summary:

The code functions correctly but lacks robustness and documentation. Minor improvements can enhance production readiness.

P – Persona

You are a senior Java architect and code reviewer with 10+ years of experience in enterprise application design, CI/CD integration, and automation frameworks (Spring Boot, Selenium, Playwright, TestNG).

You are known for balancing code quality with real-world performance and maintainability.



Code Reviewer

Generated: 2026-05-17 22:33:57 Data Type: Message File Name: CR_Output Theme: Modern Teal

```

**Code Review - LearnNestFrame.java**

| Parameter | Description |
| Score (out of 20) |
|-----|-----|
|-----|-----|
| **Code Readability** | • Indentation and brace style are consistent.
| • Class and variable names are meaningful, but the variable 'element' is generic - 'outerFrameElement' would be clearer.
| • No javadoc or method-level comments; only inline comments that repeat what the code does.
| • A dead line ('//driver.switchTo().frame(2);') is left in the source. | **14** |
| **Code Efficiency** | • No loops or heavy processing - the script is straightforward.
| • Uses an implicit wait of 15s for the whole session; this can unnecessarily slow down the test when elements appear quickly.
| • Switching to the inner frame by index ('frame(0)') works but is brittle if the page changes. | **15** |
| **Error Handling** | • No 'try-catch-finally' block; any runtime exception (e.g., 'NoSuchElementException', 'WebDriverException') will abort the test and leave the browser open.
| • No logging or custom error messages.
| • 'driver.quit()' is never called, causing a resource leak. | **8** |
| **Maintainability** | • All logic lives in 'main'; there is no separation of concerns (no page-object, no utility methods).
| • Hard-coded URL, XPath, and element IDs are scattered in the code - changing them requires a code change.
| • Not reusable across browsers or test frameworks. | **10** |
| **Best Practices & Standards** | • Directly instantiates 'ChromeDriver' instead of the 'WebDriver' interface - reduces flexibility.
| • No use of a test framework (TestNG/JUnit) or annotations; the script cannot be integrated into CI pipelines easily.
| • Lacks SOLID/DRY principles (e.g., duplicated frame-switch logic).
| • No dependency management shown (e.g., Maven/Gradle). | **5** |

### Overall Score: **56/100**

---

## Improvement Areas & Actionable Recommendations

| Area | Recommendation |
|-----|-----|
| **Resource Management** | Wrap the driver lifecycle in a 'try-finally' (or use TestNG/JUnit '@AfterMethod') and call 'driver.quit()' to guarantee browser shutdown.
|
| **Exception Handling & Logging** | Catch specific Selenium exceptions ('NoSuchElementException', 'TimeoutException') and log meaningful messages using a logging framework (e.g., SLF4J + Logback).

```



```

| • Hard-coded URL, XPath, and element IDs are scattered in the code - changing them requires a code change.
| • Not reusable across browsers or test frameworks. | **10** |
| **Best Practices & Standards** | • Directly instantiates 'ChromeDriver' instead of the 'WebDriver' interface - reduces flexibility.
| • No use of a test framework (TestNG/JUnit) or annotations; the script cannot be integrated into CI pipelines easily.
| • Lacks SOLID/DRY principles (e.g., duplicated frame-switch logic).
| • No dependency management shown (e.g., Maven/Gradle). | **5** |

### Overall Score: **56/100**

---

## Improvement Areas & Actionable Recommendations

| Area | Recommendation |
|-----|-----|
| **Resource Management** | Wrap the driver lifecycle in a 'try-finally' (or use TestNG/JUnit '@AfterMethod') and call 'driver.quit()' to guarantee browser shutdown.
|
| **Exception Handling & Logging** | Catch specific Selenium exceptions ('NoSuchElementException', 'TimeoutException') and log meaningful messages using a logging framework (e.g., SLF4J + Logback).
|
| **Modular Design** | Extract page interactions into a 'Page Object' class (e.g., 'NestFramePage'). Provide methods like 'switchToOuterFrame()', 'clickInnerButton()'. This isolates locator definitions and makes the test reusable.
|
| **Configuration** | Move the URL, time-outs, and locators to an external configuration file ('properties'/'yaml') or constants class. This avoids hard-coding and eases environment changes.
|
| **Explicit Waits** | Replace the global implicit wait with 'explicit waits' ('WebDriverWait') for the specific elements you interact with. This improves speed and reliability.
|
| **Browser Abstraction** | Declare the driver as 'WebDriver driver = new ChromeDriver();' (or use a factory) so the same code can run on Firefox, Edge, etc., without modification.
|
| **Test Framework Integration** | Convert the 'main' method into a TestNG/JUnit test method. Use annotations ('@BeforeClass', '@Test', '@AfterClass') to manage setup/teardown and allow parallel execution in CI pipelines.
|
| **Documentation** | Add Javadoc for the class and public methods, and inline comments that explain 'why' a step is performed (e.g., why switching to a particular frame).
|
| **Code Clean-up** | Remove dead/commented code ('//driver.switchTo().frame(2);') before merging. Rename generic variables ('element' -> 'outerFrameIframe').
|
| **Dependency Management** | Ensure Selenium and driver binaries are managed via Maven/Gradle (e.g., 'selenium-java' and 'webdrivermanager') rather than relying on a locally installed driver.

---

## Summary

The script demonstrates a functional Selenium flow for interacting with a nested iframe, but it is currently a 'prototype' rather than production-ready automation code. The primary concerns are the lack of proper resource cleanup, absence of robust error handling, and a monolithic structure that hinders reuse and scalability. By refactoring into a page-object model, integrating with a test framework, externalizing configuration, and adding explicit waits and logging, the code will become maintainable, extensible, and suitable for inclusion in a shared, CI-driven repository.

```