Output:

```
Enter hostname or IP address : google.com
pinging 142.250.183.14
Reply from 142.250.183.14 : time = 32 ms.
Reply from 142.250.183.14 : time = 29 ms.
Reply from 142.250.183.14 : time = 31 ms.
Reply from 142.250.183.14 : time = 30 ms.
```

Exp No: 13
Date: 24/9/26

Implement Your Own Ping Program

Aim: To implement a Simple Ping Program in Java to check whether a host is reachable and Calculate the response time.

Algorithm:

1. Read the hostname or IP address from the User.
2. Get the IP address using InetAddress.
3. Send a ping request using isReachable().
4. Record the start and end time.
5. Calculate the response time.
6. Display whether the host is reachable.

Program:

```
import java.net.InetAddress;
import java.util.Scanner;
public class Myping {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        System.out.print("Enter hostname or IP address: ");
        String host = sc.nextLine();
        try {
            InetAddress address = InetAddress.getByName(host);
            System.out.println("Pinging " + address.getHostAddress
            for (int i=1; i<=4; i++) {
                long start = System.currentTimeMillis();
                boolean reachable = address.isReachable(3000);
```

```
            long end = System.currentTimeMillis();
            long time = end - start;

            if (reachable) {
                System.out.println("Reply from " + address.getHost
                                    Address() + ": time=" + time + "
                                                ms");
            } else {
                System.out.println("Request timed out.");
            }
            Thread.sleep(1000);
        }
    } catch (Exception e) {
            System.out.println("Error: " + e.getMessage());
    }
    sc.close();
  }
}
```

Result:

Thus, a Simple Ping program was Successfully implemented in Java to check host reachability and measure response time.