Mini Project 01 — Motor Insurance Claim Intake and Triage Service

Course: UE24AM342AA5 — ML System Design and AgentOps | **Domain:** General Insurance
Component: Jackfruit (Level 3), 10 marks | **Team size:** 2–3 students

Technical terms used here are defined in `00_GLOSSARY.pdf`.

---

1. Context

Every motor insurer in India runs a claims intake pipeline. When a vehicle is damaged, the customer files a **First Notice of Loss (FNOL)**. The FNOL is mostly free text. It arrives through a call centre, an app, or a web form.

> **FNOL — First Notice of Loss.** The first report of an incident to the insurer. Structured fields such as policy number, date of loss and vehicle registration, plus a free-text description of what happened.

A claims handler then does four things. They check the submission is complete and consistent. They work out what kind of claim it is. They look up the policy wording to see what is covered. They route the claim — fast-track for small cashless repairs, a surveyor for larger ones, an investigation team if something looks wrong.

This is a high-volume, latency-sensitive, correctness-critical pipeline. Getting the coverage position wrong is a regulatory and financial problem.

---

2. What to Build

A multi-agent service that accepts an FNOL, validates it, determines the likely coverage position from the policy wording, and routes the claim to the correct queue with a justification.

This is a production service, not a notebook.

The system never approves or rejects a claim. It produces a recommendation with supporting evidence. A human claims handler decides.

---

3. Corpus

Indian insurers publish full policy wordings as PDFs on their websites. Select one insurer and one product. All documents below are free to download.

- One complete private car package policy wording from one insurer
- The same insurer's claims procedure document

Prefer documents with a text layer. A scanned document needs optical character recognition (OCR) before it can be indexed.

Why this corpus is difficult. Policy wordings define terms in one place, state the cover in another, and list restrictions and exclusions in a third. An answer taken from the cover section alone is often wrong.

---

4. What the System Must Do

#	Requirement
F1	Accept an FNOL over a documented REST interface, against a published **data contract**
F2	Enforce schema, range, categorical and cross-field validation at the **ingestion boundary**. Quarantine rejects.
F3	Classify the claim - own damage, third party, theft, total loss - and extract the entities downstream stages need
F4	Retrieve the policy clauses relevant to the claim, including any restriction or exclusion that limits them
F5	Produce a **coverage position grounded in retrieved clauses**, with clause-level citations
F6	Route to one of: fast-track, surveyor assignment, or investigation. State the reason.

#	Requirement
F7	**Escalate to a human instead of answering** when retrieval is weak, clauses conflict, or the claim falls outside your corpus
F8	Expose health, metrics and structured logs for the whole pipeline

F5 and F7 hold most of the difficulty. A system that always answers is easy to build; one that knows when not to answer is not.

4.1 The difficult case

The system will be tested against this scenario at the demonstration.

"I was making a food delivery run in my own car when the accident happened."

A search about an accident retrieves the own-damage cover. But private car policies restrict the purposes for which the vehicle may be used, and that restriction sits in a different part of the policy which the query does not resemble. The system must find both and state whether the claim falls within the permitted use, citing both passages.

At Evaluation 1, show the passages in your corpus that this case depends on, and the values you will test with. Once confirmed, this is the reference answer for your demonstration.

---

5. Design Approach

The straightforward implementation embeds the request, retrieves the highest-scoring passages, and asks the model to answer from them. This handles ordinary cases but not the case in section 4.1.

The reason is structural. A single retrieval pass returns passages resembling the question asked. The case in section 4.1 turns on a provision the request never mentions, so a single embedding-based search is unlikely to return it.

The required approach is an agent that:

1. Retrieves the provision that appears to apply
2. Determines whether any other provision modifies it, and searches for such provisions
3. Searches again, using a query derived from what it has read
4. Verifies that the retrieved passages support the answer
5. Retries with a different strategy, or escalates, if they do not

Steps 2 and 4 distinguish an agent from a fixed pipeline. Both are assessed.

---

6. Agent System Requirements

Unit 4 — agent architecture, orchestration, containerisation, observability.

#	Requirement
A1	Build the reasoning layer with **LangGraph or CrewAI**. Retrieval must be a **tool the agent chooses to call**, not a fixed stage. Provide at least three tools, such as corpus search, lookup of a clause by identifier, and lookup of the request's own fields. **Bound the loop** by steps, tool calls and wall-clock time.
A2	**At least two agents with distinct responsibilities** and a defined hand-off. Document the topology and what happens if one fails mid-run. Two prompts in one process are not two agents.
A3	**Verify every answer against the passages retrieved, before returning it.** Every citation must resolve to retrieved text. If verification fails, search again with a different strategy or escalate. An unverified answer must not be returned. This is the basis of F7.
A4	Expose the service with **FastAPI**. Runs take tens of seconds, so **execute them asynchronously**: return a run identifier immediately, and the caller polls a status endpoint or receives a callback. Justify the choice. Place a queue or task runner between submission and execution.

#	Requirement
A5	**Timeouts** on every model and tool call, **bounded retry with exponential backoff**, a **circuit breaker** on the provider, and **graceful degradation** along a defined fallback path. All must be demonstrable on request. A run that did not complete must not be returned as a confident answer.
A6	Track per agent and display on the dashboard: **task success rate**, steps and tool calls per run, latency end to end and per step, **retry rate**, container uptime.
A7	`docker compose up --scale <agent-worker>=3` must work. Measure the effect on throughput and p95, using the stub described in D6. If scaling does not help, identify the actual bottleneck.
A8	A simple **web client** that submits a request, obtains the result, and displays the recommendation with citations and the escalation path. No marks for appearance.

7. LLMOps Requirements

Unit 3 — retrieval, prompt management, evaluation, guardrails, monitoring.

#	Requirement
L1	Orchestrate retrieval with **LangChain or LlamaIndex**; index with **FAISS or Chroma**. Document the chunking and embedding strategy and how it addresses the difficulty in section 3. Re-embedding must be possible without rebuilding the whole index.
L2	Treat prompts as **versioned artifacts**, and record the prompt version with every response. Compare **at least two prompt variants** on the same evaluation set; report which performed better, on which metric, and by how much.
L3	Build a fixed evaluation set of **at least 20 scenarios**, each with its expected outcome and the passage that supports it, including the case in section 4.1, runnable as a batch from the command line. Use **TruLens** or equivalent. Report **groundedness, context relevance, faithfulness and hallucination rate**, stating how each is computed. Then make one deliberate change and **report all four metrics before and after**.
L4	**Prompt injection defence** on every free-text field reaching a model, **output filtering** so the system cannot issue a determination it is not authorised to make, and **toxicity detection** on input and output. Agents are more exposed than pipelines, because injected text can reach a model holding tools.
L5	Record **prompt tokens, completion tokens and cost at the time of the call**, attributed **per step as well as per run**. Report cost per 100 runs and the largest single cost driver.
L6	A **feedback endpoint** allowing the caller to mark a result satisfactory or not, with a reason, persisted and aggregated. **Score a small sample of live runs automatically** against the evaluation metrics, charting quality over time.

8. Platform and Deployment Requirements

Units 1 and 2 — data contracts, architecture, containerisation, observability, reliability.

#	Requirement
D1	Publish a **data contract** for every external interface. Enforce schema, type, range, category and cross-field validation at the **ingestion boundary**, before any agent starts. **Quarantine rejected records with their field-level errors.** A malformed request must not start an agent run.
D2	An **idempotent** pipeline that reads, parses, chunks, embeds and indexes the corpus, invocable from a command-line tool. Record **data freshness** — when the index was built, from which versions, how many chunks — and the pipeline's throughput, and expose both as metrics.
D3	**At least four services** under Docker Compose, starting with a **single** `docker compose up` from a clean clone, with dependencies and health checks declared. Nothing runs outside the containers. **Justify the placement of deployment boundaries** on scaling, failure isolation, independent release or resource profile.
D4	**No credentials, endpoints or model identifiers anywhere in the repository.** All environment-specific configuration injected at runtime, with a documented `.env.example`.

#	Requirement
D5	**Structured logging** throughout, a **correlation ID** across every service and agent step, tracing with **OpenTelemetry** exported to Jaeger or Grafana Tempo, **Prometheus** scraping every service, and a **Grafana** dashboard showing p50/p95 latency, error rate, throughput, availability and resource utilisation per container. **Given a run identifier, the entire run must be reconstructible** — every tool call, query, passage, prompt version, per-step latency and cost, and the verification outcome.
D6	**Declare a p95 service level objective (SLO) for a complete run before measuring anything**, justified against section 1. Measure a run from submission to final result, not the submission call alone. Load test with **Locust**, with the LLM replaced by a **stub service** that returns fixed responses after a realistic delay, so that the test measures your system rather than the provider's rate limits. Report RPS, p50 and p95 against the target and state whether it was met. Identify **the concurrency at which the target fails and the component responsible**. A target set after seeing the results does not satisfy this requirement.
D7	**Caching** — of embeddings, retrievals or whole runs, justified — and **rate limiting** per client. Report the measured effect of caching on p95 and cost per run. Rate limiting is a cost control here: one client looping against a multi-step agent can exhaust the budget in minutes.
D8	A **runbook** for the two most likely failure modes — symptom, confirmation, recovery — and an **incident log** with at least one genuine entry recording a real failure during development.

9. Demonstration

Prepare all ten items.

#	Item
1	`docker compose up` from a clean clone to a working system
2	A valid request producing a routed recommendation with citations that resolve to retrieved text
3	One run traced end to end — every tool call, query, passage, prompt version, per-step latency and cost
4	A malformed request rejected and quarantined, with evidence that no agent run started
5	A case the corpus cannot answer producing an escalation rather than a fabricated response
6	Self-verification catching an unsupported answer, followed by a further search or escalation
7	A prompt injection attempt and the guardrail response
8	The circuit breaker opening when the provider is unavailable, and the degradation path
9	Locust results against the declared target, the concurrency at which it fails, and the effect of `--scale`
10	The case in section 4.1, handled correctly

10. Assessment

If the system does not start and serve a valid request at the demonstration, the project is awarded zero marks, irrespective of the report, presentation or repository.

Establish a working end-to-end path by week two and add requirements after that. Completing all 22 requirements is not expected; sound prioritisation is itself assessed.

Criterion	Marks
Problem understanding, architecture and objective clarity	10
Presentation, teamwork and communication	10
Engineering judgement — tool selection, scope, handling of constraints	10
Report, code quality and repository documentation	10
Total (Evaluation 2, scaled to 8 marks)	**40**

11. Deliverables

Deliverable	Due
Corpus confirmation and project plan	Evaluation 1
Report and final GitHub repository	**One week before the presentation**
Live demonstration and viva	Evaluation 2

Report — a plain report covering, briefly: problem and scope; agent design (topology, tools, verification, loop limits); an architecture diagram with deployment boundaries marked; design decisions and what was rejected; evaluation results before and after the change; the p95 target, measured results, bottleneck and cost per 100 runs; and what did not work.

Repository — the README must be sufficient for someone unfamiliar with the project to run the system without assistance. This will be tested. Include the runbook, incident log, `.env.example` and evaluation set.

12. Cost

All software and data required are free. The corpus documents are public; **sentence-transformers run locally for embeddings at no cost**, and a small model such as all-MiniLM-L6-v2 keeps memory use low; FAISS, Chroma, LangGraph, CrewAI, LangChain, LlamaIndex, TruLens, FastAPI, Redis, Prometheus, Grafana, OpenTelemetry, Jaeger and Locust are all free. For the model, use a provider's free tier. A local model via Ollama is also possible but needs a considerably more powerful machine.

Embed locally. Embedding a corpus through a paid API is the only operation here with a real cost.

Agents multiply model calls — typically several per run, against one for a fixed pipeline. Free tiers also have low rate limits, which is why load testing uses a stub (D6). This is the reason for the loop limits in A1, the caching in D7 and the per-step cost tracking in L5. Set a spending limit on the account before starting, and place the model behind an interface you control so the provider can be changed by configuration.

13. Out of Scope

- Model training is not required.
- Cloud deployment is not required; the system runs locally under Docker Compose.
- **Do not attempt settlement amount calculation.** The system is advisory only, by design.