

Aim:

Write code to calculate **roots** of a **quadratic equation**.

Write a class `QuadraticRoots` with `main` method. The method receives three arguments, write code to parse them into `double` type.

For example:

if the values 2, 5, 3 are passed as arguments, then the output should be **First root is : -1.0 Second root is : -1.5**
If the values 3, 2, 1 are passed then the output should be **Roots are imaginary**
Similarly, if the values 2, 4, 2 are passed then the output should be **Roots are equal and value is : -1.0**

Note: Make sure to use the `print()` and not the `println()` method.

Note: Please don't change the package name.

Source Code:

q10851/QuadraticRoots.java

```
package q10851;
class QuadraticRoots
{
    double a,b,c;
    void getData(String c1,String c2,String c3)
    {
        a=Double.valueOf(c1);
        b=Double.valueOf(c2);
        c=Double.valueOf(c3);
    }
    void roots()
    {
        double d;
        if(a==0)
        {
            double root;
            root=c/b;
            System.out.println("linear equation"+root);
        }
        else
        {
            d=(b*b)-(4*a*c);

            if(d==0)
            {
                double root =-b/(2*a);
                System.out.println("Roots are equal and value is : "+root);
            }
            else if(d>0)
```

```

        {
            double r1,r2;
            r1=(-b+Math.sqrt(d))/(2*a);
            r2=(-b-Math.sqrt(d))/(2*a);
            System.out.println("First root is : "+r1+" Second root is : "+r2);
        }
        else
            System.out.println("Roots are imaginary");
    }
}

public static void main(String a[])
{
    QuadraticRoots r=new QuadraticRoots();
    r.getData(a[0],a[1],a[2]);
    r.roots();
}
}

```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
First root is : -0.6047152924789525 Second root is : -1.3952847075210475

Test Case - 2
User Output
Roots are equal and value is : -1.0

Test Case - 3
User Output
Roots are imaginary