

1. Use `map()` with a `lambda` to add 5 to every element of the following nested list `[[1, 2], [3, 4], [5, 6]]`
2. Given a dictionary: `d = {"apple": 100, "banana": 40, "cherry": 150}` . Use `filter()` to keep only the keys whose values are greater than 50.
3. Use `functools.reduce()` with a `lambda` to find the largest number from a given list Dynamically.
4. What happens if the `lambda` passed to `reduce()` accepts only one parameter or three parameters? Explain the output or error.
5. Use `map()` on a string to convert each character into its ASCII value (using `ord()`). Print the result list.
6. Use `filter()` to remove all vowels from a string and print the final string.
7. Use `reduce()` to concatenate a list of characters into a single string.
Example input: `['P', 'y', 't', 'h', 'o', 'n']`.
8. Given a list of integers, use `map()` with `id()` to print the memory address of each element.
Example: `[10, 350, 10, 350, 20]` – explain why some addresses repeat.
9. Explain the difference between:
`map(str, [1, 2, 3])`
`map(lambda x: str(x), [1, 2, 3])`
Which one is faster and why?
10. Given a list of numbers:
`[5, 10, 15, 20, 25, 30]`
Perform the following in a single pipeline:
 - Use `map()` to square each number
 - Use `filter()` to keep only numbers divisible by 5
 - Use `reduce()` to calculate the sum of remaining numbers