

Bubble Sort

(What are Algorithms and How to Analyze Algorithms)

Hengfeng Wei

Institute of Computer Software
Nanjing University

December 17, 2016



Bubble Sort

- 1 Sorting
- 2 Bubble Sort
- 3 Analysis

Bubble Sort

- 1 Sorting
- 2 Bubble Sort
- 3 Analysis

Sorting

The sorting problem:

Input: A sequence A of n integers $a_1 a_2 \cdots a_n$.

Output: A permutation $a'_1 a'_2 \dots a'_n$ of A *s.t.*
 $a'_1 \leq a'_2 \leq \cdots \leq a'_n$ (non-decreasing order).

Sorting

The sorting problem:

Input: A sequence A of n integers $a_1 a_2 \cdots a_n$.

Output: A permutation $a'_1 a'_2 \dots a'_n$ of A *s.t.*
 $a'_1 \leq a'_2 \leq \cdots \leq a'_n$ (non-decreasing order).

$$3\ 1\ 4\ 2 \implies 1\ 2\ 3\ 4$$

Sorting Algorithms

An algorithm is a sequence of computational steps that transform the input into the output.

Sorting Algorithms

An algorithm is a sequence of computational steps that transform the input into the output.

Definiteness: precisely defined steps

Sorting Algorithms

An algorithm is a sequence of computational steps that transform the input into the output.

Definiteness: precisely defined steps

Finiteness: termination

Sorting Algorithms

An algorithm is a sequence of computational steps that transform the input into the output.

Definiteness: precisely defined steps

Finiteness: termination

Effectiveness: operations are sufficiently basic

Sorting Algorithms

An algorithm is a sequence of computational steps that transform the input into the output.

Definiteness: precisely defined steps

Finiteness: termination

Effectiveness: operations are sufficiently basic

- RAM (Random-Access Machine) model

Sorting Algorithms

An algorithm is a sequence of computational steps that transform the input into the output.

Definiteness: precisely defined steps

Finiteness: termination

Effectiveness: operations are sufficiently basic

- RAM (Random-Access Machine) model
- unrealistic: **sort** instruction

Sorting Algorithms

An algorithm is a sequence of computational steps that transform the input into the output.

Definiteness: precisely defined steps

Finiteness: termination

Effectiveness: operations are sufficiently basic

- RAM (Random-Access Machine) model
- unrealistic: **sort** instruction
- realistic: arithmetic, data movement, and control

Sorting Algorithms

An algorithm is a sequence of computational steps that transform the input into the output.

Definiteness: precisely defined steps

Finiteness: termination

Effectiveness: operations are sufficiently basic

- RAM (Random-Access Machine) model
- unrealistic: **sort** instruction
- realistic: arithmetic, data movement, and control
- **CAS for sort:** compare and swap if out-of-order

Inversions

$$A = a_1, a_2, \dots, a_n.$$

If $i < j$ and $a_i > a_j$, then (a_i, a_j) is an **inversion**.

Inversions

$$A = a_1, a_2, \dots, a_n.$$

If $i < j$ and $a_i > a_j$, then (a_i, a_j) is an **inversion**.

$$A = 3, 1, 4, 2.$$

Inversions: $(3, 1), (3, 2), (4, 2)$

Inversions

$$A = a_1, a_2, \dots, a_n.$$

If $i < j$ and $a_i > a_j$, then (a_i, a_j) is an **inversion**.

$$A = 3, 1, 4, 2.$$

Inversions: $(3, 1), (3, 2), (4, 2)$

Adjacent inversion: $j = i + 1$

Inversions

$$A = a_1, a_2, \dots, a_n.$$

If $i < j$ and $a_i > a_j$, then (a_i, a_j) is an **inversion**.

$$A = 3, 1, 4, 2.$$

Inversions: $(3, 1), (3, 2), (4, 2)$

Adjacent inversion: $j = i + 1$

Inversions

A is sorted $\implies A$ has no inversions
 $\implies A$ has no adjacent inversions.

Inversions

A is sorted $\implies A$ has no inversions
 $\implies A$ has no adjacent inversions.

A has no adjacent inversions $\implies \forall i \in [1, n-1] : a_i \leq a_{i+1}$
 $\implies A$ is sorted.

Inversions

A is sorted $\implies A$ has no inversions
 $\implies A$ has no adjacent inversions.

A has no adjacent inversions $\implies \forall i \in [1, n-1] : a_i \leq a_{i+1}$
 $\implies A$ is sorted.

A is sorted $\iff A$ has no adjacent inversions.
--

Bubble Sort

- 1 Sorting
- 2 Bubble Sort
- 3 Analysis

Bubble Sort

Basic idea: to eliminate all adjacent inversions

```
1: procedure BUBBLESORTOVERVIEW( $A : a_1 a_2 \cdots a_n$ )
2:   repeat
3:     Pick any  $i$ 
4:     if  $a_i > a_{i+1}$  then                                ▷ CAS
5:       SWAP( $a_i, a_{i+1}$ )
6:   until no adjacent inversions
```

Bubble Sort

Basic idea: to eliminate all adjacent inversions

```
1: procedure BUBBLESORTOVERVIEW( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     Pick any  $i$ 
4:     if  $a_i > a_{i+1}$  then                                ▷ CAS
5:       SWAP( $a_i, a_{i+1}$ )
6:   until no adjacent inversions
```

Definiteness!

Bubble Sort

Basic idea: to eliminate all adjacent inversions

```
1: procedure BUBBLESORTOVERVIEW( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     Pick any  $i$ 
4:     if  $a_i > a_{i+1}$  then                                ▷ CAS
5:       SWAP( $a_i, a_{i+1}$ )
6:   until no adjacent inversions
```

Definiteness!

Finiteness!

Bubble Sort

```
1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
```

```
2:   repeat
```

```
3:
```

```
4:   for  $i \leftarrow 1 : n - 1$  do
```

▷ Pick i

```
5:       if  $a_i > a_{i+1}$  then
```

```
6:         SWAP( $a_i, a_{i+1}$ )
```

```
7:
```

```
8:   until
```

Bubble Sort

```
1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
```

```
2:   repeat
```

```
3:     swapped  $\leftarrow$  false
```

```
4:     for  $i \leftarrow 1 : n - 1$  do
```

▷ Pick i

```
5:       if  $a_i > a_{i+1}$  then
```

```
6:         SWAP( $a_i, a_{i+1}$ )
```

```
7:
```

```
8:   until
```

Bubble Sort

```
1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until 
```

▷ Pick i

Bubble Sort

```
1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false
```

▷ Pick i

Bubble Sort

```
1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false
```

▷ Pick i

Definiteness!

Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 a_2 \cdots a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do           ▷ Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false           ▷ No swaps

```

2

4

1


3

Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 a_2 \cdots a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do           ▷ Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false           ▷ No swaps

```




Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 a_2 \cdots a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```




Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \dots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```




Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 a_2 \cdots a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```




Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 a_2 \cdots a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```




Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 a_2 \cdots a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```




Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 a_2 \dots a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```




Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 a_2 \dots a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```




Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 a_2 \dots a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```



Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```

Finiteness!

Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```

Finiteness!

The inner “**for**” loops:

1) \exists loop : no swaps \implies swapped = false \implies terminates

Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```

Finiteness!

The inner “**for**” loops:

- 1) \exists loop : no swaps \implies swapped = false \implies terminates
- 2) \forall loop : has swaps

Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```


Finiteness!

The inner “**for**” loops:

- 1) \exists loop : no swaps \implies swapped = false \implies terminates
- 2) \forall loop : has swaps **Impossible!**


Bubble Sort

Effects of $\text{SWAP}(a_i, a_{i+1})$ on adjacent inversions:



Bubble Sort


Effects of $\text{SWAP}(a_i, a_{i+1})$ on adjacent inversions:



$-1 : (7, 2)$


Bubble Sort

Effects of $\text{SWAP}(a_i, a_{i+1})$ on adjacent inversions:




Bubble Sort

Effects of $\text{SWAP}(a_i, a_{i+1})$ on **#inversions**:



Bubble Sort


Effects of $\text{SWAP}(a_i, a_{i+1})$ on **#inversions**:



$$-1 : (a_i, a_{i+1})$$


Bubble Sort

Effects of $\text{SWAP}(a_i, a_{i+1})$ on **#inversions**:



Bubble Sort

Effects of $\text{SWAP}(a_i, a_{i+1})$ on **#inversions**:



$-1 : (a_i, a_{i+1})$

$+0$

Total #inversions is finite.

Optimizing Bubble Sort

```
1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:    $n \leftarrow \text{len}(A)$ 
3:   repeat
4:     swapped  $\leftarrow$  false
5:     for  $i \leftarrow 1 : n - 1$  do
6:       if  $a_i > a_{i+1}$  then
7:         SWAP( $a_i, a_{i+1}$ )
8:         swapped  $\leftarrow$  true
9:      $n \leftarrow n - 1$ 
10:  until swapped = false
```

▷ One maximal bubbles up

Optimizing Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     lsp  $\leftarrow$  0                                ▷ lsp: the last swap position
5:     for  $i \leftarrow 1 : n - 1$  do
6:       if  $a_i > a_{i+1}$  then
7:         SWAP( $a_i, a_{i+1}$ )
8:         swapped  $\leftarrow$  true
9:         lsp  $\leftarrow$  i                            ▷ Update lsp
10:     $n \leftarrow$  lsp                               ▷ Elements after lsp are sorted
11:  until swapped = false

```

Optimizing Bubble Sort

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:      $\text{swapped} \leftarrow \text{false}$ 
4:      $\text{lsp} \leftarrow 0$                                 ▷  $\text{lsp}$ : the last swap position
5:     for  $i \leftarrow 1 : n - 1$  do
6:       if  $a_i > a_{i+1}$  then
7:         SWAP( $a_i, a_{i+1}$ )
8:          $\text{swapped} \leftarrow \text{true}$ 
9:          $\text{lsp} \leftarrow i$                             ▷ Update  $\text{lsp}$ 
10:     $n \leftarrow \text{lsp}$                                 ▷ Elements after  $\text{lsp}$  are sorted
11:   until  $\text{swapped} = \text{false}$ 

```

Optimizing Bubble Sort

```
1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:      $\text{lsp} \leftarrow 0$                                 ▷  $\text{lsp}$ : the last swap position
4:     for  $i \leftarrow 1 : n - 1$  do
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:          $\text{lsp} \leftarrow i$                                 ▷ Update  $\text{lsp}$ 
8:      $n \leftarrow \text{lsp}$                                 ▷ Elements after  $\text{lsp}$  are sorted
9:   until  $n = 0$ 
```

Bubble Sort

- 1 Sorting
- 2 Bubble Sort
- 3 Analysis**

Time Complexity of Bubble Sort

- Finiteness is NOT enough \implies Quantitative finiteness

Time Complexity of Bubble Sort

- Finiteness is NOT enough \implies Quantitative finiteness
- Time on real computers varies \implies #Ops on RAM model:

Time Complexity of Bubble Sort

- Finiteness is NOT enough \implies Quantitative finiteness
- Time on real computers varies \implies #Ops on RAM model:

$|P|$: #Passes (the “**for**” loops)

$|C|$: #Comparisons (**if** $a_{i-1} > a_i$)

$|S|$: #Swaps (SWAP(a_{i-1}, a_i))

Time Complexity of Bubble Sort

- Finiteness is NOT enough \implies Quantitative finiteness
- Time on real computers varies \implies #Ops on RAM model:
 - $|P|$: #Passes (the “**for**” loops)
 - $|C|$: #Comparisons (**if** $a_{i-1} > a_i$)
 - $|S|$: #Swaps (SWAP(a_{i-1}, a_i))
- Different inputs \implies different execution time:

Time Complexity of Bubble Sort

- Finiteness is NOT enough \implies Quantitative finiteness
- Time on real computers varies \implies #Ops on RAM model:
 - $|P|$: #Passes (the “**for**” loops)
 - $|C|$: #Comparisons (**if** $a_{i-1} > a_i$)
 - $|S|$: #Swaps (SWAP(a_{i-1}, a_i))
- Different inputs \implies different execution time:
 - Best-case, worst-case, and average-case analysis

Best-case and Worst-case Analysis

Best-case:

Worst-case:

$$|P| = (\quad);$$

$$|C| = (\quad);$$

$$|S| = (\quad).$$

Best-case and Worst-case Analysis

Best-case: 1 2 3 4 5 6 7 8

Best-case:
ascendingly sorted

Worst-case:

$|P| = (\quad);$

$|C| = (\quad);$

$|S| = (\quad).$

Best-case and Worst-case Analysis

Best-case: 1 2 3 4 5 6 7 8

Best-case:
ascendingly sorted

Worst-case:

$$|P| = (\min : 1, \quad);$$

$$|C| = (\min : n - 1, \quad);$$

$$|S| = (\min : 0, \quad).$$

Best-case and Worst-case Analysis

Best-case: 1 2 3 4 5 6 7 8

Best-case:
ascendingly sorted

Worst-case:
descendingly sorted

$$|P| = (\min : 1, \quad);$$

$$|C| = (\min : n - 1, \quad);$$

$$|S| = (\min : 0, \quad).$$

Worst-case: 8 7 6 5 4 3 2 1

Best-case and Worst-case Analysis

Best-case: 1 2 3 4 5 6 7 8

Best-case:
ascendingly sorted

Worst-case:
descendingly sorted

$$|P| = (\min : 1, \quad \max : n);$$

$$|C| = (\min : n - 1, \quad \max : \frac{n^2 - n}{2});$$

$$|S| = (\min : 0, \quad \max : \frac{n^2 - n}{2}).$$

Worst-case: 8 7 6 5 4 3 2 1

$|S|$: #Swaps (Average Analysis)

Assumptions on inputs:

1. The input is a random permutation
2. All numbers are distinct

$|S|$: #Swaps (Average Analysis)

Assumptions on inputs:

1. The input is a random permutation
2. All numbers are distinct

$$\boxed{\text{SWAP}(a_i, a_{i+1}) \implies -1 \text{ inversion}}$$

$|S|$: #Swaps (Average Analysis)

Assumptions on inputs:

1. The input is a random permutation
2. All numbers are distinct

$$\text{SWAP}(a_i, a_{i+1}) \implies -1 \text{ inversion}$$

Question: What is the expected #inversions?

$|S|$: #Swaps (Average Analysis)

I_{ij} : indicator of inversion (a_i, a_j)

$|S|$: #Swaps (Average Analysis)

I_{ij} : indicator of inversion (a_i, a_j)

$$X = \sum_j \sum_{i < j} I_{ij}$$

$|S|$: #Swaps (Average Analysis)

I_{ij} : indicator of inversion (a_i, a_j)

$$X = \sum_j \sum_{i < j} I_{ij}$$

$$E(X) = E\left(\sum_j \sum_{i < j} I_{ij}\right) = \sum_j \sum_{i < j} E(I_{ij})$$

$|S|$: #Swaps (Average Analysis)

I_{ij} : indicator of inversion (a_i, a_j)

$$X = \sum_j \sum_{i < j} I_{ij}$$

$$E(X) = E\left(\sum_j \sum_{i < j} I_{ij}\right) = \sum_j \sum_{i < j} E(I_{ij})$$

$$E(I_{ij}) = P\{I_{ij}\} = \frac{1}{2}$$

$|S|$: #Swaps (Average Analysis)

I_{ij} : indicator of inversion (a_i, a_j)

$$X = \sum_j \sum_{i < j} I_{ij}$$

$$E(X) = E\left(\sum_j \sum_{i < j} I_{ij}\right) = \sum_j \sum_{i < j} E(I_{ij})$$

$$E(I_{ij}) = P\{I_{ij}\} = \frac{1}{2}$$

$$E(X) = \sum_j \sum_{i < j} \frac{1}{2} = \binom{n}{2} \cdot \frac{1}{2} = \frac{n(n-1)}{4}$$