Hengfeng Wei

Institute of Computer Software Nanjing University

December 11, 2016







- The MST Problem
- 2 The Generic MST Algorithm
- 3 Kruskal's and Prim's Algorithms

- 1 The MST Problem
- 2 The Generic MST Algorithm
- 3 Kruskal's and Prim's Algorithms

G = (V, E): connected, undirected, weighted graph (w(e))




G = (V, E): connected, undirected, weighted graph (w(e))




Spanning tree $T = (V, E' \subseteq E)$: connected, acyclic

G = (V, E): connected, undirected, weighted graph (w(e))




Spanning tree $T = (V, E' \subseteq E)$: connected, acyclic $(\Rightarrow n-1 \text{ edges})$

G = (V, E): connected, undirected, weighted graph (w(e))




Spanning tree $T = (V, E' \subseteq E)$: connected, acyclic $(\Rightarrow n-1 \text{ edges})$

G = (V, E): connected, undirected, weighted graph (w(e))



Spanning tree $T=(V,E'\subseteq E)$: connected, acyclic $(\Rightarrow n-1 \text{ edges})$

G = (V, E): connected, undirected, weighted graph (w(e))




Spanning tree $T = (V, E' \subseteq E)$: connected, acyclic $(\Rightarrow n-1 \text{ edges})$


$$w(T) = \sum_{e \in E'} w(e)$$




 $MST: \quad \underset{T}{\operatorname{arg\,min}} \ w(T)$



 $MST: \quad \underset{T}{\operatorname{arg\,min}} \ w(T)$



 $MST: \quad \underset{T}{\operatorname{arg\,min}} \ w(T)$



Wrong divide-and-conquer algorithm for MST


Input: G = (V, E, w)

Divide: $V = (S, V \setminus S); ||S| - |V \setminus S|| \le 1$

Wrong divide-and-conquer algorithm for MST

Input: G = (V, E, w)

Divide: $V = (S, V \setminus S); ||S| - |V \setminus S|| \le 1$ (Cut)




Wrong divide-and-conquer algorithm for MST

Input: G = (V, E, w)

Divide: $V = (S, V \setminus S); ||S| - |V \setminus S|| \le 1$ (Cut)

Conquer: T_1 : an MST of S; T_2 : an MST of $V \setminus S$




Wrong divide-and-conquer algorithm for MST

Input: G = (V, E, w)


Divide: $V = (S, V \setminus S); ||S| - |V \setminus S|| \le 1$ (Cut)

Conquer: T_1 : an MST of S; T_2 : an MST of $V \setminus S$

Combine: $T_1 + T_2 + \{e\}$: e is a **lightest** edge across $(S, V \setminus S)$




What is wrong?



The edges bc and ad do **not** belong to any MST.

What is wrong?



The edges bc and ad do **not** belong to any MST.

What if:

Invariant: Manages a set of edges X which is a subset of **some** MST.



- The MST Problem
- 2 The Generic MST Algorithm
- 3 Kruskal's and Prim's Algorithms

Overview: Grow the MST one edge at a time

Overview: Grow the MST one edge at a time

State: Manage a set of edges X

Overview: Grow the MST one edge at a time

State: Manage a set of edges X

Invariant: X is a subset of some MST

Overview: Grow the MST one edge at a time

State: Manage a set of edges X

Invariant: X is a subset of some MST

Init: $X = \emptyset$

Overview: Grow the MST one edge at a time

State: Manage a set of edges X

Invariant: X is a subset of some MST

Init: $X = \emptyset$

Iteration: Find an edge e s.t.

 $X \cup \{e\}$ is also a subset of some MST

Overview: Grow the MST one edge at a time

State: Manage a set of edges X

Invariant: X is a subset of some MST

Init: $X = \emptyset$

Iteration: Find a safe edge $e \ s.t.$

 $X \cup \{e\}$ is also a subset of some MST

Overview: Grow the MST one edge at a time

State: Manage a set of edges X

Invariant: X is a subset of some MST

Init: $X = \emptyset$

Iteration: Find a safe edge $e \ s.t.$

 $X \cup \{e\}$ is also a subset of some MST

Termination: (n-1) iterations

Overview: Grow the MST one edge at a time

State: Manage a set of edges X

Invariant: X is a subset of some MST

Init: $X = \emptyset$


Iteration: Find a safe edge e s.t.

 $X \cup \{e\}$ is also a subset of some MST

Termination: (n-1) iterations


How to find a safe e for X in each iteration?

Given that X is part of some MST:




Given that X is part of some MST:

■ A cut $(S, V \setminus S)$ respecting X (X does not cross $(S, V \setminus S)$)




Given that X is part of some MST:

■ A cut $(S, V \setminus S)$ respecting X (X does not cross $(S, V \setminus S)$)




Given that X is part of some MST:

■ A cut $(S, V \setminus S)$ respecting X (X does not cross $(S, V \setminus S)$)




Given that X is part of some MST:

■ A cut $(S, V \setminus S)$ respecting X (X does not cross $(S, V \setminus S)$)




Given that X is part of some MST:


- A cut $(S, V \setminus S)$ respecting X (X does not cross $(S, V \setminus S)$)
- e: a lightest edge across $(S, V \setminus S)$



Given that X is part of some MST:

- A cut $(S, V \setminus S)$ respecting X (X does not cross $(S, V \setminus S)$)
- e: a lightest edge across $(S, V \setminus S)$






Basic idea: $e \notin T \Rightarrow e \in T'$.


- $\blacksquare T + \{e\}$ to construct a cycle C
- $\exists e' \in C$ such that e' across the cut; $w(e') \geq w(e)$
- $T' = T + \{e\} \{e'\}$
- $w(T') \le w(T) \Rightarrow w(T') = w(T) \Rightarrow T'$ is an MST




- 1 The MST Problem
- 2 The Generic MST Algorithm
- 3 Kruskal's and Prim's Algorithms

```
sort (non-descreasingly) the edges E X=\emptyset Y=\emptyset for e\in E in non-descreasing order Y=\emptyset if X\cup\{e\} does not produce cycle X\leftarrow X\cup\{e\}
```







```
sort (non-descreasingly) the edges E X=\emptyset for e\in E in non-descreasing order if X\cup\{e\} does not produce cycle X\leftarrow X\cup\{e\}
```





```
sort (non-descreasingly) the edges E
X=\emptyset
for e\in E in non-descreasing order
if X\cup\{e\} does not produce cycle
X\leftarrow X\cup\{e\}
```






```
sort (non-descreasingly) the edges E X=\emptyset for e\in E in non-descreasing order if X\cup\{e\} does not produce cycle X\leftarrow X\cup\{e\}
```





```
sort (non-descreasingly) the edges E : X=\emptyset for e\in E in non-descreasing order if X\cup\{e\} does not produce cycle X\leftarrow X\cup\{e\}
```



State: forest \triangleq a collection of connected components

Ops: on connected components

- cycle detection
- union two CCs


State: forest \triangleq a collection of connected components

Ops: on connected components


- cycle detection
- union two CCs

Using the **disjoint-set** data structure.


```
\begin{array}{lll} 1 & X=\emptyset \\ 2 & S=\{s\} \text{ // pick any } s\in V \\ 3 & R=V\setminus S \\ 4 & \text{while } R\neq\emptyset \\ 5 & e=(u,v)\leftarrow \text{ a lightest edge across } (S,R) \\ 6 & X\leftarrow X\cup\{e\} \\ 7 & S\leftarrow S\cup\{u\} & R\leftarrow R\setminus\{v\} \end{array}
```




```
\begin{array}{lll} 1 & X=\emptyset \\ 2 & S=\{s\} \text{ // pick any } s\in V \\ 3 & R=V\setminus S \\ 4 & \text{while } R\neq\emptyset \\ 5 & e=(u,v)\leftarrow \text{ a lightest edge across } (S,R) \\ 6 & X\leftarrow X\cup\{e\} \\ 7 & S\leftarrow S\cup\{u\} & R\leftarrow R\setminus\{v\} \end{array}
```




```
\begin{array}{lll} 1 & X=\emptyset \\ 2 & S=\{s\} \text{ // pick any } s\in V \\ 3 & R=V\setminus S \\ 4 & \text{while } R\neq\emptyset \\ 5 & e=(u,v)\leftarrow \text{ a lightest edge across } (S,R) \\ 6 & X\leftarrow X\cup\{e\} \\ 7 & S\leftarrow S\cup\{u\} & R\leftarrow R\setminus\{v\} \end{array}
```




```
X = \emptyset
S = \{s\} \text{ // pick any } s \in V
R = V \setminus S
\text{while } R \neq \emptyset
e = (u, v) \leftarrow \text{ a lightest edge across } (S, R)
X \leftarrow X \cup \{e\}
S \leftarrow S \cup \{u\} \quad R \leftarrow R \setminus \{v\}
```




```
\begin{array}{lll} 1 & X=\emptyset \\ 2 & S=\{s\} \text{ // pick any } s\in V \\ 3 & R=V\setminus S \\ 4 & \text{while } R\neq\emptyset \\ 5 & e=(u,v)\leftarrow \text{ a lightest edge across } (S,R) \\ 6 & X\leftarrow X\cup\{e\} \\ 7 & S\leftarrow S\cup\{u\} & R\leftarrow R\setminus\{v\} \end{array}
```



```
\begin{array}{lll} 1 & X=\emptyset \\ 2 & S=\{s\} \text{ // pick any } s\in V \\ 3 & R=V\setminus S \\ 4 & \text{while } R\neq\emptyset \\ 5 & e=(u,v)\leftarrow \text{ a lightest edge across } (S,R) \\ 6 & X\leftarrow X\cup\{e\} \\ 7 & S\leftarrow S\cup\{u\} & R\leftarrow R\setminus\{v\} \end{array}
```



```
\begin{array}{lll} 1 & X=\emptyset \\ 2 & S=\{s\} \text{ // pick any } s\in V \\ 3 & R=V\setminus S \\ 4 & \text{while } R\neq\emptyset \\ 5 & e=(u,v)\leftarrow \text{ a lightest edge across } (S,R) \\ 6 & X\leftarrow X\cup\{e\} \\ 7 & S\leftarrow S\cup\{u\} & R\leftarrow R\setminus\{v\} \end{array}
```



State: a growing tree (CC)

Op: identifying a lightest edge

State: a growing tree (CC)

Op: identifying a lightest edge

Using the **priority-queue** (min-heap) data structure.