

Bubble Sort

(A Taste of Algorithms: Definition, Design, and Analysis)

Hengfeng Wei

Institute of Computer Software
Nanjing University

December 18, 2016



Bubble Sort

- 1 Sorting
- 2 Bubble Sort
- 3 Analysis

Bubble Sort

- 1 Sorting
- 2 Bubble Sort
- 3 Analysis

Sorting


The sorting problem:

Input: A sequence of n integers A : $a_1 a_2 \cdots a_n$.


Output: A sorted (non-decreasing order).

$$3 \ 1 \ 4 \ 2 \implies 1 \ 2 \ 3 \ 4$$

Algorithms




Algorithms



Correctness!


Algorithms



Correctness!

Definiteness: precisely defined operations

Algorithms




Correctness!

Definiteness: precisely defined operations

Finiteness: termination

Algorithms




Correctness!

Definiteness: precisely defined operations

Finiteness: termination

Effectiveness: a reasonable model; basic operations

Algorithms



Correctness!

Definiteness: precisely defined operations

Finiteness: termination


Effectiveness: a reasonable model; basic operations

- for sorting: compare, swap

Inversions

$$A = a_1 \quad a_2 \quad \dots \quad a_n.$$


If $i < j$ and $a_i > a_j$, then (a_i, a_j) is an **inversion**.



Inversions

$$A = a_1 \quad a_2 \quad \dots \quad a_n.$$

If $i < j$ and $a_i > a_j$, then (a_i, a_j) is an **inversion**.



Adjacent inversion: $j = i + 1$

Inversions

A is sorted $\implies A$ has no inversions

Inversions

A is sorted $\implies A$ has no inversions
 $\implies A$ has no adjacent inversions.

Inversions

A is sorted $\implies A$ has no inversions
 $\implies A$ has no adjacent inversions.

A has no adjacent inversions $\implies \forall i \in [1, n-1] : a_i \leq a_{i+1}$

Inversions

A is sorted $\implies A$ has no inversions
 $\implies A$ has no adjacent inversions.

A has no adjacent inversions $\implies \forall i \in [1, n-1] : a_i \leq a_{i+1}$
 $\implies A$ is sorted.

Inversions

A is sorted $\implies A$ has no inversions
 $\implies A$ has no adjacent inversions.

A has no adjacent inversions $\implies \forall i \in [1, n-1] : a_i \leq a_{i+1}$
 $\implies A$ is sorted.

A is sorted $\iff A$ has no adjacent inversions.
--

Bubble Sort

- 1 Sorting
- 2 Bubble Sort
- 3 Analysis

Bubble Sort

Basic idea: to eliminate all adjacent inversions

Bubble Sort

Basic idea: to eliminate all adjacent inversions

```
1: repeat  
2:   pick any  $i$   
3:   if  $a_i > a_{i+1}$  then  
4:     SWAP( $a_i, a_{i+1}$ )  
5: until no adjacent inversions
```

Bubble Sort

Basic idea: to eliminate all adjacent inversions

```
1: repeat
2:   pick any  $i$                                 ▷ Definiteness!
3:   if  $a_i > a_{i+1}$  then
4:     SWAP( $a_i, a_{i+1}$ )
5: until no adjacent inversions                ▷ Definiteness!
```

Bubble Sort

Basic idea: to eliminate all adjacent inversions

```
1: repeat
2:   pick any  $i$                                 ▷ Definiteness!
3:   if  $a_i > a_{i+1}$  then
4:     SWAP( $a_i, a_{i+1}$ )
5: until no adjacent inversions                ▷ Finiteness! Definiteness!
```

Bubble Sort: Definiteness

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     
4:     for  do
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         
8:   until  no adjacent inversions

```

▷ Pick i

Bubble Sort: Definiteness

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     
4:     for  $i \leftarrow 1 : n - 1$  do
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:       
8:   until no adjacent inversions

```

▷ Pick i

Bubble Sort: Definiteness

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped
4:     for  $i \leftarrow 1 : n - 1$  do
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         
8:   until no adjacent inversions

```

▷ Pick i

Bubble Sort: Definiteness

```
1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         
8:   until no adjacent inversions
```

▷ Pick i

Bubble Sort: Definiteness

```
1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until no adjacent inversions
```

▷ Pick i


Bubble Sort: Definiteness

```
1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false
```


▷ Pick i

Bubble Sort: Example

2
4
1
3



Bubble Sort: Example




2	2
4	4
1	1
3	3


Bubble Sort: Example

2	2	2
4	4	4
1	1	3
3	3	1


Bubble Sort: Example




Bubble Sort: Example




Bubble Sort: Example




Bubble Sort: Example




Bubble Sort: Example




Bubble Sort: Example




Bubble Sort: Example



Bubble Sort: Example



Bubble Sort: Example



Bubble Sort: Finiteness

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do           ▷ Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false           ▷ No swaps

```

The inner “**for**” loops:

1) \exists loop : no swaps \implies swapped = false \implies terminates

Bubble Sort: Finiteness

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \dots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do           ▷ Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false           ▷ No swaps

```

The inner “**for**” loops:

- 1) \exists loop : no swaps \implies swapped = false \implies terminates
- 2) \forall loop : has swaps

Bubble Sort: Finiteness

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do            $\triangleright$  Pick  $i$ 
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:         swapped  $\leftarrow$  true
8:   until swapped = false            $\triangleright$  No swaps

```

The inner “**for**” loops:

- 1) \exists loop : no swaps \implies swapped = false \implies terminates
- 2) \forall loop : has swaps **Impossible!**

Bubble Sort: Finiteness


Total #inversions is finite.

¹Not on #adjacent inversions!

Bubble Sort: Finiteness

Total #inversions is finite.

Effects of $\text{SWAP}(a_i, a_{i+1})$ on #inversions¹:




¹Not on #adjacent inversions!

Bubble Sort: Finiteness

Total #inversions is finite.


Effects of $\text{SWAP}(a_i, a_{i+1})$ on #inversions¹:



$$-1 : (a_i, a_{i+1})$$

¹Not on #adjacent inversions!

Effects of $\text{SWAP}(a_i, a_{i+1})$ on $\# \text{inversions}^1$:


$$-1 : (a_i, a_{i+1})$$


+0

¹Not on #adjacent inversions!

Bubble Sort: Finiteness

Total #inversions is finite.

Effects of $\text{SWAP}(a_i, a_{i+1})$ on #inversions¹:



$-1 : (a_i, a_{i+1})$

$+0$

$\text{SWAP}(a_i, a_{i+1}) \implies -1 \text{ inversion}$

¹Not on #adjacent inversions!

Bubble Sort: Correctness

Finiteness

Bubble Sort: Correctness

Finiteness $\implies \exists \text{ loop : no swaps}$

Bubble Sort: Correctness

Finiteness $\implies \exists \text{ loop : no swaps}$
 $\implies A$ has no adjacent inversions any more

Bubble Sort: Correctness

Finiteness $\implies \exists \text{ loop : no swaps}$
 $\implies A$ has no adjacent inversions any more
 $\implies A$ is already sorted.

Optimizing Bubble Sort (I)²

Idea: After each “**for**” loop, one more element is settled.

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:    $n \leftarrow \text{len}(A)$ 
3:   repeat
4:     swapped  $\leftarrow$  false
5:     for  $i \leftarrow 1 : n - 1$  do
6:       if  $a_i > a_{i+1}$  then
7:         SWAP( $a_i, a_{i+1}$ )
8:         swapped  $\leftarrow$  true
9:      $n \leftarrow n - 1$ 
10:  until swapped = false

```

▷ One maximal bubbles up

²See Appendix for “Optimizing Bubble Sort (II)”. 

Bubble Sort

- 1 Sorting
- 2 Bubble Sort
- 3 Analysis**

Time Complexity of Bubble Sort

- Finiteness is NOT enough \implies Quantitative finiteness

Time Complexity of Bubble Sort

- Finiteness is NOT enough \implies Quantitative finiteness
- Time on real computers varies \implies #Ops on our model:

Time Complexity of Bubble Sort

- Finiteness is NOT enough \implies Quantitative finiteness
- Time on real computers varies \implies #Ops on our model:

$|C|$: #Comparisons (**if** $a_i > a_{i+1}$)

$|S|$: #Swaps (SWAP(a_i, a_{i+1}))

Time Complexity of Bubble Sort

- Finiteness is NOT enough \implies Quantitative finiteness
- Time on real computers varies \implies #Ops on our model:

$|C|$: #Comparisons (**if** $a_i > a_{i+1}$)

$|S|$: #Swaps (SWAP(a_i, a_{i+1}))

- Different inputs $\implies |C|$ and $|S|$ vary:

Time Complexity of Bubble Sort

- Finiteness is NOT enough \implies Quantitative finiteness
- Time on real computers varies \implies #Ops on our model:

$|C|$: #Comparisons (**if** $a_i > a_{i+1}$)

$|S|$: #Swaps (SWAP(a_i, a_{i+1}))

- Different inputs $\implies |C|$ and $|S|$ vary:
 - Best-case, worst-case, and average-case analysis

Best-case and Worst-case Analysis

Best-case:

Worst-case:

$$|C| = (\quad);$$

$$|S| = (\quad).$$

Best-case and Worst-case Analysis

Best-case: 1 2 3 4 5 6 7 8

Best-case:
ascendingly sorted

Worst-case:

$|C| = (\quad);$

$|S| = (\quad).$

Best-case and Worst-case Analysis

Best-case: 1 2 3 4 5 6 7 8

Best-case:
ascendingly sorted

Worst-case:

$$|C| = (\min : n - 1, \quad);$$

$$|S| = (\min : 0, \quad).$$

Best-case and Worst-case Analysis

Best-case: 1 2 3 4 5 6 7 8

Best-case:
ascendingly sorted

Worst-case:
descendingly sorted

$$|C| = (\min : n - 1, \quad);$$

$$|S| = (\min : 0, \quad).$$

Worst-case: 8 7 6 5 4 3 2 1

Best-case and Worst-case Analysis

Best-case: 1 2 3 4 5 6 7 8

Best-case:
ascendingly sorted

Worst-case:
descendingly sorted

$$|C| = (\min : n - 1, \quad \max : \frac{n^2 - n}{2});$$

$$|S| = (\min : 0, \quad \max : \frac{n^2 - n}{2}).$$

Worst-case: 8 7 6 5 4 3 2 1

$$\#inversions = (n - 1) + (n - 2) + \cdots + 1 = \frac{n^2 - n}{2}.$$

$|S| : \# \text{Swaps (Average Analysis)}$ ³

Assumptions on inputs:

1. The input is a random permutation
2. All numbers are distinct

³The calculation of $|C|$ in average is much more involved.

$|S| : \# \text{Swaps (Average Analysis)}$ ³

Assumptions on inputs:

1. The input is a random permutation
2. All numbers are distinct

$$\text{SWAP}(a_i, a_{i+1}) \implies -1 \text{ inversion}$$

³The calculation of $|C|$ in average is much more involved.

$|S| : \# \text{Swaps (Average Analysis)}^3$

Assumptions on inputs:

1. The input is a random permutation
2. All numbers are distinct

$$\text{SWAP}(a_i, a_{i+1}) \implies -1 \text{ inversion}$$

$$|S| = \mathbb{E}(\# \text{inversions})$$

³The calculation of $|C|$ in average is much more involved.

$|S|$: #Swaps (Average Analysis)

$$I_{ij} = \begin{cases} 1 & (a_i, a_j) \text{ is an inversion} \\ 0 & \text{o.w.} \end{cases}$$

$$X = \sum_j \sum_{i < j} I_{ij} \quad (\text{\#inversions})$$

$|S|$: #Swaps (Average Analysis)

$$I_{ij} = \begin{cases} 1 & (a_i, a_j) \text{ is an inversion} \\ 0 & \text{o.w.} \end{cases}$$

$$X = \sum_j \sum_{i < j} I_{ij} \quad (\text{\#inversions})$$

$$\mathbb{E}(X) = \mathbb{E}\left(\sum_j \sum_{i < j} I_{ij}\right) = \sum_j \sum_{i < j} \mathbb{E}(I_{ij})$$

$|S|$: #Swaps (Average Analysis)

$$I_{ij} = \begin{cases} 1 & (a_i, a_j) \text{ is an inversion} \\ 0 & \text{o.w.} \end{cases}$$

$$X = \sum_j \sum_{i < j} I_{ij} \quad (\text{\#inversions})$$

$$\mathbb{E}(X) = \mathbb{E}\left(\sum_j \sum_{i < j} I_{ij}\right) = \sum_j \sum_{i < j} \mathbb{E}(I_{ij})$$

$$\mathbb{E}(I_{ij}) = \mathbb{P}\{I_{ij} = 1\} = \frac{1}{2} \quad (a_i > a_j \vee a_i < a_j)$$

$|S| : \# \text{Swaps}$ (Average Analysis)

$$I_{ij} = \begin{cases} 1 & (a_i, a_j) \text{ is an inversion} \\ 0 & \text{o.w.} \end{cases}$$

$$X = \sum_j \sum_{i < j} I_{ij} \quad (\# \text{inversions})$$

$$\mathbb{E}(X) = \mathbb{E}\left(\sum_j \sum_{i < j} I_{ij}\right) = \sum_j \sum_{i < j} \mathbb{E}(I_{ij})$$

$$\mathbb{E}(I_{ij}) = \mathbb{P}\{I_{ij} = 1\} = \frac{1}{2} \quad (a_i > a_j \vee a_i < a_j)$$

$$\mathbb{E}(X) = \sum_j \sum_{i < j} \frac{1}{2} = \binom{n}{2} \cdot \frac{1}{2} = \frac{n(n-1)}{4}$$

$|S|$: #Swaps (Average Analysis)

$$I_{ij} = \begin{cases} 1 & (a_i, a_j) \text{ is an inversion} \\ 0 & \text{o.w.} \end{cases}$$

$$X = \sum_j \sum_{i < j} I_{ij} \quad (\text{\#inversions})$$

$$\mathbb{E}(X) = \mathbb{E}\left(\sum_j \sum_{i < j} I_{ij}\right) = \sum_j \sum_{i < j} \mathbb{E}(I_{ij})$$

$$\mathbb{E}(I_{ij}) = \mathbb{P}\{I_{ij} = 1\} = \frac{1}{2} \quad (a_i > a_j \vee a_i < a_j)$$

$$\mathbb{E}(X) = \sum_j \sum_{i < j} \frac{1}{2} = \binom{n}{2} \cdot \frac{1}{2} = \frac{n(n-1)}{4} = O(n^2)$$

Faster Algorithms

*It took a good deal of work to analyze the bubble sort; and although [...], the results are disappointing since they tell us that **the bubble sort isn't really very good at all.***

— Donald E. Knuth

Faster Algorithms

*It took a good deal of work to analyze the bubble sort; and although [...], the results are disappointing since they tell us that **the bubble sort isn't really very good at all.***

— Donald E. Knuth

faster: $O(n^2) \rightarrow O(n \lg n)$?

Faster Algorithms

*It took a good deal of work to analyze the bubble sort; and although [...], the results are disappointing since they tell us that **the bubble sort isn't really very good at all.***

— Donald E. Knuth

faster: $O(n^2) \rightarrow O(n \lg n)$?

... and faster: $O(n \lg n) \rightarrow O(n)$?

Faster Algorithms

*It took a good deal of work to analyze the bubble sort; and although [...], the results are disappointing since they tell us that **the bubble sort isn't really very good at all.***

— Donald E. Knuth

faster: $O(n^2) \rightarrow O(n \lg n)$?

... and faster: $O(n \lg n) \rightarrow O(n)$?





hengxin0912@gmail.com



4 Appendix

Bubble Sort: Correctness

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     for  $i \leftarrow 1 : n - 1$  do       $\triangleright$  Loop invariant?
5:       if  $a_i > a_{i+1}$  then         $\triangleright$  CAS
6:         SWAP( $a_i, a_{i+1}$ )
7:       swapped  $\leftarrow$  true
8:   until swapped = false

```

Loop invariant:

Before the k -th ($k \geq 1$) “**for**” loop, $a_{n-(k-1)} \cdots a_n$

- (1) consists of the largest $(k - 1)$ elements
- (2) in sorted order.

Correctness: Initialization + Maintenance + Termination

Bubble Sort: Finiteness

Idea: well-founded relation over \mathbf{N}


Effects of $\text{SWAP}(a_i, a_{i+1})$ on adjacent inversions:



Bubble Sort: Finiteness

Idea: well-founded relation over \mathbf{N}

Effects of $\text{SWAP}(a_i, a_{i+1})$ on adjacent inversions:




$-1 : (7, 2)$

Bubble Sort: Finiteness

Idea: well-founded relation over \mathbf{N}

Effects of $\text{SWAP}(a_i, a_{i+1})$ on adjacent inversions:



Optimizing Bubble Sort (II)

Idea: After each “**for**” loop, all elements after “**lsp**” are settled.

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     lsp  $\leftarrow$  0                                 $\triangleright$  lsp: the last swap position
5:     for  $i \leftarrow 1 : n - 1$  do
6:       if  $a_i > a_{i+1}$  then
7:         SWAP( $a_i, a_{i+1}$ )
8:         swapped  $\leftarrow$  true
9:         lsp  $\leftarrow$  i                             $\triangleright$  Update lsp
10:     $n \leftarrow$  lsp                                 $\triangleright$  Elements after lsp are sorted
11:   until swapped = false

```

Optimizing Bubble Sort (II)

Idea: After each “**for**” loop, all elements after “**lsp**” are settled.

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:     swapped  $\leftarrow$  false
4:     lsp  $\leftarrow$  0                                 $\triangleright$  lsp: the last swap position
5:     for  $i \leftarrow 1 : n - 1$  do
6:       if  $a_i > a_{i+1}$  then
7:         SWAP( $a_i, a_{i+1}$ )
8:         swapped  $\leftarrow$  true
9:         lsp  $\leftarrow$  i                                 $\triangleright$  Update lsp
10:     $n \leftarrow$  lsp                                 $\triangleright$  Elements after lsp are sorted
11:  until swapped = false

```

Optimizing Bubble Sort (II)

Idea: After each “**for**” loop, all elements after “**lsp**” are settled.

```

1: procedure BUBBLESORT( $A : a_1 \ a_2 \ \cdots \ a_n$ )
2:   repeat
3:      $\text{lsp} \leftarrow 0$                                  $\triangleright$  lsp: the last swap position
4:     for  $i \leftarrow 1 : n - 1$  do
5:       if  $a_i > a_{i+1}$  then
6:         SWAP( $a_i, a_{i+1}$ )
7:          $\text{lsp} \leftarrow i$                                  $\triangleright$  Update lsp
8:      $n \leftarrow \text{lsp}$                                  $\triangleright$  Elements after lsp are sorted
9:   until  $\text{lsp} = 0$ 

```
