#### Hengfeng Wei

Institute of Computer Software Nanjing University

December 8, 2016





- The MST Problem
- 2 The Generic MST Algorithm
- 3 The Algorithms of Kruskal and Prim

- 1 The MST Problem
- 2 The Generic MST Algorithm
- 3 The Algorithms of Kruskal and Prim

### Definition (MST)

#### Given:

- ightharpoonup connected, undirected, weighted graph G = (V, E)
- ightharpoonup edge weight w(e)

### Definition (MST)

#### Given:

- ightharpoonup connected, undirected, weighted graph G=(V,E)
- edge weight w(e)

Spanning tree  $T = (V, E_T \subseteq E)$ :

► connected, acyclic

#### Definition (MST)

#### Given:

- $\triangleright$  connected, undirected, weighted graph G = (V, E)
- ightharpoonup edge weight w(e)

Spanning tree  $T = (V, E_T \subseteq E)$ :

ightharpoonup connected, acyclic (n-1 edges)

### Definition (MST)

#### Given:

- ightharpoonup connected, undirected, weighted graph G = (V, E)
- edge weight w(e)

Spanning tree  $T = (V, E_T \subseteq E)$ :

- ightharpoonup connected, acyclic (n-1 edges)
- $\mathbf{v}(T) = \sum_{e \in T} w(e)$



#### Definition (MST)

#### Given:

- ightharpoonup connected, undirected, weighted graph G = (V, E)
- ightharpoonup edge weight w(e)

Spanning tree  $T = (V, E_T \subseteq E)$ :

- ightharpoonup connected, acyclic (n-1 edges)
- $\mathbf{v}(T) = \sum_{e \in T} w(e)$

MST: Mimimize w(T) over all possible STs



MST Example



Wrong divide-and-conquer algorithm for MST


Input: G = (V, E, w)

Divide:  $V = (S, V \setminus S); ||S| - |V \setminus S|| \le 1$ 

Wrong divide-and-conquer algorithm for MST

Input: G = (V, E, w)

Divide:  $V = (S, V \setminus S); ||S| - |V \setminus S|| \le 1$  (Cut)




Wrong divide-and-conquer algorithm for MST

Input: G = (V, E, w)

Divide:  $V = (S, V \setminus S); ||S| - |V \setminus S|| \le 1$  (Cut)

Conquer:  $T_1$ : an MST of S;  $T_2$ : an MST of  $V \setminus S$ 




Wrong divide-and-conquer algorithm for MST

Input: G = (V, E, w)

Divide:  $V = (S, V \setminus S); ||S| - |V \setminus S|| \le 1$  (Cut)


Conquer:  $T_1$ : an MST of S;  $T_2$ : an MST of  $V \setminus S$ 

Combine:  $T_1 + T_2 + \{e\}$ : e is a **lightest** edge across  $(S, V \setminus S)$ 




4/9

### What is wrong?



The edges bc and ad do **not** belong to any MST.

#### What is wrong?



The edges bc and ad do **not** belong to any MST.

#### What if:

Invariant: Manages a set of edges X which is a subset of **some** MST.



- 1 The MST Problem
- 2 The Generic MST Algorithm
- 3 The Algorithms of Kruskal and Prim

Overview: Grow the MST one edge at a time

Overview: Grow the MST one edge at a time

State: Manage a set of edges X

Overview: Grow the MST one edge at a time

State: Manage a set of edges X

**Invariant:** Prior to each iteration, X is a subset of some MST

Overview: Grow the MST one edge at a time

State: Manage a set of edges X

**Invariant:** Prior to each iteration, X is a subset of some MST

Iteration: Pick an edge e s.t.

 $X \cup \{e\}$  is also a subset of some MST

Overview: Grow the MST one edge at a time

State: Manage a set of edges X

**Invariant:** Prior to each iteration, X is a subset of some MST

Iteration: Pick a safe edge e s.t.

 $X \cup \{e\}$  is also a subset of some MST

Proof.

Initialization:

Maintenance:

Termination:



## The Cut Property


#### Cut Property

- Graph G = (V, E); X is part of an MST.
- ▶ A cut  $(S, V \setminus S)$  respecting X (X does not cross  $(S, V \setminus S)$ )
- ▶ Let e be a lightest edge across  $(S, V \setminus S)$

Then,  $X + \{e\}$  is part of some MST T.

8/9

## The Cut Property



#### Proof.

Basic idea:  $e \notin T \Rightarrow e \in T'$ .

- $ightharpoonup T + \{e\}$  to construct a cycle C
- $ightharpoonup \exists e' \in C \text{ such that } e' \text{ across the cut; } w(e') \geq w(e)$
- $T' = T + \{e\} \{e'\}$
- $w(T') \le w(T) \Rightarrow w(T') = w(T) \Rightarrow T'$  is an MST



- 1 The MST Problem
- 2 The Generic MST Algorithm
- 3 The Algorithms of Kruskal and Prim