

THE PUBLIC IS MORE FAMILIAR WITH BAD DESIGN THAN GOOD DESIGN. IT IS, IN EFFECT, CONDITIONED TO PREFER BAD DESIGN, BECAUSE THAT IS WHAT IT LIVES WITH. THE NEW BECOMES THREATENING, THE OLD REASSURING.

PAUL RAND

A DESIGNER KNOWS THAT HE HAS ACHIEVED PERFECTION NOT WHEN THERE IS NOTHING LEFT TO ADD, BUT WHEN THERE IS NOTHING LEFT TO TAKE AWAY.

ANTOINE DE SAINT-EXUPÉRY

...THE DESIGNER OF A NEW SYSTEM MUST NOT ONLY BE THE IMPLEMENTOR AND THE FIRST LARGE-SCALE USER; THE DESIGNER SHOULD ALSO WRITE THE FIRST USER MANUAL...IF I HAD NOT PARTICIPATED FULLY IN ALL THESE ACTIVITIES, LITERALLY HUNDREDS OF IMPROVEMENTS WOULD NEVER HAVE BEEN MADE, BECAUSE I WOULD NEVER HAVE THOUGHT OF THEM OR PERCEIVED WHY THEY WERE IMPORTANT.

DONALD E. KNUTH

HENGFENG WEI

COLLECTION OF ALGO- RITHMS PSEUDOCODE

ANT

Copyright © 2018 Hengfeng Wei

PUBLISHED BY ANT

TUFTE-LATEX.GOOGLECODE.COM

Licensed under the Apache License, Version 2.0 (the “License”); you may not use this file except in compliance with the License. You may obtain a copy of the License at <http://www.apache.org/licenses/LICENSE-2.0>. Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an “AS IS” BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

First printing, June 2018

Contents

Basic Iterative and Recursive Algorithms 17

Sorting 19

Selection 23

Searching 25

Dynamic Programming 27

Traversal on Trees 29

Stack and Queue 33

DAG 35

Paths in Graphs 37

Bibliography 39

List of Algorithms

1	Horner rule for polynomial evaluation.	17
2	Integer Multiplication.	17
3	Bubblesort (Bubble the smallest element each time.).	19
4	Bubblesort (Bubble the largest element each time.).	19
5	Bubblesort (An improved version; from wiki).	20
6	Hoare partition.	20
7	Selection Sort.	21
8	COUNTING-SORT in place in $O(n + k)$ time.	21
9	Deterministic search.	25
10	Iterative binary search.	26
11	Recursive binary search.	26
12	Computing $\binom{n}{k}$ recursively.	27
13	Computing $\binom{n}{k}$ by dynamic programming.	28
14	Max-sum subarray.	28
15	Max-sum subarray (Implementation Simplified).	28
16	Recursive DFS pre-order traversal on binary tree.	29
17	Iterative DFS pre-order traversal on binary tree.	29
18	Recursive DFS traversal on a rooted tree stored using the “left-child, right-sibling” representation.	30
19	Calculate the sum of depths of all nodes of a tree T .	30
20	Count the number of nodes in T at depth K .	30
21	Check whether a tree T has any leaf at an even depth.	31
22	Calculate the sum of contents of nodes of a tree T at each depth.	31
23	Count the number of nodes of a tree T at each depth.	32
24	Circular queue.	33
25	Simulating a queue using two stacks S_1, S_2 .	34
26	Dijkstra’s algorithm for SSSP	37
27	Floyd-Warshall algorithm for APSP	37
28	Hierholzer’s algorithm for finding an Eulerian circuit.	38

List of Figures

- 1 3-element sorting algorithm represented by a decision tree. 19
- 2 3-element median selection algorithm represented by a decision tree. 23
- 3 Binary stride. 25
- 4 Calculate $\binom{4}{2}$ recursively. 27
- 5 Pascal triangle for binomial coefficients. 27

List of Tables

*Dedicated to those who appreciate \LaTeX
and the work of Edward R. Tufte and Donald E. Knuth.*

Introduction

This is a collection of psuedocode for classic algorithms.

Basic Iterative and Recursive Algorithms

Algorithm 1 Horner rule for polynomial evaluation.

```
1: procedure HORNER( $A[0 \dots n], x$ )  $\triangleright A : \{a_0 \dots a_n\}$ 
2:    $p \leftarrow A[n]$ 
3:   for  $i \leftarrow n - 1$  downto 0 do
4:      $p \leftarrow px + A[i]$ 
5:   return  $p$ 
```

Algorithm 2 Integer Multiplication.

```
1: procedure INT-MULT( $y, z$ )  $\triangleright y, z \geq 0; y, z \in \mathbb{Z}$ 
2:   if  $z = 0$  then
3:     return 0
4:   return INT-MULT( $cy, \lfloor \frac{z}{c} \rfloor$ ) +  $y(z \bmod c)$ 
```

Sorting




Figure 1: 3-element sorting algorithm represented by a decision tree.

Algorithm 3 Bubblesort (Bubble the smallest element each time.).

```

1: procedure BUBBLESORT( $A[1 \dots n]$ )
2:   for  $i \leftarrow 1$  to  $n - 1$  do
3:     for  $j \leftarrow n$  downto  $i + 1$  do
4:       if  $A[j] < A[j - 1]$  then
5:         SWAP( $A[j], A[j - 1]$ )

```

Algorithm 4 Bubblesort (Bubble the largest element each time.).

```

1: procedure BUBBLESORT( $A[1 \dots n]$ )
2:   for  $i \leftarrow n$  downto 2 do
3:     for  $j \leftarrow 1$  to  $i - 1$  do
4:       if  $A[j] > A[j + 1]$  then
5:         SWAP( $A[j], A[j + 1]$ )

```

Algorithm 5 Bubblesort (An improved version; from wiki).

```

1: procedure BUBBLESORT( $A[1 \cdots n]$ )
2:   repeat
3:      $newn \leftarrow 0$ 
4:     for  $i \leftarrow 1$  to  $n - 1$  do
5:       if  $A[i - 1] > A[i]$  then
6:         SWAP( $A[i - 1], A[i]$ )
7:          $newn \leftarrow i$ 
8:      $n \leftarrow newn$ 
9:   until  $n = 0$ 

```

Quicksort

HOARE-PARTITION (alg4)

Algorithm 6 Hoare partition.

```

procedure HOARE-PARTITION( $A, l, r$ )
   $x \leftarrow A[l]$ 
   $i \leftarrow l$ 
   $j \leftarrow r + 1$ 

  while TRUE do
    while  $A[+ + i] < x$  do
      if  $i = r$  then
        break
    while  $A[- - j] > x$  do
      if  $j = l$  then
        break

    if  $i < j$  then
      SWAP( $A, i, j$ )

  SWAP( $A, l, j$ )

```

Linear Time Sorting

Algorithm 7 Selection Sort.

```
1: procedure SELECTION-SORT( $A, n$ )  
2:   for  $i \leftarrow 1$  to  $n - 1$  do  
3:     for  $j \leftarrow i + 1$  to  $n$  do  
4:       if  $A[j] < A[i]$  then  
5:         SWAP( $A[j], A[i]$ )
```

Algorithm 8 COUNTING-SORT in place in $O(n + k)$ time.

```
1: procedure COUNTING-SORT( $A, k$ )  
2:   TODO
```

Selection




Figure 2: 3-element median selection algorithm represented by a decision tree.

Searching

Algorithm 9 (see Problem 5 – 2 of ¹) searches for a value x in an unsorted array A consisting of n elements by checking $A[1], A[2], \dots, A[n]$ in order until either it finds $A[i] = x$ or it reaches the end of the array.

¹ Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, and Clifford Stein. *Introduction to Algorithms, Third Edition*. The MIT Press, 3rd edition, 2009. ISBN 0262033844, 9780262033848

Algorithm 9 Deterministic search.

```
1: procedure DETERMINISTIC-SEARCH( $A[1 \dots n], x$ )
2:    $i \leftarrow 1$ 
3:   while  $i \leq n$  do
4:     if  $A[i] = x$  then
5:       return true
6:      $i \leftarrow i + 1$ 
7:   return false
```




Figure 3: Binary stride.

Algorithm 10 Iterative binary search.

```

1: procedure BINARYSEARCH( $A[0 \cdots n - 1], x$ )
2:    $L \leftarrow 0$ 
3:    $R \leftarrow n - 1$ 
4:   while  $L \leq R$  do
5:      $m \leftarrow L + (R - L)/2$ 
6:     if  $A[m] < x$  then
7:        $L \leftarrow m + 1$ 
8:     else if  $A[m] > x$  then
9:        $R \leftarrow m - 1$ 
10:    else
11:      return  $m$ 
12:  return  $-1$ 

```

Algorithm 11 Recursive binary search.

```

1: procedure BINARYSEARCH( $A, L, R, x$ )
2:   if  $R < L$  then
3:     return  $-1$ 
4:    $m \leftarrow L + (R - L)/2$ 
5:   if  $A[m] = x$  then
6:     return  $m$ 
7:   else if  $A[m] > x$  then
8:     return BINARYSEARCH( $A, L, m - 1, x$ )
9:   else
10:    return BINARYSEARCH( $A, m + 1, R, x$ )

```

Dynamic Programming

Algorithm 12 Computing $\binom{n}{k}$ recursively.

```

1: procedure BINOM( $n, k$ ) ▷ Required:  $n \geq k \geq 0$ 
2:   if  $k = 0 \vee n = k$  then
3:     return 1
4:   return BINOM( $n - 1, k$ ) + BINOM( $n - 1, k - 1$ )

```




Figure 4: Calculate $\binom{4}{2}$ recursively.




Figure 5: Pascal triangle for binomial coefficients.

Algorithm 13 Computing $\binom{n}{k}$ by dynamic programming.

```

1: procedure BINOM( $n, k$ ) ▷ Required:  $n \geq k \geq 0$ 
2:   for  $i \leftarrow 0$  to  $n - k$  do
3:      $B[i][0] \leftarrow 1$ 
4:   for  $i \leftarrow 1$  to  $k$  do
5:      $B[i][i] \leftarrow 1$ 
6:   for  $j \leftarrow 1$  to  $k$  do
7:     for  $d \leftarrow 1$  to  $n - k$  do
8:        $i \leftarrow j + d$ 
9:        $B[i][j] \leftarrow B[i - 1][j] + B[i - 1][j - 1]$ 
10:  return  $B[n][k]$ 

```

$$(n - k + 1) + (k) + k(n - k) = nk - k^2 + n + 1$$

Algorithm 14 Max-sum subarray.

```

1: procedure MSS( $A[1 \dots n]$ )
2:    $MSS[0] \leftarrow 0$ 
3:   for  $i \leftarrow 1$  to  $n$  do
4:      $MSS[i] \leftarrow \max \{MSS[i - 1] + A[i], 0\}$ 
5:   return  $\max_{1 \leq i \leq n} MSS[i]$ 

```

Algorithm 15 Max-sum subarray (Implementation Simplified).

```

1: procedure MSS( $A[1 \dots n]$ )
2:    $mss \leftarrow 0$ 
3:    $MSS \leftarrow 0$ 
4:   for  $i \leftarrow 1$  to  $n$  do
5:      $MSS \leftarrow \max \{MSS + A[i], 0\}$ 
6:      $mss \leftarrow \max \{mss, MSS\}$ 
7:   return  $mss$ 

```

Traversal on Trees

DFS on Trees

Algorithm 16 Recursive DFS pre-order traversal on binary tree.

```
procedure RECURSIVE-DFS( $t$ )  
  print  $t.key$   
  
  if  $t.left \neq \text{NIL}$  then  
    RECURSIVE-DFS( $t.left$ )  
  if  $t.right \neq \text{NIL}$  then  
    RECURSIVE-DFS( $t.right$ )
```

```
RECURSIVE-DFS( $T.root$ )
```

Algorithm 17 Iterative DFS pre-order traversal on binary tree.

```
procedure ITERATIVE-DFS( $t$ )  
  S.PUSH( $t$ ) ▷ S : stack  
  
  while  $S \neq \emptyset$  do  
     $v \leftarrow S.POP()$   
    print  $v.key$   
  
    if  $v.right \neq \text{NIL}$  then  
      S.PUSH( $v.right$ )  
    if  $v.left \neq \text{NIL}$  then  
      S.PUSH( $v.left$ )
```

```
ITERATIVE-DFS( $T.root$ )
```

Algorithm 18 Recursive DFS traversal on a rooted tree stored using the “left-child, right-sibling” representation.

```

procedure RECURSIVE-DFS( $t$ )
    print  $t.key$ 

    if  $t.left-child \neq \text{NIL}$  then
        RECURSIVE-DFS( $t.left-child$ )
    if  $t.right-sibling \neq \text{NIL}$  then
        RECURSIVE-DFS( $t.right-sibling$ )

RECURSIVE-DFS( $T.root$ )

```

Algorithm 19 Calculate the sum of depths of all nodes of a tree T .

```

1: procedure SUM-OF-DEPTHS()
2:     return SUM-OF-DEPTHS( $T, 0$ )

3: procedure SUM-OF-DEPTHS( $r, depth$ )            $\triangleright r$ : root of a tree
4:     if  $r$  is a leaf then
5:         return  $depth$ 

6:      $sum \leftarrow depth$ 
7:     for all child vertex  $v$  of  $r$  do
8:          $sum \leftarrow sum + \text{SUM-OF-DEPTHS}(v, depth + 1)$ 
9:     return  $sum$ 

```

Algorithm 20 Count the number of nodes in T at depth K .

```

1: procedure NODES-AT-DEPTH()
2:     return NODES-AT-DEPTH( $T, K$ )

3: procedure NODES-AT-DEPTH( $r, k$ )            $\triangleright r$ : root of a tree
4:     if  $k = 0$  then
5:         return 1

6:     if  $r$  is a leaf then
7:         return 0

8:      $num \leftarrow 0$ 
9:     for all child vertex  $v$  of  $r$  do
10:         $num \leftarrow num + \text{NODES-AT-DEPTH}(v, k - 1)$ 
11:    return  $num$ 

```

Algorithm 21 Check whether a tree T has any leaf at an even depth.

```

1: procedure LEAF-AT-EVEN-DEPTH()
2:   return LEAF-AT-DEPTH( $T, \text{even} = 0$ )

3: procedure LEAF-AT-DEPTH( $r, \text{parity}$ )            $\triangleright r$ : root of a tree
4:   if  $r$  is a leaf then
5:     return  $1 - \text{parity}$ 

6:    $\text{result} \leftarrow 0$ 
7:   for all child vertex  $v$  of  $r$  do
8:      $\text{result} \leftarrow \text{result} \vee \text{LEAF-AT-DEPTH}(v, 1 - \text{parity})$ 
9:   return  $\text{result}$ 

```

BFS on Trees

Algorithm 22 Calculate the sum of contents of nodes of a tree T at each depth.

```

1: procedure SUM-AT-DEPTH( $r$ )            $\triangleright r$ : root of the tree  $T$ 
2:    $r.\text{depth} \leftarrow 0$ 

3:    $Q \leftarrow \emptyset$ 
4:   ENQUEUE( $Q, r$ )

5:   while  $Q \neq \emptyset$  do
6:      $u \leftarrow \text{DEQUEUE}(Q)$ 
7:      $\text{sumAtDepth}[u.\text{depth}] += u.\text{content}$ 

8:     for all child vertex  $v$  of  $u$  do
9:        $v.\text{depth} \leftarrow u.\text{depth} + 1$ 
10:    ENQUEUE( $Q, v$ )

```

Algorithm 23 Count the number of nodes of a tree T at each depth.

```

1: procedure NODES-AT-DEPTH( $r$ )            $\triangleright r$ : root of the tree  $T$ 
2:    $r.depth \leftarrow 0$ 
3:    $Q \leftarrow \emptyset$ 
4:   ENQUEUE( $Q, r$ )
5:   while  $Q \neq \emptyset$  do
6:      $u \leftarrow$  DEQUEUE( $Q$ )
7:      $nodesAtDepth[u.depth] += 1$ 
8:     for all child vertex  $v$  of  $u$  do
9:        $v.depth \leftarrow u.depth + 1$ 
10:      ENQUEUE( $Q, v$ )
11:  return  $\text{argmax}_K nodesAtDepth[k]$ 

```

Stack and Queue

Stack

Queue

Algorithm 24 Circular queue.

procedure ENQUEUE(Q, x)

if $Q.head = Q.tail + 1$ **then**
 return "OVERFLOW"

$Q[Q.tail] = x$

if $Q.tail = Q.length$ **then**
 $Q.tail = 1$

else
 $Q.tail = Q.tail + 1$

procedure DEQUEUE(Q)

if $Q.head = Q.tail$ **then**
 return "UNDERFLOW"

$x = Q[Q.head]$

if $Q.head = Q.length$ **then**
 $Q.head = 1$

else
 $Q.head = Q.head + 1$

return x

Stack and Queue

Algorithm 25 Simulating a queue using two stacks S_1, S_2 .

procedure ENQ(x)*Push*(S_1, x)**procedure** DEQ()**if** $S_2 = \emptyset$ **then****while** $S_1 \neq \emptyset$ **do***Push*($S_2, \text{Pop}(S_1)$)*Pop*(S_2)

DAG

Paths in Graphs

Single-Source Shortest Paths (SSSP)

Algorithm 26 Dijkstra's algorithm for SSSP

```
for all  $v \in V$  do
     $\text{dist}[v] \leftarrow \infty$ 
 $\text{dist}[s] \leftarrow 0$ 

 $Q \leftarrow \text{MINPQ}(V)$ 
while  $Q \neq \emptyset$  do
     $u \leftarrow \text{DELETMIN}(Q)$ 

    for all  $(u, v) \in E \wedge v \notin Q$  do
        if  $\text{dist}[v] > \text{dist}[u] + l(u, v)$  then
             $\text{dist}[v] \leftarrow \text{dist}[u] + l(u, v)$ 
             $\text{DECREASEKEY}(Q, v)$ 
```

All-Pairs Shortest Paths (APSP)

Algorithm 27 Floyd-Warshall algorithm for APSP

```
for all  $(i, j)$  do
    if  $(i, j) \in E$  then
         $\text{dist}(i, j, 0) \leftarrow l(i, j)$ 
    else
         $\text{dist}(i, j, 0) \leftarrow \infty$ 

for  $k \leftarrow 1$  to  $n$  do
    for  $i \leftarrow 1$  to  $n$  do
        for  $j \leftarrow 1$  to  $n$  do
             $\text{dist}(i, j, k) = \min \left( \text{dist}(i, j, k - 1), \text{dist}(i, k, k - 1) + \right.$ 
             $\left. \text{dist}(k, j, k - 1) \right)$ 
```

Eulerian Path and Eulerian Circuit

Algorithm 28 Hierholzer's algorithm for finding an Eulerian circuit.

 $VE \leftarrow \emptyset$ $C \leftarrow \emptyset$ **while** $VE \neq E$ **do** $u \leftarrow \text{CHOOSE}(u : (u \rightarrow v) \notin VE)$ $C' \leftarrow \text{CIRCUIT}(u, E \setminus VE)$ $VE \leftarrow VE \cup C'$ $C \leftarrow C \cup C'$

Bibliography

Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, and Clifford Stein. *Introduction to Algorithms, Third Edition*. The MIT Press, 3rd edition, 2009. ISBN 0262033844, 9780262033848.