

```

1  |----- MODULE XJupiterExtended -----|
   | XJupiter extended with Cop with the sctx field. |
5  | EXTENDS Integers, OT, TLCUtils, AdditionalFunctionOperators, AdditionalSequenceOperators |
6  |-----|
7  CONSTANTS
8      Client,      the set of client replicas
9      Server,      the (unique) server replica
10     Char,        set of characters allowed
11     InitState    the initial state of each replica

13  Replica  $\triangleq$  Client  $\cup$  {Server}

15  List  $\triangleq$  Seq(Char  $\cup$  Range(InitState))    all possible lists/strings
16  MaxLen  $\triangleq$  Cardinality(Char) + Len(InitState)    the max length of lists in any states;
17      We assume that all inserted elements are unique.

19  ClientNum  $\triangleq$  Cardinality(Client)
20  Priority  $\triangleq$  CHOOSE  $f \in [Client \rightarrow 1 \dots ClientNum] : Injective(f)$ 

22  direction flags
23  Local  $\triangleq$  0
24  Remote  $\triangleq$  1

25  |-----|
26  ASSUME
27       $\wedge Range(InitState) \cap Char = \{\}$     due to the uniqueness requirement
28       $\wedge Priority \in [Client \rightarrow 1 \dots ClientNum]$ 

29  |-----|
   | The set of all operations. Note: The positions are indexed from 1. |
34  Rd  $\triangleq$  [type : { "Rd" }]
35  Del  $\triangleq$  [type : { "Del" }, pos : 1 .. MaxLen]
36  Ins  $\triangleq$  [type : { "Ins" }, pos : 1 .. (MaxLen + 1), ch : Char, pr : 1 .. ClientNum]    pr: priority

38  Op  $\triangleq$  Ins  $\cup$  Del

39  |-----|
   | Cop: operation of type Op with context |
43  Oid  $\triangleq$  [c : Client, seq : Nat]    operation identifier
   | Cop with the sctx field (the extended part) |
47  Cop  $\triangleq$  [op : Op  $\cup$  {Nop}, oid : Oid, ctx : SUBSET Oid, sctx : SUBSET Oid]

   | OT of two operations of type Cop. |
52  COT(lcp, rcp)  $\triangleq$  [lcp EXCEPT !.op = Xform(lcp.op, rcp.op), !.ctx = @  $\cup$  {rcp.oid}]

53  |-----|
54  VARIABLES
   | For the client replicas: |
58  cseq,    cseq[c]: local sequence number at client c  $\in$  Client

```

For the server replica (the extended part):

62 *soids*, the set of operations the *Server* has executed

The 2D state spaces (*ss*, for short). Each client maintains one 2D state space. The server maintains *n* 2D state spaces, one for each client.

68 *css*, *css*[*c*]: the 2D state space at client *c* ∈ *Client*

69 *ccur*, *ccur*[*c*]: the current node of *css*[*c*]

70 *sss*, *sss*[*c*]: the 2D state space maintained by the *Server* for client *c* ∈ *Client*

71 *scur*, *scur*[*c*]: the current node of *sss*[*c*]

For all replicas

75 *state*, *state*[*r*]: state (the list content) of replica *r* ∈ *Replica*

For communication between the *Server* and the *Clients*:

79 *cincoming*, *cincoming*[*c*]: incoming channel at the client *c* ∈ *Client*

80 *sincoming*, incoming channel at the *Server*

For model checking:

84 *chins* a set of chars to insert

85

86 *comm* \triangleq INSTANCE *CSComm* WITH *Msg* \leftarrow *Cop*

87

88 *eVars* \triangleq $\langle \textit{chins} \rangle$ variables for the environment

89 *cVars* \triangleq $\langle \textit{cseq} \rangle$ variables for the clients

90 *cssVars* \triangleq $\langle \textit{css}, \textit{ccur} \rangle$ variables for 2D state spaces at clients

91 *sssVars* \triangleq $\langle \textit{sss}, \textit{scur} \rangle$ variables for 2D state spaces at the *Server*

92 *commVars* \triangleq $\langle \textit{cincoming}, \textit{sincoming} \rangle$ variables for communication

93 *vars* \triangleq $\langle \textit{eVars}, \textit{cVars}, \textit{commVars}, \textit{cssVars}, \textit{sssVars}, \textit{state} \rangle$ all variables

94

A 2D state space is a directed graph with labeled edges. It is represented by a record with node field and edge field. Each node is characterized by its context, a set of operations. Each edge is labeled with an operation and a direction flag indicating whether this edge is LOCAL or REMOTE. For clarity, we denote edges by records instead of tuples.

103 *IsSS*(*G*) \triangleq

104 $\wedge G = [\textit{node} \mapsto G.\textit{node}, \textit{edge} \mapsto G.\textit{edge}]$

105 $\wedge G.\textit{node} \subseteq (\text{SUBSET } \textit{Oid})$

106 $\wedge G.\textit{edge} \subseteq [\textit{from} : G.\textit{node}, \textit{to} : G.\textit{node}, \textit{cop} : \textit{Cop}, \textit{lr} : \{\textit{Local}, \textit{Remote}\}]$

108 *TypeOK* \triangleq

For the client replicas:

112 $\wedge \textit{cseq} \in [\textit{Client} \rightarrow \textit{Nat}]$

For the 2D state spaces:

116 $\wedge \forall c \in \textit{Client} : \textit{IsSS}(\textit{css}[c]) \wedge \textit{IsSS}(\textit{sss}[c])$

117 $\wedge \textit{ccur} \in [\textit{Client} \rightarrow \text{SUBSET } \textit{Oid}]$

118 $\wedge \textit{scur} \in [\textit{Client} \rightarrow \text{SUBSET } \textit{Oid}]$

119 $\wedge \textit{state} \in [\textit{Replica} \rightarrow \textit{List}]$

For communication between the server and the clients:

```

123     $\wedge comm!TypeOK$ 
      For model checking:
127     $\wedge chins \subseteq Char$ 
128 |-----|
      The Init predicate.
132 Init  $\triangleq$ 
      For the client replicas:
136     $\wedge cseq = [c \in Client \mapsto 0]$ 
      For the Server replica (the extended part):
140     $\wedge soids = \{\}$ 
      For the 2D state spaces:
144     $\wedge css = [c \in Client \mapsto [node \mapsto \{\{\}\}, edge \mapsto \{\}]]$ 
145     $\wedge ccur = [c \in Client \mapsto \{\}]$ 
146     $\wedge sss = [c \in Client \mapsto [node \mapsto \{\{\}\}, edge \mapsto \{\}]]$ 
147     $\wedge scur = [c \in Client \mapsto \{\}]$ 
      For all replicas:
151     $\wedge state = [r \in Replica \mapsto InitState]$ 
      For communication between the server and the clients:
155     $\wedge comm!Init$ 
      For model checking:
159     $\wedge chins = Char$ 
160 |-----|
      Locate the node in the 2D state space ss which matches the context ctx of cop.
164 Locate(cop, ss)  $\triangleq$  CHOOSE  $n \in (ss.node) : n = cop.ctx$ 

xForm: iteratively transform cop with a path through the 2D state space ss at some client,
following the edges with the direction flag d.
171 xForm(cop, ss, cur, d)  $\triangleq$ 
172   LET  $u \triangleq Locate(cop, ss)$ 
173    $v \triangleq u \cup \{cop.oid\}$ 
174   RECURSIVE xFormHelper( $-, -, -, -$ )
175   'h' stands for "helper"; xss: eXtra ss created during transformation
176   xFormHelper(uh, vh, coph, xss)  $\triangleq$ 
177   IF uh = cur
178     THEN xss
179   ELSE LET  $e \triangleq$  CHOOSE  $e \in ss.edge : e.from = uh \wedge e.lr = d$ 
180      $uprime \triangleq e.to$ 
181      $copprime \triangleq e.cop$ 
182      $coph2copprime \triangleq COT(coph, copprime)$ 
183      $copprime2coph \triangleq COT(copprime, coph)$ 
184      $vprime \triangleq vh \cup \{copprime.oid\}$ 
185     IN xFormHelper(uprime, vprime, coph2copprime,
186       [xss EXCEPT  $!.node = @ \circ \langle vprime \rangle$ ],

```

187 the order of recording edges here is important
188 so that the last one is labeled with the final transformed operation
189 $!.edge = @ \circ \langle [from \mapsto vh, to \mapsto vprime, cop \mapsto copprime2coph, lr \mapsto$
190 $[from \mapsto uprime, to \mapsto vprime, cop \mapsto coph2copprime,$
191 IN $xFormHelper(u, v, cop, [node \mapsto \langle v \rangle,$
192 $edge \mapsto \langle [from \mapsto u, to \mapsto v, cop \mapsto cop, lr \mapsto 1 - d] \rangle]$
193 \vdash Client $c \in Client$ perform operation cop guided by the direction flag d .

197 $ClientPerform(cop, c, d) \triangleq$
198 LET $xss \triangleq xForm(cop, css[c], ccur[c], d)$
199 $xn \triangleq xss.node$
200 $xe \triangleq xss.edge$
201 $xcur \triangleq Last(xn)$
202 $xcop \triangleq Last(xe).cop$
203 IN $\wedge css' = [css \text{ EXCEPT } ![c].node = @ \cup Range(xn),$
204 $![c].edge = @ \cup Range(xe)]$
205 $\wedge ccur' = [ccur \text{ EXCEPT } ![c] = xcur]$
206 $\wedge state' = [state \text{ EXCEPT } ![c] = Apply(xcop.op, @)]$
Client $c \in Client$ issues an operation op .

210 $DoOp(c, op) \triangleq$ op : the raw operation generated by the client $c \in Client$
211 $\wedge cseq' = [cseq \text{ EXCEPT } ![c] = @ + 1]$
212 op with the $sctx$ field (the extended part)
213 $\wedge \text{LET } cop \triangleq [op \mapsto op, oid \mapsto [c \mapsto c, seq \mapsto cseq'[c]], ctx \mapsto ccur[c], sctx \mapsto \{\}]$
214 IN $\wedge ClientPerform(cop, c, Remote)$
215 $\wedge comm!CSend(cop)$

217 $DoIns(c) \triangleq$
218 $\exists ins \in Ins :$
219 $\wedge ins.pos \in 1 \dots (Len(state[c]) + 1)$
220 $\wedge ins.ch \in chins$
221 $\wedge ins.pr = Priority[c]$
222 $\wedge chins' = chins \setminus \{ins.ch\}$ We assume that all inserted elements are unique.
223 $\wedge DoOp(c, ins)$
224 $\wedge \text{UNCHANGED } \langle sssVars \rangle$

226 $DoDel(c) \triangleq$
227 $\exists del \in Del :$
228 $\wedge del.pos \in 1 \dots Len(state[c])$
229 $\wedge DoOp(c, del)$
230 $\wedge \text{UNCHANGED } \langle sssVars, eVars \rangle$

232 $Do(c) \triangleq$
233 $\vee DoIns(c)$
234 $\vee DoDel(c)$
Client $c \in Client$ receives a message from the *Server*.

```

238  $Rev(c) \triangleq$ 
239    $\wedge comm!CRev(c)$ 
240    $\wedge LET\ cop \triangleq Head(cincoming[c])$  the received (transformed) operation
241     IN  $ClientPerform(cop, c, Local)$ 
242    $\wedge UNCHANGED \langle eVars, cVars, sssVars \rangle$ 
243 |-----|
244 | The Server performs operation cop.
245 |
247  $ServerPerform(cop) \triangleq$ 
248   LET  $c \triangleq cop.oid.c$ 
249    $xss \triangleq xForm(cop, sss[c], scur[c], Remote)$ 
250    $xn \triangleq xss.node$ 
251    $xe \triangleq xss.edge$ 
252    $xcur \triangleq Last(xn)$ 
253    $xcop \triangleq Last(xe).cop$ 
254   IN  $\wedge sss' = [cl \in Client \mapsto$ 
255     IF  $cl = c$ 
256       THEN  $[sss[cl] EXCEPT !.node = @ \cup Range(xn),$ 
257          $!.edge = @ \cup Range(xe)]$ 
258     ELSE LET  $scurcl \triangleq scur[cl]$ 
259        $scurclprime \triangleq scurcl \cup \{cop.oid\}$ 
260     IN  $[sss[cl] EXCEPT !.node = @ \cup \{scurclprime\},$ 
261        $!.edge = @ \cup \{[from \mapsto scurcl, to \mapsto scurclprime,$ 
262          $cop \mapsto xcop, lr \mapsto Remote]\}]$ 
263     ]
264    $\wedge scur' = [cl \in Client \mapsto$ 
265     IF  $cl = c$  THEN  $xcur$  ELSE  $scur[cl] \cup \{cop.oid\}$ 
266    $\wedge state' = [state EXCEPT ![Server] = Apply(xcop.op, @)]$ 
267    $\wedge comm!SSendSame(c, xcop)$  broadcast the transformed operation
268 |-----|
269 | The Server receives a message.
270 |
271  $SRev \triangleq$ 
272    $\wedge comm!SRev$ 
273    $\wedge LET\ cop \triangleq [Head(sincoming) EXCEPT !.sctx = soids]$ 
274     cop with the sctx field (the extended part)
275     IN  $ServerPerform(cop)$ 
276    $\wedge UNCHANGED \langle eVars, cVars, cssVars \rangle$ 
277 |-----|
278 | The next-state relation.
279 |
281  $Next \triangleq$ 
282    $\vee \exists c \in Client : Do(c) \vee Rev(c)$ 
283    $\vee SRev$ 
284 |-----|
285 | The Spec. (TODO: Check the fairness condition.)
286 |
287  $Spec \triangleq Init \wedge \Box[Next]_{vars} \wedge WF_{vars}(Next)$ 
288 |-----|

```

\ * Modification History

* *Last modified Tue Oct 30 20:52:50 CST 2018 by hengxin*
* *Created Tue Oct 30 20:32:27 CST 2018 by hengxin*