

```

1  |----- MODULE CSComm -----|
   | Specification of communication in a Client-Server system model. |
5  | EXTENDS SequenceUtils |
6  |-----|
7  | CONSTANTS |
8  |   Client, the set of clients |
9  |   Server, the (unique) server |
10 |   Msg the set of messages |
11 |-----|
12 | VARIABLES |
13 |   cincoming, cincoming[c]: incoming channel at client c ∈ Client |
14 |   sincoming incoming channel at the Server |
15 |-----|
16 | TypeOK ≜ |
17 |   ∧ cincoming ∈ [Client → Seq(Msg)] |
18 |   ∧ sincoming ∈ Seq(Msg) |
20 | Init ≜ |
21 |   ∧ cincoming = [c ∈ Client ↦ ⟨⟩] |
22 |   ∧ sincoming = ⟨⟩ |
24 | EmptyChannel ≜ Init |
25 |-----|
26 | CSend(msg) ≜ A client sends a message msg to the Server. |
27 |   ∧ sincoming' = Append(sincoming, msg) |
28 |   ∧ UNCHANGED cincoming |
30 | CRev(c) ≜ Client c receives and consumes a message from the Server. |
31 |   ∧ cincoming[c] ≠ ⟨⟩ |
32 |   ∧ cincoming' = [cincoming EXCEPT ![c] = Tail(@)] |
33 |   ∧ UNCHANGED sincoming |
34 |-----|
35 | SRev ≜ The Server receives and consumes a message. |
36 |   ∧ sincoming ≠ ⟨⟩ |
37 |   ∧ sincoming' = Tail(sincoming) |
39 | SSend(c, cmsg) ≜ The Server sends a message cmsg to each client other than c ∈ Client. |
40 |   ∧ cincoming' = [cl ∈ Client ↦ IF cl = c |
41 |                                     THEN cincoming[cl] |
42 |                                     ELSE Append(cincoming[cl], cmsg[cl])] |
44 | SSendSame(c, msg) ≜ The Server broadcasts the message msg to all clients other than c ∈ Client. |
45 |   ∧ SSend(c, [cl ∈ Client ↦ msg]) |
46 |-----|
   | \ * Modification History |
   | \ * Last modified Thu Jan 03 09:46:24 CST 2019 by hengxin |

```

* Created Sun Jun 24 10:25:34 CST 2018 by *hengxin*