

```

1  |----- MODULE AJupiter -----|
  | Model checking the Jupiter protocol presented by Attiya and others. |
5  | EXTENDS OT, TLC |
6  |-----|
7  CONSTANTS
8      Client,      the set of client replicas
9      Server,      the (unique) server replica
10     State,      the initial state of each replica
11     Cop         Cop[c]: operations issued by the client c ∈ Client

13 ASSUME
14     ∧ State ∈ List
15     ∧ Cop ∈ [Client → Seq(Op)]

17 VARIABLES
18     cop,          cop[c]: operations issued by the client c ∈ Client
  | For the client replicas: |
22     cbuf,        cbuf[c]: buffer (of operations) at the client c ∈ Client
23     crec,        crec[c]: the number of new messages have been received by the client c ∈ Client
24                   since the last time a message was sent
25     cstate,      cstate[c]: state (the list content) of the client c ∈ Client
  | For the server replica: |
30     sbuf,        sbuf[c]: buffer (of operations) at the Server, one per client c ∈ Client
31     srec,        srec[c]: the number of new messages have been ... , one per client c ∈ Client
32     sstate,      sstate: state (the list content) of the server Server
  | For communication between the Server and the Clients: |
37     cincoming,  cincoming[c]: incoming channel at the client c ∈ Client
38     sincoming   incoming channel at the Server

39 |-----|
40 comm ≜ INSTANCE CSComm
41 |-----|
42 cVars ≜ ⟨cop, cbuf, crec, cstate⟩
43 sVars ≜ ⟨sbuf, srec, sstate⟩
44 vars ≜ cVars ∘ sVars ∘ comm! vars
45 |-----|
46 TypeOK ≜
47     ∧ cop ∈ [Client → Seq(Op)]
  | For the client replicas: |
51     ∧ cbuf ∈ [Client → Seq(Op)]
52     ∧ crec ∈ [Client → Nat]
53     ∧ cstate ∈ [Client → List]
  | For the server replica: |

```

```

57       $\wedge sbuf \in [Client \rightarrow Seq(Op)]$ 
58       $\wedge srec \in [Client \rightarrow Nat]$ 
59       $\wedge sstate \in [Client \rightarrow List]$ 
      For communication between the server and the clients:
63       $\wedge comm!TypeOK$ 
64 |-----|
      The Init predicate.
68 Init  $\triangleq$ 
69       $\wedge cop = Cop$ 
      For the client replicas:
73       $\wedge cbuf = [c \in Client \mapsto \langle \rangle]$ 
74       $\wedge crec = [c \in Client \mapsto 0]$ 
75       $\wedge cstate = [c \in Client \mapsto State]$ 
      For the server replica:
79       $\wedge sbuf = [c \in Client \mapsto \langle \rangle]$ 
80       $\wedge srec = [c \in Client \mapsto 0]$ 
81       $\wedge sstate = [c \in Client \mapsto State]$ 
      For communication between the server and the clients:
85       $\wedge comm!Init$ 
86 |-----|
      Client  $c \in Client$  issues an operation  $op$ .
90 Do( $c$ )  $\triangleq$ 
91       $\wedge Print("Do", TRUE)$ 
92       $\wedge cop[c] \neq \langle \rangle$ 
93       $\wedge LET\ op \triangleq Head(cop[c])$ 
94      IN  $\wedge Print(op, TRUE)$ 
95       $\wedge cstate' = [cstate\ EXCEPT\ ![c] = Apply(op, @)]$ 
96       $\wedge cbuf' = [cbuf\ EXCEPT\ ![c] = Append(@, op)]$ 
97       $\wedge comm!CSend([c \mapsto c, ack \mapsto crec[c], op \mapsto op])$ 
98       $\wedge crec' = [crec\ EXCEPT\ ![c] = 0]$ 
99       $\wedge cop' = [cop\ EXCEPT\ ![c] = Tail(@)]$ 
100      $\wedge UNCHANGED\ sVars$ 
101 |-----|
      The Next state relation.
105 Next  $\triangleq$ 
106      $\vee \exists c \in Client : Do(c)$ 
      The Spec.
110 Spec  $\triangleq Init \wedge \Box [Next]_{vars}$ 
111 |-----|
  
```

\ \* Modification History  
 \ \* Last modified Sun Jul 01 21:13:54 CST 2018 by hengxin  
 \ \* Created Sat Jun 23 17:14:18 CST 2018 by hengxin