```
- Module JupiterInterface
1 1
    This module declares the parameters and defines the operators that describe the interface of a
    family of Jupiter specs.
    EXTENDS SequenceUtils, OT
 7 |
    CONSTANTS
         Client,
                        the set of client replicas
 9
         Server,
10
                         the (unique) server replica
         Msq,
                        the set of messages
11
         Char,
12
                         the set of characters
         InitState
                        the initial state of each replica
13
    ASSUME We assume that all inserted elements are unique.
15
               Range(InitState) \cap Char = \{\} due to the uniqueness requirement
16
17
    VARIABLES
18
                    op[r]: the actual operation applied at replica r \in Replica
19
         aop,
                    state[r]: state (the list content) of replica r \in Replica
         state,
20
                          cincoming[c]: incoming channel at the client c \in Client
21
         cincoming,
                          incoming channel at the Server
22
         sincoming,
23
                   a set of chars allowed to insert; this is for model checking
    intVars \triangleq \langle aop, state, cincoming, sincoming, chins \rangle
26
    Comm \triangleq INSTANCE \ CSComm
27
    Replica \triangleq Client \cup \{Server\}
    List \triangleq Seq(Char \cup Range(InitState))
                                                                 all possible lists
    MaxLen \stackrel{\Delta}{=} Cardinality(Char) + Len(InitState) the max length of lists in any state
    ClientNum \stackrel{\triangle}{=} Cardinality(Client)
    Priority \triangleq CHOOSE f \in [Client \rightarrow 1 .. ClientNum] : Injective(f)
35
    The set of all operations. Note: The positions are indexed from 1.
   Rd \stackrel{\triangle}{=} [type : \{ \text{``Rd''} \}]
    Del \triangleq [type : \{ "Del" \}, pos : 1 .. MaxLen]
    Ins \stackrel{\triangle}{=} [type: \{"Ins"\}, pos: 1...(MaxLen + 1), ch: Char, pr: 1...ClientNum] pr: priority
    Op \stackrel{\triangle}{=} Ins \cup Del Now we don't consider Rd operations
    SetNewAop(r, aopr) \stackrel{\triangle}{=}
46
         aop' = [aop \ EXCEPT \ ![r] = aopr]
47
    ApplyNewAop(r) \stackrel{\triangle}{=}
49
         state' = [state \ EXCEPT \ ![r] = Apply(aop'[r], @)]
50
51
```

```
TypeOKInt \triangleq
52
          \land aop \in [Replica \rightarrow Op \cup \{Nop\}]
53
          \land state \in [Replica \rightarrow List]
54
          \land chins \subseteq Char
55
    InitInt \stackrel{\triangle}{=}
57
          \land aop = [r \in Replica \mapsto Nop]
58
          \land state = [r \in Replica \mapsto InitState]
59
          \wedge chins = Char
60
     DoIns(DoOp(\_,\_), c) \stackrel{\Delta}{=} Client c \in Client generates an "Ins" operation.
62
         \exists ins \in Ins :
63
             \land ins.pos \in 1 ... (Len(state[c]) + 1)
64
             \land \mathit{ins.ch} \in \mathit{chins}
65
             \land \ ins.pr = Priority[c]
66
             \wedge DoOp(c, ins)
67
             \land chins' = chins \setminus \{ins.ch\} We assume that all inserted elements are unique.
68
     DoDel(DoOp(\_,\_), c) \stackrel{\triangle}{=} Client c \in Client generates a "Del" operation.
70
         \exists del \in Del:
71
             \land del.pos \in 1 \dots Len(state[c])
72
             \wedge DoOp(c, del)
73
             ∧ UNCHANGED chins
74
     DoInt(DoOp(\_,\_), c) \triangleq
                                       Client c \in Client issues an operation.
          \wedge \vee DoIns(DoOp, c)
77
78
             \vee DoDel(DoOp, c)
          \land ApplyNewAop(c)
79
     RevInt(ClientPerformInt(\_,\_), c) \stackrel{\triangle}{=} Client c \in Client receives and processes a message.
81
          \land Comm! CRev(c)
82
83
          \land ClientPerformInt(c, Head(cincoming[c]))
          \land ApplyNewAop(c)
84
          \land UNCHANGED chins
85
    SRevInt(ServerPerformInt(\_)) \stackrel{\triangle}{=} The Server receives and processes a message.
87
          \land Comm! SRev
88
             ServerPerformInt(Head(sincoming))
89
              ApplyNewAop(Server)
90
              UNCHANGED chins
          \wedge
91
     \* Modification History
     \* Last modified Wed Jan 02 18:56:22 CST 2019 by hengxin
     \* Created Tue Dec 04 19:01:01 CST 2018 by hengxin
```