

```

1  |----- MODULE JupiterCtx -----|
   | Definitions for context-based Jupiter protocols, including AbsJupiter, CJupiter, and XJupiter. |
5  | EXTENDS JupiterInterface |
6  |-----|
7  VARIABLES
8      cseq,      cseq[c]: local sequence number at client c ∈ Client
9      ds         ds[r]: document state (a set of Oids) of replica r ∈ Replica

11 ctxVars ≜ ⟨cseq, ds⟩
12 |-----|
13 Oid ≜ [c : Client, seq : Nat] operation identifier
14 Cop ≜ [op : Op ∪ {Nop}, oid : Oid, ctx : SUBSET Oid] contexted-based op
16 ClientOf(cop) ≜ cop.oid.c

18 COT(lcp, rcop) ≜ OT of two Cop(s)
19 [lcp EXCEPT !.op = Xform(lcp.op, rcop.op), !.ctx = @ ∪ {rcop.oid}]

21 UpdateDS(r, oid) ≜ update ds[r] to include new oid ∈ Oid
22 ds' = [ds EXCEPT ![r] = @ ∪ {oid}]
23 |-----|
24 TypeOKCtx ≜
25   ∧ cseq ∈ [Client → Nat]
26   ∧ ds ∈ [Replica → SUBSET Oid]

28 InitCtx ≜
29   ∧ cseq = [c ∈ Client ↦ 1]
30   ∧ ds = [r ∈ Replica ↦ {}]

32 DoCtx(c) ≜
33   ∧ cseq' = [cseq EXCEPT ![c] = @ + 1]
34   ∧ UpdateDS(c, [c ↦ c, seq ↦ cseq[c]))

36 RevCtx(c) ≜
37   ∧ UpdateDS(c, Head(cincoming[c]).oid)
38   ∧ UNCHANGED cseq

40 SRevCtx ≜
41   ∧ UpdateDS(Server, Head(sincoming).oid)
42   ∧ UNCHANGED cseq
43 |-----|

\ * Modification History
\ * Last modified Wed Jan 02 20:44:02 CST 2019 by hengxin
\ * Created Wed Dec 05 20:03:50 CST 2018 by hengxin

```