

```

1  |----- MODULE JupiterCtx -----|
  | Definitions for context-based Jupiter protocols, including AbsJupiter, CJupiter, and XJupiter. |
5  | EXTENDS JupiterInterface, OT |
6  |-----|
7  | VARIABLES |
8      cseq,      cseq[c]: local sequence number at client c ∈ Client
9      ds         ds[r]: document state (i.e., a set of Oids) of replica r ∈ Replica
11 ctxVars ≜ ⟨cseq, ds⟩
12 |-----|
13 Oid ≜ [c : Client, seq : Nat] operation identifier
14 Cop ≜ [op : Op ∪ {Nop}, oid : Oid, ctx : SUBSET Oid] context-based op
16 ClientOf(cop) ≜ cop.oid.c
18 COT(lcop, rcop) ≜ OT of lcop ∈ Cop against rcop ∈ Cop
19      [lcop EXCEPT !.op = OT(lcop.op, rcop.op), !.ctx = @ ∪ {rcop.oid}]
21 UpdateDS(r, oid) ≜ update ds[r] to include new oid ∈ Oid
22      ds' = [ds EXCEPT ![r] = @ ∪ {oid}]
23 |-----|
24 TypeOKCtx ≜
25      ∧ cseq ∈ [Client → Nat]
26      ∧ ds ∈ [Replica → SUBSET Oid]
28 InitCtx ≜
29      ∧ cseq = [c ∈ Client ↦ 1]
30      ∧ ds = [r ∈ Replica ↦ {}]
32 DoCtx(c) ≜
33      ∧ cseq' = [cseq EXCEPT ![c] = @ + 1]
34      ∧ UpdateDS(c, [c ↦ c, seq ↦ cseq[c]) oid for newly generated operation
36 RevCtx(c) ≜
37      ∧ UNCHANGED cseq
38      ∧ UpdateDS(c, Head(cincoming[c]).oid)
40 SRevCtx ≜
41      ∧ UNCHANGED cseq
42      ∧ UpdateDS(Server, Head(sincoming).oid)
43 |-----|
  | * Modification History
  | * Last modified Sat Jan 19 21:13:06 CST 2019 by hengxin
  | * Created Wed Dec 05 20:03:50 CST 2018 by hengxin

```