

Consensus Number

魏恒峰

hfwei@nju.edu.cn

2017 年 12 月 14 日

Definition (Consensus Number)

The **consensus number** for X is the largest n for which X solves n -thread consensus.

If no largest n exists, the consensus number is said to be **infinite**.

Lemma (Y Implements X)

Theorem (Consensus Number as ...)

in the following, main results (table)

beautiful ideas and proofs

What is a Protocol \mathcal{P} ?

Protocol

$$\mathcal{P} = \{\text{All executions of this protocol}\}$$

Execution

$$e = \sigma_0 \xrightarrow{o_1} \sigma_1 \xrightarrow{o_2} \cdots \xrightarrow{o_{n-1}} \sigma_n$$

State


σ_i : states of individual threads + states of shared objects

Operation

o_i : method calls to a shared object

Modeling \mathcal{P} as a Computation “Tree”

(Binary Consensus for 2 Threads)



Theorem (Bivalent Initial State)

Every 2-thread binary consensus protocol has a bivalent initial state.

Theorem (Bivalent Initial State)


Every 2-thread binary consensus protocol has a bivalent initial state.

$$(A, B, O) : (0, 0, *) \quad (1, 1, *) \quad (0, 1, *) \quad (1, 0, *)$$

Theorem (Bivalent Initial State)

Every 2-thread binary consensus protocol has a bivalent initial state.

$$(A, B, O) : (0, 0, *) \quad (1, 1, *) \quad (0, 1, *) \quad (1, 0, *)$$



Lemma (Bivalent Initial State)

Every n -thread (binary) consensus protocol has a bivalent initial state.

Lemma (Bivalent Initial State)

Every n -thread (binary) consensus protocol has a bivalent initial state.

Theorem (Existence of Critical States)

Every wait-free consensus protocol has a critical state.

Lemma (Bivalent Initial State)

Every n -thread (binary) consensus protocol has a bivalent initial state.

Theorem (Existence of Critical States)

Every wait-free consensus protocol has a critical state.

Proof.

fig here. □

Thank
You!