


# Specification, Implementation, and Complexity of Replicated Data Types with Composite Operations

Hengfeng Wei

State Key Laboratory for Novel Software Technology, Nanjing University, China


hfwei@nju.edu.cn

 <https://orcid.org/0000-0002-0427-9710>

Huang Yu

State Key Laboratory for Novel Software Technology, Nanjing University, China

yuhuang@nju.edu.cn

 <https://orcid.org/0000-0001-8921-036X>

Jian Lu

State Key Laboratory for Novel Software Technology, Nanjing University, China

lj@nju.edu.cn

---

## Abstract

2012 ACM Subject Classification

Keywords and phrases Replicated set

Digital Object Identifier 10.4230/LIPIcs...

## 1 Introduction

## 2 Preliminaries

### 2.1 Observed-Remove Set (OR-Set)

$$\mathcal{F}_{\text{orset}}(\text{rd}, E, \text{op}, \text{vis}, \text{ar}) = \{a \mid \exists e \in E. \text{op}(e) = \text{add}(a) \quad (1)$$

$$\wedge (\forall f \in E. \text{op}(f) = \text{rm}(a) \implies \neg(e \xrightarrow{\text{vis}} f))\}. \quad (2)$$

## 3 Replicated Data Types with Composite Operations

### 3.1 Specification

We consider a composite operation of a replicated data type  $\tau$  in the form of  $C = A \oplus B$ , where  $A$ ,  $B$ , and  $C$  are different objects of type  $\tau$ .

Following [1], we specify the semantics of a composite operation  $A \oplus B$  of a replicated data type  $\tau$  by a function  $\mathcal{F}_\tau$  that determines the return value of  $\oplus$  based on prior operations performed on the two objects involved (i.e.,  $A$  and  $B$ ). However,  $\mathcal{F}_\tau$  for a composite operation  $\oplus$  takes as parameters two, not one as in [1], *operation contexts*, one on each object involved.

*Q : Generalize to different data types?*

*Note: Partial operation context [2]*



© Hengfeng Wei, Yu Huang, and Jian Lu;

licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

LIPICS Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

34 ► **Definition 1** (Product of Operation Contexts). Consider two operation contexts for the  
 35 same replicated data type  $\tau$ :

$$36 \quad \mathcal{C}_A = (E_A, \text{op}_A, \text{vis}_A, \text{ar}_A) \quad (3)$$

$$37 \quad \mathcal{C}_B = (E_B, \text{op}_B, \text{vis}_B, \text{ar}_B) \quad (4)$$

39 The product  $\mathcal{C} = \mathcal{C}_A \times \mathcal{C}_B$  of  $\mathcal{C}_A$  and  $\mathcal{C}_B$  is also an operation context defined as  $\mathcal{C} =$   
 40  $(E, \text{op}, \text{vis}, \text{ar})$ , where

$$41 \quad \text{■ } E = E_A \times E_B$$

$$42 \quad \text{■ } \text{op} = \text{op}_A \sqcup \text{op}_B$$

$$43 \quad \text{■ } \text{vis} = \text{vis}_A \times \text{vis}_B$$

$$44 \quad \text{■ } \text{ar} = \text{ar}_A \times \text{ar}_B$$

► **Definition 2.**

$$45 \quad \mathcal{F}_\tau(\oplus, \mathcal{C}_A, \mathcal{C}_B) = \mathcal{F}_\tau(\oplus, \mathcal{C}_A \times \mathcal{C}_B) \quad (5)$$

## 47 **4 Replicated Set with Composite Operations**

48 We consider the replicated set data type with composite operations including union ( $\cup$ ),  
 49 intersection ( $\cap$ ), and set difference ( $\setminus$ ).

### 50 **4.1 Specification**

$$51 \quad \mathcal{F}_{\text{orset}}(A \setminus B, \mathcal{C}_A, \mathcal{C}_B) = \{a \mid \dots\}. \quad (6)$$

### 53 **4.2 Protocol**

## 54 **5 Related Work**

## 55 **6 Conclusion and Future Work**

## 56 **References**

- 57 **1** Sebastian Burckhardt, Alexey Gotsman, Hongseok Yang, and Marek Zawirski. Replic-  
 58 ated data types: Specification, verification, optimality. In *Proceedings of the 41st ACM*  
 59 *SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, POPL '14, pages  
 60 271–284, New York, NY, USA, 2014. ACM. URL: <http://doi.acm.org/10.1145/2535838.2535848>, doi:10.1145/2535838.2535848.
- 62 **2** Alexey Gotsman and Hongseok Yang. Composite replicated data types. In *European*  
 63 *Symposium on Programming Languages and Systems*, pages 585–609. Springer, 2015.