Specification and Implementation of Replicated List

— The Jupiter Protocol Revisited

(Brief Announcement at PODC'2018)

Hengfeng Wei, Yu Huang, Jian Lu

Nanjing University

July 24, 2018

Background

Collaborative Text Editing Systems



(a) Google Docs



(c) Wikipedia



(b) Apache Wave



Replication (for availability)



Replication (for availability)



- Replicas respond to user operations immediately
 - ► Updates are propagated asynchronously

Replicated List

INS(a, p): Insert a at position p.

 $\mathrm{DEL}(p)$: Delete an element at position p.

READ: Return the list.

Replicated List

INS(a, p): Insert a at position p.

 $\mathrm{DEL}(p)$: Delete an element at position p.

READ: Return the list.

To implement a highly available replicated list object.

Definition (Eventual Convergence)

The final lists at all replicas are identical at quiescence.



Definition (Strong Eventual Consistency)

The lists at the replicas that *have executed the same set of user operations* are identical.

Definition (Eventual Convergence)

The final lists at all replicas are identical at quiescence.



Definition (Strong Eventual Consistency)

The lists at the replicas that *have executed the same set of user operations* are identical.

Specify little on *intermediate states* going through by replicas.

Specification and Complexity of Collaborative Text Editing

Hagit Attiya Technion

Adam Morrison Technion Sebastian Burckhardt Microsoft Research

> Hongseok Yang University of Oxford

Alexey Gotsman IMDEA Software Institute

Marek Zawirski* Inria & Sorbonne Universités, UPMC Univ Paris 06, LIP6

Strong/Weak List Specification

Global properties on all possible states at all replicas.

¹CRDT: Conflict-free Replicated Data Types [?]
²OT: Operational Transformation [?]

Specification and Complexity of Collaborative Text Editing

Hagit Attiya Technion

Adam Morrison Technion Sebastian Burckhardt Microsoft Research

> Hongseok Yang University of Oxford

Alexey Gotsman IMDEA Software Institute

Marek Zawirski*
Inria & Sorbonne Universités,
UPMC Univ Paris 06. LIP6

Strong/Weak List Specification

Global properties on all possible states at all replicas.

Proved: CRDT ¹-based RGA [?] protocol satisfies the strong list spec.

Conjecture: OT ²-based *Jupiter* [?] protocol satisfies the weak list spec.

¹CRDT: Conflict-free Replicated Data Types [?]
²OT: Operational Transformation [?]

Does Jupiter satisfy the weak list specification?



Does Jupiter satisfy the weak list specification?



Yes, it does.

Weak List Specification

Definition (Weak List Specification A_{weak} [?])

Informally, A_{weak} requires the ordering between elements that are not deleted to be consistent across the system.


Definition (Weak List Specification A_{weak} [?])

Informally, A_{weak} requires the ordering between elements that are not deleted to be consistent across the system.


$$\forall \sigma, \sigma' : a, b \in \sigma \cap \sigma' \implies (a \prec_{\sigma} b \iff a \prec_{\sigma'} b)$$


$$\forall \sigma, \sigma': a,b \in \sigma \cap \sigma' \implies (a \prec_{\sigma} b \iff a \prec_{\sigma'} b)$$

$$\forall \sigma, \sigma' : a, b \in \sigma \cap \sigma' \implies (a \prec_{\sigma} b \iff a \prec_{\sigma'} b)$$



$$\forall \sigma, \sigma' : a, b \in \sigma \cap \sigma' \implies (a \prec_{\sigma} b \iff a \prec_{\sigma'} b)$$





Thank You!



Office 302

Mailbox: H016

hfwei@nju.edu.cn