

Parameterized and Runtime-tunable Snapshot Isolation in Distributed Transactional Key-value Stores

Hengfeng Wei, Yu Huang, Jian Lu

Nanjing University, China

September 19, 2017



Parameterized and Runtime-tunable Snapshot Isolation

RVSI: Relaxed Version Snapshot Isolation

1 Experimental Evaluation

Parameterized and Runtime-tunable Snapshot Isolation

RVSI: Relaxed Version Snapshot Isolation

1 Experimental Evaluation

Impacts of RVSI specification on the *transaction abort rates* in various scenarios


Impacts of RVSI specification
on the *transaction abort rates* in various scenarios

What about performance?

- ▶ Not done yet in this work
- ▶ RVSI-MS and RVSI-MP protocols in CHAMELEON are simple

CHAMELEON prototype on Aliyun:

- ▶ 3 datacenters ¹
- ▶ 3 nodes in each datacenter
- ▶ Partition & Replication
- ▶ Clients in our lab ²



¹ Located in East China, North China, and South China, respectively.

² Located in East China.

³ <https://github.com/hengxin/aliyun-ping-traces>

CHAMELEON prototype on Aliyun:


- ▶ 3 datacenters ¹
- ▶ 3 nodes in each datacenter
- ▶ Partition & Replication
- ▶ Clients in our lab ²

(One-way) delays among nodes ³:

Within datacenter: 1 ~ 2ms

Across datacenters: 15 ~ 25ms

Clients to nodes: 15 ~ 20ms



¹Located in East China, North China, and South China, respectively.

²Located in East China.

³<https://github.com/hengxin/aliyun-ping-traces>

Three categories of workload parameters for experiments on Aliyun.

Parameter	Value	Explanation
#keys	25 = 5 (rows) \times 5 (columns)	
#clients	5, 10, 15, 20, 25, 30	
#txs/client	1000	
#ops/tx	\sim Binomial(20, 0.5)	
rwRatio	1:2, 1:1, 4:1	#reads/#writes
zipfExponent	1	parameter for Zipfian distribution
minInterval	0ms	min/max/mean inter-transaction time
maxInterval	10ms	
meanInterval	5ms	
(k_1, k_2, k_3)	(1,0,0) (1,1,0) (1,1,1) (2,0,0) (2,0,1) (2,1,1)	

Three categories of workload parameters for experiments on Aliyun.

Parameter	Value	Explanation
#keys	25 = 5 (rows) \times 5 (columns)	
#clients	5, 10, 15, 20, 25, 30	
#txs/client	1000	
#ops/tx	\sim Binomial(20, 0.5)	
rwRatio	1:2, 1:1, 4:1	#reads/#writes
zipfExponent	1	parameter for Zipfian distribution
minInterval	0ms	min/max/mean inter-transaction time
maxInterval	10ms	
meanInterval	5ms	
(k_1, k_2, k_3)	(1,0,0) (1,1,0) (1,1,1) (2,0,0) (2,0,1) (2,1,1)	

Transactions abort for two reasons:

- ▶ “vc-aborted”: RVSI version constraints violated
- ▶ “wcf-aborted”: the WCF property violated

¹<https://github.com/hengxin/chameleon-transactional-kvstore>

Transactions abort for two reasons:

- ▶ “vc-aborted”: RVS version constraints violated
- ▶ “wcf-aborted”: the WCF property violated

Transaction abort rates due to “vc-aborted” are *sensitive* to different values of k_1 , k_2 , or k_3 ,

¹<https://github.com/hengxin/chameleon-transactional-kvstore>

Transactions abort for two reasons:

- ▶ “vc-aborted”: RVS version constraints violated
- ▶ “wcf-aborted”: the WCF property violated

Transaction abort rates due to “vc-aborted” are *sensitive* to different values of k_1 , k_2 , or k_3 , but those due to “wcf-aborted” are not.

¹<https://github.com/hengxin/chameleon-transactional-kvstore>

Transactions abort for two reasons:

- ▶ “vc-aborted”: RVSI version constraints violated
- ▶ “wcf-aborted”: the WCF property violated

Transaction abort rates due to “vc-aborted” are *sensitive* to different values of k_1 , k_2 , or k_3 , but those due to “wcf-aborted” are not.

$$h \in \text{RVSI} \iff h \in k_1\text{-BV} \cap k_2\text{-FV} \cap k_3\text{-SV} \cap \text{WCF}.$$

¹<https://github.com/hengxin/chameleon-transactional-kvstore>

Transactions abort for two reasons:


- ▶ “vc-aborted”: RVSI version constraints violated
- ▶ “wcf-aborted”: the WCF property violated


Transaction abort rates due to “vc-aborted” are *sensitive* to different values of k_1 , k_2 , or k_3 , but those due to “wcf-aborted” are not.

$$h \in \text{RVSI} \iff h \in k_1\text{-BV} \cap k_2\text{-FV} \cap k_3\text{-SV} \cap \text{WCF}.$$


We report the results under the read-frequent workloads ¹.

¹<https://github.com/hengxin/chameleon-transactional-kvstore>







The transaction abort rates due to “vc-aborted”



The transaction abort rates due to “vc-aborted” can be **greatly reduced** by **slightly** increasing the values of k_1 , k_2 , or k_3 :

$$vc(1, 0, 0) = 0.1994 \implies vc(2, 1, 1) = 0.0091 \quad (\#clients = 30)$$





Most “vc-aborted” transactions abort because of violating k_2 -FV.

$$fv(1, 0, 0) = 0.1889 \implies fv(2, 0, 0) = 0.1866 \implies fv(1, \mathbf{1}, 0) = 0.0064$$

Question: when does k_1 for k_1 -BV take effect?

It seems that k_1 -BV has *little* impact on the transaction abort rates.



Question: when does k_1 for k_1 -BV take effect?

It seems that k_1 -BV has *little* impact on the transaction abort rates.

It may be the case in the Aliyun scenarios.


What about other scenarios?

Three types of delays for **controlled experiments** on local hosts.




Types	Values (ms)	Explanation
-------	-------------	-------------

Three types of delays for **controlled experiments** on local hosts.




Types	Values (ms)	Explanation
issueDelay	5, 8, 10, 12, 15, 20	delays between clients and replicas

Three types of delays for **controlled experiments** on local hosts.




Types	Values (ms)	Explanation
<code>replDelay</code>	5, 10, 15, 20, 30	delays between masters and slaves


Three types of delays for **controlled experiments** on local hosts.



Types	Values (ms)	Explanation
2pcDelay	10, 20, 30, 40, 50	delays among masters



(Under read-frequent workloads.)



(Under write-frequent workloads.)

When the “issueDelay” gets shorter,
the impacts of k_1 -BV have begun to emerge.

Generally, RVSI *helps to reduce the transaction abort rates* when applications are willing to tolerate certain anomalies.

Generally, RVSI *helps to reduce the transaction abort rates* when applications are willing to tolerate certain anomalies.

k_2 -FV: In the Aliyun scenarios, most transactions have been aborted because of violating k_2 -FV.

Generally, RVSI *helps to reduce the transaction abort rates* when applications are willing to tolerate certain anomalies.

k_2 -FV: In the Aliyun scenarios, most transactions have been aborted because of violating k_2 -FV.

k_1 -BV: In controlled experiments, the impacts of k_1 -BV emerge when the “issueDelay” gets shorter.

Generally, RVSI *helps to reduce the transaction abort rates* when applications are willing to tolerate certain anomalies.

k_2 -FV: In the Aliyun scenarios, most transactions have been aborted because of violating k_2 -FV.

k_1 -BV: In controlled experiments, the impacts of k_1 -BV emerge when the “issueDelay” gets shorter.

k_3 -SV: Complex and challenging (involving multiple data items)