

# Chapter ML:II

## II. Machine Learning Basics

- ❑ On Data
- ❑ Regression
- ❑ Concept Learning: Search in Hypothesis Space
- ❑ Concept Learning: Search in Version Space
- ❑ Measuring Performance

# On Data [Tan et al. 2005]

- ❑ An object  $o \in O$  is described by a set of attributes.  
An object is also known as record, point, case, sample, entity, or instance.
- ❑ An attribute  $A$  is a property of an object.  
An attribute is also known as variable, field, characteristic, or feature.
- ❑ A measurement scale is a system (often a convention) of assigning a numerical or symbolic value to an attribute of an object.

		Attributes			
Objects	ID	Check	Status	Income	Risk
	1	+	single	125 000	No
	2	-	married	100 000	No
	3	-	single	70 000	No
	4	+	married	120 000	No
	5	-	divorced	95 000	Yes
	6	-	married	60 000	No
	7	+	divorced	220 000	No
	8	-	single	85 000	Yes
	9	-	married	75 000	No
	10	-	single	90 000	Yes

# On Data [Tan et al. 2005]

- ❑ An object  $o \in O$  is described by a set of attributes.  
An object is also known as record, point, case, sample, entity, or instance.
- ❑ An attribute  $A$  is a property of an object.  
An attribute is also known as variable, field, characteristic, or feature.
- ❑ A measurement scale is a system (often a convention) of assigning a numerical or symbolic value to an attribute of an object.

		Attributes			
Objects	ID	Check	Status	Income	Risk
	1	+	single	125 000	No
	2	-	married	100 000	No
	3	-	single	70 000	No
	4	+	married	120 000	No
	5	-	divorced	95 000	Yes
	6	-	married	60 000	No
	7	+	divorced	220 000	No
	8	-	single	85 000	Yes
	9	-	married	75 000	No
	10	-	single	90 000	Yes

# On Data [Tan et al. 2005]


- ❑ An object  $o \in O$  is described by a set of attributes.  
An object is also known as record, point, case, sample, entity, or instance.
- ❑ An attribute  $A$  is a property of an object.  
An attribute is also known as variable, field, characteristic, or feature.
- ❑ A measurement scale is a system (often a convention) of assigning a numerical or symbolic value to an attribute of an object.

		Attributes			
Objects	ID	Check	Status	Income	Risk
	1	+	single	125 000	No
	2	-	married	100 000	No
	3	-	single	70 000	No
	4	+	married	120 000	No
	5	-	divorced	95 000	Yes
	6	-	married	60 000	No
	7	+	divorced	220 000	No
	8	-	single	85 000	Yes
	9	-	married	75 000	No
	10	-	single	90 000	Yes

# On Data [Tan et al. 2005]

- ❑ Attribute values may vary from one object to another or one time to another.
- ❑ The same attribute can be mapped to different attribute values.  
Example: height can be measured in feet or meters.
- ❑ Different attributes can be mapped to the same set of values.  
Example: attribute values for person ID and age are integers.

The way an attribute is measured may not match the attribute's properties:



## Types of Attributes

Type		Comparison	Statistics	Examples
<i>categorical</i> <i>(qualitative)</i>	nominal	values are names, only information to distinguish objects  =    ≠	mode, entropy, contingency, correlation, $\chi^2$ test	zip codes, employee IDs, eye color, gender: {male, female}

## Types of Attributes

Type		Comparison	Statistics	Examples
<i>categorical</i> <i>(qualitative)</i>	<b>nominal</b>	values are names, only information to distinguish objects  =    ≠	mode, entropy, contingency, correlation, $\chi^2$ test	zip codes, employee IDs, eye color, gender: {male, female}
	<b>ordinal</b>	enough information to order objects  <   >   ≤   ≥	median, percentiles, rank correlation, run tests, sign tests	hardness of minerals, grades, street numbers, quality: {good, better, best}

# On Data [Tan et al. 2005]

## Types of Attributes

Type		Comparison	Statistics	Examples
<i>categorical</i> <i>(qualitative)</i>	<b>nominal</b>	values are names, only information to distinguish objects  =    ≠	mode, entropy, contingency, correlation, $\chi^2$ test	zip codes, employee IDs, eye color, gender: {male, female}
	<b>ordinal</b>	enough information to order objects  <   >   ≤   ≥	median, percentiles, rank correlation, run tests, sign tests	hardness of minerals, grades, street numbers, quality: {good, better, best}
<i>numeric</i> <i>(quantitative)</i>	<b>interval</b>	differences are meaningful, a unit of measurement exists  +    −	mean, standard deviation, Pearson's correlation, <i>t</i> -test, <i>F</i> -test	calendar dates, temperature in Celsius, temperature in Fahrenheit



## Types of Attributes

Type		Comparison	Statistics	Examples
<i>categorical</i> <i>(qualitative)</i>	nominal	values are names, only information to distinguish objects  =    ≠	mode, entropy, contingency, correlation, $\chi^2$ test	zip codes, employee IDs, eye color, gender: {male, female}
	ordinal	enough information to order objects  <   >   ≤   ≥	median, percentiles, rank correlation, run tests, sign tests	hardness of minerals, grades, street numbers, quality: {good, better, best}
<i>numeric</i> <i>(quantitative)</i>	interval	differences are meaningful, a unit of measurement exists  +    −	mean, standard deviation, Pearson's correlation, <i>t</i> -test, <i>F</i> -test	calendar dates, temperature in Celsius, temperature in Fahrenheit
	ratio	differences and ratios are meaningful  *    /	geometric mean, harmonic mean, percent variation	temperature in Kelvin, monetary quantities, counts, age, length, electrical current

## Types of Attributes

Type		Permissible transformation	Comment
<i>categorical</i> <i>(qualitative)</i>	nominal	any one-to-one mapping, permutation of values	A reassignment of employee ID numbers will not make any difference.

# On Data [Tan et al. 2005]

## Types of Attributes

Type		Permissible transformation	Comment
<i>categorical</i> ( <i>qualitative</i> )	<b>nominal</b>	any one-to-one mapping, permutation of values	A reassignment of employee ID numbers will not make any difference.
	<b>ordinal</b>	any order-preserving change of values: $x \rightarrow f(x)$ , where $f$ is a monotonic	An attribute encompassing the notion of {good, better, best} can be represented equally well by the values {1, 2, 3}.

# On Data [Tan et al. 2005]

## Types of Attributes

Type		Permissible transformation	Comment
<i>categorical</i> ( <i>qualitative</i> )	<b>nominal</b>	any one-to-one mapping, permutation of values	A reassignment of employee ID numbers will not make any difference.
	<b>ordinal</b>	any order-preserving change of values: $x \rightarrow f(x)$ , where $f$ is a monotonic	An attribute encompassing the notion of {good, better, best} can be represented equally well by the values {1, 2, 3}.
<i>numeric</i> ( <i>quantitative</i> )	<b>interval</b>	$x \rightarrow a \cdot x + b$ , where $a$ and $b$ are constants	Thus, the Fahrenheit and Celsius temperature scales differ in terms of where their zero value is and the size of a unit (degree).

# On Data [Tan et al. 2005]

## Types of Attributes

Type		Permissible transformation	Comment
<i>categorical</i> ( <i>qualitative</i> )	<b>nominal</b>	any one-to-one mapping, permutation of values	A reassignment of employee ID numbers will not make any difference.
	<b>ordinal</b>	any order-preserving change of values: $x \rightarrow f(x)$ , where $f$ is a monotonic	An attribute encompassing the notion of {good, better, best} can be represented equally well by the values {1, 2, 3}.
<i>numeric</i> ( <i>quantitative</i> )	<b>interval</b>	$x \rightarrow a \cdot x + b$ , where $a$ and $b$ are constants	Thus, the Fahrenheit and Celsius temperature scales differ in terms of where their zero value is and the size of a unit (degree).
	<b>ratio</b>	$x \rightarrow a \cdot x$ , where $a$ is a constant	Length can be measured in meters or feet.

## Remarks:

- ❑ Identifying, considering, and measuring an attribute  $A$  of an object  $O$  is the heart of model formation and always goes along with a sort of abstraction. Formally, this abstraction is operationalized by a model formation function  $\alpha : O \rightarrow X$ . [\[ML Introduction\]](#)
- ❑ The terms “attribute” and “feature” can be used synonymously. However, a slight distinction is the following: attributes are often associated with objects,  $O$ , while features usually designate the dimensions of the feature space,  $X$ .
- ❑ The type of an attribute is also referred to as the type of a *measurement scale* or *level of measurement*.
- ❑ We call a transformation of an attribute *permissible* if its meaning is unchanged after the transformation.
- ❑ Distinguish between *discrete* attributes and *continuous* attributes. The former can only take a finite or countably infinite set of values, the latter can be measured in infinitely small units. Be careful when deriving from this distinction an attribute's type.
- ❑ We will encode attributes of interval type or ratio type by real numbers. Note that attributes of nominal type and ordinal type can also be encoded by real numbers.
- ❑ Particular learning methods require particular attribute types.

## Types of Data Sets

Data sets may not be a homogeneous collection of objects but come along with differently intricate characteristics:

1. Inhomogeneity of attributes:
2. Inhomogeneity of objects:
3. Inhomogeneity of distributions:
4. Curse of dimensionality:
5. Resolution:

## Types of Data Sets

Data sets may not be a homogeneous collection of objects but come along with differently intricate characteristics:

1. Inhomogeneity of attributes:

Consider the combination of different attribute types within a single object.

2. Inhomogeneity of objects:

Consider the combination of different objects in a single data set.

3. Inhomogeneity of distributions:

The correlation between attributes varies in the sample space.

4. Curse of dimensionality:

Attribute number and object density stand in exponential relation.

5. Resolution:

The number of objects or attributes may be given at different resolutions.



## Types of Data Sets: Record Data

Collection of records, each of which consists of a fixed set of attributes:

ID	Check	Status	Income	Risk
1	+	single	125 000	No
2	-	married	100 000	No
3	-	single	70 000	No
4	+	married	120 000	No
5	-	divorced	95 000	Yes
6	-	married	60 000	No
7	+	divorced	220 000	No
8	-	single	85 000	Yes
9	-	married	75 000	No
10	-	single	90 000	Yes


- ❑ If all elements in a data set have the same fixed set of numeric attributes, they can be thought of as points in a multi-dimensional space.
- ❑ Such data can be represented by a matrix, where each row stores an object and each column stores an attribute.

Example: term-document matrices in information retrieval.

# On Data [Tan et al. 2005]

## Types of Data Sets: Graph Data


### Graph of the Linked Open Data cloud [richard.cyganiak.de] :



# On Data [Tan et al. 2005]

## Types of Data Sets: Ordered Data

Average monthly temperature of land and ocean (= spatio-temporal data) :



## Data Quality

When repeating measurements of a quantity, measurement errors and data collection errors may occur during the measurement process. Questions:

1. What kinds of data quality problems exist?
2. How to detect data quality problems?
3. How to address data quality problems?

## Data Quality

When repeating measurements of a quantity, measurement errors and data collection errors may occur during the measurement process. Questions:

1. What kinds of data quality problems exist?
2. How to detect data quality problems?
3. How to address data quality problems?

### Definition 1 (Precision, Bias, Accuracy)

Given a set of repeated measurements of the same quantity. Then, the closeness of the measurements to one another is called *precision*, a possible systematic variation is called *bias*, and the closeness to the true value is called *accuracy*.

## Data Quality

When repeating measurements of a quantity, measurement errors and data collection errors may occur during the measurement process. Questions:

1. What kinds of data quality problems exist?
2. How to detect data quality problems?
3. How to address data quality problems?

### Definition 1 (Precision, Bias, Accuracy)

Given a set of repeated measurements of the same quantity. Then, the closeness of the measurements to one another is called *precision*, a possible systematic variation is called *bias*, and the closeness to the true value is called *accuracy*.


Examples for data quality problems:

- ❑ noise, artifacts, outliers
- ❑ missing values
- ❑ duplicate data


# On Data [Tan et al. 2005]

## Data Quality: Noise

Noise refers to random modifications of attributes that often have a spatial or temporal characteristics:



sin waves




sin waves with noise

Noise represents the intrinsic variability of data. [Bishop 2006, p.47]

Artifacts refer to more deterministic distortions of a measurement process.

## Data Quality: Outliers


Outliers are members in the data set with characteristics that are considerably different than most of the other elements:





## Data Quality: Outliers

Outliers are members in the data set with characteristics that are considerably different than most of the other elements:



## Data Quality: Missing Values

Main reasons for missing values:

1. Information is not collected.  
Example: people decline to give their age or weight.
2. Attributes may not be applicable to all elements in  $O$ .  
Example: annual income is not applicable to children.
3. Information is not trustworthy.  
Example: profile data on Facebook is intentionally misleading.

Strategies for handling missing values:

- ❑ eliminate members of the data
- ❑ estimate missing values
- ❑ ignore the missing value during analysis
- ❑ replace with all possible values weighted by their probabilities

# On Data [Tan et al. 2005]

## Data Preprocessing

- ❑ sampling of object set  $O$
- ❑ modeling of objects,  $\alpha : O \rightarrow X$
- ❑ sampling of feature space  $X$  [[ML Introduction](#)]
- ❑ selection of attributes (features) [[attributes versus features](#)]
- ❑ transformation of attributes (features)
- ❑ discretization and binarization of attributes (features)
- ❑ dimensionality reduction of feature space  $X$