

# NB-IoT Functional and Performance Report 3GPP and Qualcomm Based Tests

Classification: Confidential

Doc. Type: Report

Revision: Rev. 02

Date: 10/23/2024

Code: Tests, Report, Performance

## Report Info

Operator: admin

DUT: HTNB32L-0XX

Batch: NBITT07-06-010-RETEST

Testplan: ['Yield\_Platform\_for\_Production\_1.0\_PCB2\_CMW500.ini']

Plat SW Ver.: Yield-Alpha 0.1

Plat HW Ver.: 1.0 ID1

# **Summary**

Test Start Time: 10/23/2024 11:56:53 Test End Time: 10/23/2024 12:00:01

Total Test Time: 0:03:08
Test Items Passed: 124
Test Items Failed: 0
Number of Test Items: 124

#### **Tests Resume**

Test item	Qty	Set Lower	Set Upper	Res Lower	Res Mean	Res Upper	Unit	Judg
Short Open	13	8	340	10.3	212.9	330.0	kΩ	PASS
Firmware Flash	5	-	-	-	-	-	-	PASS
Interleaved	22	-	-	-	-	-	_	PASS
Peripherals	11	-	-	-	-	-	-	PASS
DeepSleep	4	0.4	25.0	0.9	6.3	14.5	μΑ	PASS
Calibration	4	-	-	-	-	-	-	PASS
Max_Output 00@00	5	21.0	24.2	22.1	22.2	22.4	dBm	PASS
Max_Output 03@00	5	19.8	22.3	20.9	21.4	21.8	dBm	PASS
EVM	10	-	17.5	0.3	2.4	7.3	%	PASS
Freq Error	10	-	195.0	0.23	3.4	10.49	Hz	PASS
OBW	10	-	200.0	141.56	158.3	182.81	Hz	PASS
ACLR	10	-	-36.2	-56.2	-54.4	-51.8	dBc	PASS
SEM	10	-	0.0	0.0	0.0	0.0	%	PASS
BLER	5	-	5.0	0.0	0.0	0.0	%	PASS

## Test HT criteria - ShortOpen in Default configuration

Pin Name	Lower	Upper	Result	Unit	Judgement
VCC	8	340	10.3	kΩ	PASS
NRST	8	340	330.0	kΩ	PASS
воот	8	340	330.0	kΩ	PASS
UART1_TX	8	340	330.0	kΩ	PASS
UART1_RX	8	340	330.0	kΩ	PASS
USIM_VCC	8	340	39.9	kΩ	PASS
ESIM_VCC	8	340	57.2	kΩ	PASS
IO_1833_SEL	8	340	261.8	kΩ	PASS
USIM_IO	8	340	44.3	kΩ	PASS
ESIM_IO	8	340	330.0	kΩ	PASS
USIM_CLK	8	340	330.0	kΩ	PASS
ESIM_CLK	8	340	330.0	kΩ	PASS
SIM_NRST	8	340	44.3	kΩ	PASS

## Test HT criteria - Firmware Flash in Default configuration

ID	Lower	Upper	Result	Unit	Judgement
Erase	-	-	PASS	-	PASS
Bootload	-	-	PASS	_	PASS
App Data	-	-	PASS	-	PASS
Merge RF Table 1	-	-	PASS	-	PASS
Merge RF Table 2	-	-	PASS	-	PASS

## Test HT criteria - Interleaved in Default configuration

ID	Lower	Upper	Result	Unit	Judgement
GPIO2 [Int0]	0	-	0	-	PASS
GPIO3 [Int0]	0	-	0	-	PASS
GPIO5 [Int0]	0	-	0	-	PASS
SWD_CLK [Int0]	0	-	0	-	PASS
GPIO6 [Int0]	0	-	0	-	PASS
GPIO10 [Int0]	0	-	0	-	PASS
GPIO7 [Int0]	0	-	0	-	PASS
GPIO1 [Int0]	-	1	1	-	PASS
GPIO4 [Int0]	-	1	1	-	PASS
SWD_IO [Int0]	-	1	1	-	PASS
AON_GPIO [Int0]	-	1	1	-	PASS
GPIO2 [Int1]	-	1	1	-	PASS
GPIO3 [Int1]	-	1	1	-	PASS
GPIO5 [Int1]	-	1	1	-	PASS
SWD_CLK [Int1]	-	1	1	-	PASS
GPIO6 [Int1]	-	1	1	-	PASS
GPIO10 [Int1]	-	1	1	-	PASS
GPIO7 [Int1]	-	1	1	-	PASS
GPIO1 [Int1]	0	-	0	-	PASS
GPIO4 [Int1]	0	-	0	-	PASS
SWD_IO [Int1]	0	-	0	-	PASS
AON_GPIO [Int1]	0	-	0	-	PASS

# Test HT criteria - Peripherals in Default configuration

ID	Lower	Upper	Result	Unit	Judgement
UART0 TX	-	-	PASS	-	PASS
UART0 RX	-	-	PASS	-	PASS
UART2 TX	-	-	PASS	-	PASS
UART2 RX	-	-	PASS	-	PASS
I2C0 TX	-	-	PASS	-	PASS
I2C0 RX	-	-	PASS	-	PASS
I2C1 TX	-	-	PASS	-	PASS
I2C1 RX	-	-	PASS	-	PASS
SPI1 TX	-	-	PASS	-	PASS
SPI1 RX	-	-	PASS	-	PASS
USIM	-	-	PASS	-	PASS

## Test HT criteria - DeepSleep in Default configuration

Sleep Mode	Lower	Upper	Result	Unit	Judgement
HIB2	0.4	1.5	0.9	μΑ	PASS
HIB1	2.0	4.0	3.0	μΑ	PASS
SLEEP2	5.0	10.0	6.8	μΑ	PASS
SLEEP1	10.0	25.0	14.5	μΑ	PASS

## Test Qualcomm criteria - Calibration in Default configuration

ID	Lower	Upper	Result	Unit	Judgement
AFC	-	-	PASS	-	PASS
AGC	-	-	PASS	-	PASS
APC	-	-	PASS	-	PASS
DPD	-	-	PASS	-	PASS

Test 6.2.2F - UE maximum output power in Default configuration

Band	Frequency	Test item	Lower	Upper	Result	Unit	Judgement
01	1950.0	00@00	21.0	24.2	22.1	dBm	PASS
01	1950.0	03@00	19.8	22.3	20.9	dBm	PASS
03	1747.5	00@00	21.0	24.2	22.1	dBm	PASS
03	1747.5	03@00	19.8	22.3	21.4	dBm	PASS
05	836.5	00@00	21.0	24.2	22.1	dBm	PASS
05	836.5	03@00	19.8	22.3	21.5	dBm	PASS
08	897.5	00@00	21.0	24.2	22.1	dBm	PASS
08	897.5	03@00	19.8	22.3	21.3	dBm	PASS
28	725.5	00@00	21.0	24.2	22.4	dBm	PASS
28	725.5	03@00	19.8	22.3	21.8	dBm	PASS

Test 6.5.2.1F.1 - Error vector magnitude (EVM) in Default configuration

Band	Frequency	Test item	Lower	Upper	Result	Unit	Judgement
01	1950.0	00@00	-	17.5	0.3	%	PASS
01	1950.0	03@00	-	17.5	7.3	%	PASS
03	1747.5	00@00	-	17.5	0.4	%	PASS
03	1747.5	03@00	-	17.5	4.4	%	PASS
05	836.5	00@00	-	17.5	0.3	%	PASS
05	836.5	03@00	-	17.5	2.8	%	PASS
08	897.5	00@00	-	17.5	0.4	%	PASS
08	897.5	03@00	-	17.5	5.0	%	PASS
28	725.5	00@00	_	17.5	0.4	%	PASS
28	725.5	03@00	-	17.5	2.3	%	PASS

Test 6.5.1F - Frequency Error in Default configuration

Band	Frequency	Test item	Lower	Upper	Result	Unit	Judgement
01	1950.0	00@00	-	195.0	5.46	Hz	PASS
01	1950.0	03@00	-	195.0	10.49	Hz	PASS
03	1747.5	00@00	-	174.75	4.45	Hz	PASS
03	1747.5	03@00	-	174.75	0.81	Hz	PASS
05	836.5	00@00	-	167.3	4.99	Hz	PASS
05	836.5	03@00	-	167.3	1.11	Hz	PASS
08	897.5	00@00	-	179.5	1.95	Hz	PASS
08	897.5	03@00	-	179.5	2.1	Hz	PASS
28	725.5	00@00	-	145.1	0.23	Hz	PASS
28	725.5	03@00	-	145.1	2.91	Hz	PASS

Test 6.6.1F - Occupied bandwidth (OBW) in Default configuration

Band	Frequency	Test item	Lower	Upper	Result	Unit	Judgement
01	1950.0	00@00	-	200.0	155.62	Hz	PASS
01	1950.0	03@00	-	200.0	182.81	Hz	PASS
03	1747.5	00@00	-	200.0	143.44	Hz	PASS
03	1747.5	03@00	-	200.0	168.75	Hz	PASS
05	836.5	00@00	-	200.0	141.56	Hz	PASS
05	836.5	03@00	-	200.0	168.75	Hz	PASS
08	897.5	00@00	-	200.0	143.44	Hz	PASS
08	897.5	03@00	-	200.0	168.75	Hz	PASS
28	725.5	00@00	_	200.0	141.56	Hz	PASS
28	725.5	03@00	-	200.0	168.75	Hz	PASS

# Test 6.6.2.3F - ACLR in Default configuration

Band	Frequency	Test item	Lower	Upper	Result	Unit	Judgement
01	1950.0	00@00	-	-36.2	-54.0	dBc	PASS
01	1950.0	03@00	-	-36.2	-51.8	dBc	PASS
03	1747.5	00@00	-	-36.2	-54.9	dBc	PASS
03	1747.5	03@00	-	-36.2	-53.4	dBc	PASS
05	836.5	00@00	-	-36.2	-56.2	dBc	PASS
05	836.5	03@00	-	-36.2	-54.7	dBc	PASS
08	897.5	00@00	-	-36.2	-56.1	dBc	PASS
08	897.5	03@00	-	-36.2	-51.9	dBc	PASS
28	725.5	00@00	_	-36.2	-56.2	dBc	PASS
28	725.5	03@00	-	-36.2	-55.3	dBc	PASS

Test 6.6.2.1F - Spectrum Emission Mask (SEM) in Default configuration

Band	Frequency	Test item	Lower	Upper	Result	Unit	Judgement
01	1950.0	00@00	-	0.0	0.0	%	PASS
01	1950.0	03@00	-	0.0	0.0	%	PASS
03	1747.5	00@00	-	0.0	0.0	%	PASS
03	1747.5	03@00	-	0.0	0.0	%	PASS
05	836.5	00@00	-	0.0	0.0	%	PASS
05	836.5	03@00	-	0.0	0.0	%	PASS
08	897.5	00@00	-	0.0	0.0	%	PASS
08	897.5	03@00	-	0.0	0.0	%	PASS
28	725.5	00@00	_	0.0	0.0	%	PASS
28	725.5	03@00	-	0.0	0.0	%	PASS

## Test HT criteria - BLER in Default configuration

Band	DIChannel	CellLevel	Lower	Upper	Result	Unit	Judgement
01	300	-100	-	5.0	0.0	%	PASS
03	1400	-100	-	5.0	0.0	%	PASS
05	2525	-100	-	5.0	0.0	%	PASS
08	3625	-100	-	5.0	0.0	%	PASS
28	9435	-100	-	5.0	0.0	%	PASS