



CRYPTO HUNTER PRO

CIE - Crypto Intelligence Engine

Advanced Cryptocurrency Wallet Scanner Module

Complete User Manual

August / 2026

*Equipe Crypto Hunter Pro
Henrique Lourenço e Alexandre Senra*

=====

=====

CREATORS

=====

=====

CRIADOR / CREATOR:

Henrique Lourenco

LinkedIn: <https://www.linkedin.com/in/henriquelourenco>

Instagram: <https://www.instagram.com/henrique.web3>

DOE / DONATE:

BTC: bc1qpq0cgvyxczetumdf87345zzk0zr0xz96ampmhs

ETH: henriquelourenco.eth

PIX: henriquesamuel@yahoo.com.br

CRIADOR / CREATOR:

Alexandre Senra

LinkedIn: <https://www.linkedin.com/in/alexandresenra>

Instagram: https://www.instagram.com/alexandresenra_

EN: Help us keep this project alive! Donate any amount.

EN: Free software, made with dedication. Support the creators!

PT: Ajude-nos a manter este projeto vivo! Doe qualquer valor.

PT: Software livre, feito com dedicacao. Apoie os criadores!

=====

TABLE OF CONTENTS

1. INTRODUCTION

- 1.1. The Problem: Accessibility and Management of Multiple Wallets
- 1.2. The Solution: Crypto Hunter Pro - CIE
- 1.3. Target Audience

2. ARCHITECTURE AND TECHNOLOGY

- 2.1. Architecture Overview
- 2.2. Language and Performance
- 2.3. Project File Structure

3. SUPPORTED NETWORKS AND TOKENS

- 3.1. Supported Networks Overview
- 3.2. Detailed EVM Tokens
- 3.3. Solana Tokens (SPL)
- 3.4. Tron Tokens (TRC-20)

4. ADDRESS DERIVATION

- 4.1. BIP Standards (BIP32, BIP39, BIP44, BIP49, BIP84, BIP86)
- 4.2. Ed25519 (Solana, TON, Stellar, Sui and Near)
- 4.3. Complete Derivation Paths Table

5. APIs AND DATA SOURCES

- 5.1. APIs Used per Network
- 5.2. API Pool System and Rate Limiting

6. SYSTEM REQUIREMENTS

7. INSTALLATION AND COMPILATION

7.1. Prerequisites

7.2. Compilation Process

8. COMPLETE USAGE GUIDE

8.1. Initial Screen and Language Selection

8.2. Main Menu

8.3. Manual Seed Phrase Input

8.4. Excel File Import (Unmixer Seed)

8.5. API Key Configuration

8.6. Network Selection

8.7. Derivation Configuration (BTC/BCH/LTC)

8.8. Index Range

8.9. Optional Passphrase (BIP39)

8.10. Real-Time Scanning

8.11. Results and Excel Report

9. EXCEL REPORTS

9.1. Summary Tab

9.2. With Balance Tab

9.3. With History Tab

9.4. Detailed Columns

10. LICENSE SYSTEM AND ANTI-BYPASS PROTECTION

10.1. License Types

10.2. Anti-Bypass Time Verification

10.3. Behavior in Different Scenarios

11. SECURITY AND BEST PRACTICES

12. FREQUENTLY ASKED QUESTIONS (FAQ)

13. CONCLUSION

1. INTRODUCTION

1.1. The Problem: Accessibility and Management of Multiple Wallets

In the cryptocurrency universe, managing multiple digital assets can become a complex and challenging task. With the proliferation of blockchains and tokens, it is common for users to have funds distributed across various networks. The loss of access to a seed phrase, forgetting derived wallets or the difficulty in tracking balances across different blockchains are recurring problems that can lead to permanent loss of funds.

It is estimated that billions of dollars in cryptocurrencies are permanently inaccessible due to lost keys, forgotten wallets or human errors in managing multiple addresses.

Complexity increases exponentially when we consider that a single seed phrase can generate hundreds of addresses across dozens of different networks, each with its own formats and derivation standards.

The main challenges faced by cryptocurrency holders include:

- **Asset Fragmentation:** Having assets across multiple networks (Ethereum, Bitcoin, Solana, Tron, etc.) makes consolidated portfolio visualization difficult. Each network has its own block explorer and address format.
- **Derived Wallets:** A single seed phrase can generate a virtually infinite number of addresses through different derivation paths. Addresses that have not been used recently can be easily forgotten, especially when using multiple software wallets.
- **Format Complexity:** Networks like Bitcoin have multiple address formats (Legacy starting with 1, SegWit with 3, Native SegWit with bc1q and Taproot with bc1p). Not all wallets support all formats, generating confusion and potential loss of access.
- **Tokens Across Multiple Networks:** Stablecoins like USDT and USDC exist on virtually all networks (Ethereum, BSC, Polygon, Tron, Solana, Arbitrum, etc.), making it impossible to manually check each network for remaining balances.

1.2. The Solution: Crypto Hunter Pro - CIE

The Crypto Hunter Pro - CIE (Crypto Intelligence Engine) was specifically developed to solve these challenges, automating the process of searching and verifying cryptocurrency wallets at industrial scale. The software acts as a cryptographic intelligence engine, capable of systematically scanning multiple blockchains for addresses with balance or transaction history derived from one or more seed phrases.

The program automates the derivation of thousands of addresses across 32 supported networks, verifies balances of 170+ tokens and consolidates results in detailed Excel reports, drastically increasing the chances of finding lost or forgotten assets. The CIE is capable of processing multiple seeds simultaneously, directly importing results from the Unmixer Seed Search module.

1.3. Target Audience

The Crypto Hunter Pro - CIE is intended for:

- Cryptocurrency Holders who have multiple seed phrases and want to verify if there are remaining funds in old or forgotten wallets.
- Security and Digital Forensics Professionals who need to audit wallets derived from seed phrases in investigations.
- Digital Asset Custody and Management Companies that need to systematically verify wallets associated with keys under their custody.
- Blockchain Developers and Researchers who need a robust tool for address derivation analysis.

2. ARCHITECTURE AND TECHNOLOGY

2.1. Architecture Overview

The CIE was designed with a modular and efficient architecture, clearly separating responsibilities into distinct components. The operation flow follows a well-defined pipeline: data input (seed phrases) -> key and address derivation -> balance queries via APIs -> result consolidation -> Excel report generation.

The architecture is composed of eight main modules, each implemented in a separate Go file, ensuring maintainability and code clarity:

Module	File	Responsibility
Main	main.go	Program entry point and main flow orchestration
Globals	globals.go	Struct definitions, global variables, supported networks and tokens
Derivation	derivation.go	Key and address derivation (BIP32/39/44, Ed25519, Zcash)
Network	network.go	API queries, balance verification and transaction history
Scanner	scanner.go	Scanning engine with real-time display
Excel	excel.go	Excel report generation with 3 organized tabs
UI	ui.go	Bilingual CLI user interface (PT/EN)
License	license.go	NTP license system with anti-bypass verification

2.2. Language and Performance

The CIE is built in Go (Golang), a compiled language developed by Google, chosen for its ideal characteristics for this type of application:

- **High Performance:** Go compiles to native code, offering execution speed comparable to C/C++, essential for intensive cryptographic operations such as key derivation.
- **Native Concurrency:** Go's goroutine model enables efficient parallelism in API queries, drastically reducing total scanning time.
- **Static Compilation:** The generated executable is self-contained, with no external runtime dependencies, facilitating distribution and execution on any Windows system.
- **Cross-Compilation:** The code can be compiled for Windows, Linux and macOS from any platform.

2.3. Project File Structure

File	Description
main.go	Entry point, initialization and main menu loop
globals.go	Structs (ScanConfig, ScanResult, TokenResult, etc.), networks, derivations and tokens

derivation.go	Implementation of BIP32/39/44/49/84/86, Ed25519, CashAddr, Bech32
network.go	API pool, query functions per network (EVM, BTC, BCH, LTC, DOGE, TRX, SOL, TON, ZEC, XRP, XLM, ALGO, SUI, NEAR, Liquid) + Alchemy/TronGrid integration
scanner.go	Scan orchestration, real-time display of each verified address
excel.go	Generation of .xlsx with 3 tabs: Summary, With Balance, With History
ui.go	Bilingual CLI interface, menus, network selection, ASCII logo
go.mod / go.sum	Go dependency management
compilador.bat	Automated compilation script for Windows
license.go	NTP anti-bypass license system (direct IPs + cross-validation + HTTPS)

3. SUPPORTED NETWORKS AND TOKENS

3.1. Supported Networks Overview

The CIE supports a total of 32 blockchain networks, organized into 15 selection groups. Each group can be enabled or disabled independently during scan configuration. The table below presents all supported networks with their respective native tokens and address types:

Group	Network(s)	Native Token	Address Type
EVM	Ethereum	ETH	0x... (20 bytes hex)
EVM	BNB Smart Chain (BSC)	BNB	0x... (same EVM address)
EVM	Polygon	POL	0x... (same EVM address)
EVM	Arbitrum	ETH	0x... (same EVM address)
EVM	Avalanche C-Chain	AVAX	0x... (same EVM address)
EVM	Optimism	ETH	0x... (same EVM address)
EVM	Base	ETH	0x... (same EVM address)
EVM	Sonic	S	0x... (same EVM address)
EVM	Mantle	MNT	0x... (same EVM address)
EVM	Flare	FLR	0x... (same EVM address)
EVM	Linea	ETH	0x... (same EVM address)
EVM	Scroll	ETH	0x... (same EVM address)
EVM	Gnosis	xDAI	0x... (same EVM address)
EVM	zkSync Era	ETH	0x... (same EVM address)
EVM	Blast	ETH	0x... (same EVM address)
EVM	Cronos	CRO	0x... (same EVM address)
EVM	Celo	CELO	0x... (same EVM address)
EVM	Berachain	BERA	0x... (same EVM address)

Bitcoin	Bitcoin	BTC	1.../3.../bc1q.../bc1p...
Bitcoin Cash	Bitcoin Cash	BCH	bitcoincash:q.../1...
Tron	Tron	TRX	T... (Base58)
Solana	Solana	SOL	Base58 (32-44 chars)
Litecoin	Litecoin	LTC	L.../M.../ltc1q...
Dogecoin	Dogecoin	DOGE	D... (Base58)
TON	TON	TON	UQ.../EQ... (Base64)
Zcash	Zcash	ZEC	t1... (transparente)
XRP	XRP (Ripple)	XRP	r... (Base58)
Stellar	Stellar	XLM	G... (Ed25519, Base32)
Algorand	Algorand	ALGO	Base32 (58 chars)
Sui	Sui	SUI	0x... (Ed25519, 64 hex)
Near	Near Protocol	NEAR	hex (Ed25519, 64 hex)
Liquid	Liquid Network	L-BTC	ex1... (Bech32)

3.2. Detailed EVM Tokens

In addition to the native balance of each EVM network, the CIE automatically verifies the balances of 138 ERC-20/BEP-20 tokens distributed across the 18 EVM networks. Below is the complete list of tokens verified on each network:

Ethereum (ETH + 24 tokens):

Nativo: ETH. Tokens: USDT, USDC, DAI, BUSD, TUSD, FRAX, WBTC, WETH, LINK, UNI, AAVE, MKR, COMP, SNX, CRV, LDO, SHIB, PEPE, POL, APE, SAND, MANA, GRT, ENS.

BNB Smart Chain - BSC (BNB + 14 tokens):

Nativo: BNB. Tokens: USDT, USDC, BUSD, DAI, CAKE, WBNB, XVS, BTCB, ETH, LINK, DOT, ADA, DOGE, FLOKI.

Polygon (POL + 12 tokens):

Nativo: POL. Tokens: USDT, USDC, DAI, WPOL, AAVE, LINK, WBTC, WETH, CRV, BAL, GNS, QUICK.

Arbitrum (ETH + 11 tokens):

Nativo: ETH. Tokens: USDT, USDC, DAI, WETH, ARB, LINK, GRT, GMX, MAGIC, RDNT, PENDLE.

Avalanche C-Chain (AVAX + 6 tokens):

Nativo: AVAX. Tokens: USDT, USDC, WAVAX, JOE, GMX, sAVAX.

Optimism (ETH + 10 tokens):

Nativo: ETH. Tokens: USDT, USDC, DAI, OP, WETH, LINK, SNX, VELO, AAVE, PERP.

Base (ETH + 9 tokens):

Nativo: ETH. Tokens: USDC, DAI, WETH, cbETH, AERO, BRETT, DEGEN, TOSHI, USDbC.

Sonic (S + 5 tokens):

Nativo: S. Tokens: WETH, wS, BRUSH, EQUAL, USDT.

Mantle (MNT + 6 tokens):

Nativo: MNT. Tokens: USDT, USDC, WMNT, WETH, mETH, PUFF.

Flare (FLR + 3 tokens):

Nativo: FLR. Tokens: WFLR, sFLR, WETH.

Linea (ETH + 5 tokens):

Nativo: ETH. Tokens: USDC, USDT, WETH, DAI, wstETH.

Scroll (ETH + 5 tokens):

Nativo: ETH. Tokens: USDC, USDT, WETH, wstETH, SCR.

Gnosis (xDAI + 6 tokens):

Nativo: xDAI. Tokens: USDC, USDT, WETH, GNO, sDAI, wstETH.

zkSync Era (ETH + 4 tokens):

Nativo: ETH. Tokens: USDC, USDT, WETH, ZK.

Blast (ETH + 3 tokens):

Nativo: ETH. Tokens: USDB, WETH, USDT.

Cronos (CRO + 4 tokens):

Nativo: CRO. Tokens: USDC, USDT, WETH, WCRO.

Celo (CELO + 5 tokens):

Nativo: CELO. Tokens: cUSD, cEUR, USDC, USDT, WETH.

Berachain (BERA + 6 tokens):

Nativo: BERA. Tokens: HONEY, USDC, USDT, WETH, WBTC, WBERA.

3.3. Solana Tokens (SPL)

On the Solana network, the CIE verifies the native SOL balance and 13 SPL (Solana Program Library) tokens:

Nativo: SOL. Tokens SPL: USDC, USDT, JUP (Jupiter), BONK, RAY (Raydium), ORCA, JTO (Jito), PYTH (Pyth Network), W (Wormhole), RENDER, WIF (dogwifhat), mSOL (Marinade Staked SOL), jitoSOL (Jito Staked SOL).

3.4. Tron Tokens (TRC-20)

On the Tron network, the CIE verifies the native TRX balance and 9 TRC-20 tokens:

Nativo: TRX. Tokens TRC-20: USDT, USDC, USDD, TUSD, WTRX, BTT (BitTorrent), JST (JUST), SUN, WIN (WINKLink).

4. ADDRESS DERIVATION

4.1. BIP Standards

The CIE implements the following industry standards for hierarchical deterministic derivation of keys and addresses:

- BIP39 (Mnemonic Code): Defines the standard for key generation from mnemonic phrases of 12 to 24 words. The CIE supports seeds of 12, 15, 18, 21 and 24 words in all 9 official BIP39 languages.
- BIP32 (HD Wallets): Defines the hierarchical deterministic wallet structure, allowing the derivation of an unlimited number of child keys from a master key.
- BIP44 (Multi-Account): Defines the m/purpose'/coin_type'/account'/change/address_index structure for organizing multiple accounts and coins.
- BIP49 (P2SH-SegWit): Defines the derivation path m/49'/coin_type'/... for compatible SegWit addresses (P2SH-P2WPKH), used in Bitcoin (3...) and Litecoin (M...).
- BIP84 (Native SegWit): Defines the derivation path m/84'/coin_type'/... for Native SegWit addresses (Bech32), used in Bitcoin (bc1q...) and Litecoin (ltc1q...).
- BIP86 (Taproot): Defines the derivation path m/86'/coin_type'/... for Taproot addresses (P2TR), the most recent Bitcoin format (bc1p...).

4.2. Ed25519 (Solana, TON, Stellar, Sui and Near)

For networks that use the Ed25519 signature algorithm (Edwards 25519 elliptic curve), such as Solana, TON, Stellar, Sui and Near, the CIE implements SLIP-0010 derivation, which adapts BIP32 for non-secp256k1 curves. The 32-byte private key is derived via HMAC-SHA512 from the seed, and the public key is calculated using scalar multiplication on the Ed25519 curve.

4.3. Complete Derivation Paths Table

Network	Format	Derivation Path	Coin Type
Bitcoin	Legacy (1...)	m/44'/0'/0'/0/x	0
Bitcoin	SegWit (3...)	m/49'/0'/0'/0/x	0
Bitcoin	Native SegWit (bc1q...)	m/84'/0'/0'/0/x	0
Bitcoin	Taproot (bc1p...)	m/86'/0'/0'/0/x	0
Bitcoin Cash	CashAddr (bitcoincash:q...)	m/44'/145'/0'/0/x	145
Bitcoin Cash	Legacy (1...)	m/44'/145'/0'/0/x	145
EVM (todas)	Padrão (0x...)	m/44'/60'/0'/0/x	60
Tron	Padrão (T...)	m/44'/195'/0'/0/x	195
Solana	Ed25519 (Base58)	m/44'/501'/0'/0'	501
Litecoin	Legacy (L...)	m/44'/2'/0'/0/x	2
Litecoin	SegWit (M...)	m/49'/2'/0'/0/x	2
Litecoin	Native SegWit (ltc1q...)	m/84'/2'/0'/0/x	2
Dogecoin	Padrão (D...)	m/44'/3'/0'/0/x	3
TON	Ed25519 (UQ.../EQ...)	m/44'/607'/0'	607
Zcash	Transparente (t1...)	m/44'/133'/0'/0/x	133
XRP (Ripple)	Padrão (r...)	m/44'/144'/0'/0/x	144

Stellar	Ed25519 (G...)	m/44'/148'/0'	148
Algorand	Ed25519 (Base32)	m/44'/283'/0'/0/x	283
Sui	Ed25519 (0x...)	m/44'/784'/0'/0'/0'	784
Near Protocol	Ed25519 (hex)	m/44'/397'/0'	397
Liquid Network	Bech32 (ex1...)	m/44'/1776'/0'/0/x	1776
Bitcoin (Electrum Standard)	P2PKH (1...)	m/0/x	-
Bitcoin (Electrum Segwit)	P2WPKH (bc1q...)	m/0'/0/x	-
Litecoin (Electrum Standard)	P2PKH (L...)	m/0/x	-
Litecoin (Electrum Segwit)	P2WPKH (ltc1q...)	m/0'/0/x	-

5. APIs AND DATA SOURCES

5.1. APIs Used per Network

The CIE uses multiple public and third-party APIs to query balances and transaction history. The system implements an API pool with automatic failover, ensuring high availability even when an API is temporarily unavailable or rate-limited.

Network	APIs Used	Type
EVM (todas)	Etherscan, BscScan, PolygonScan, Arbiscan, Snowtrace, etc.	REST API + JSON-RPC
Bitcoin	Blockstream.info, Blockchain.info, Mempool.space	REST API
Bitcoin Cash	Blockchain.info/bch, Bitcoin.com REST	REST API
Litecoin	Blockchair, Litecoinspace	REST API
Dogecoin	Blockchair, DogeChain	REST API
Tron	TronGrid, TronScan	REST API
Solana	Solana RPC (mainnet-beta)	JSON-RPC
TON	Toncenter.com	REST API
Zcash	Blockchair	REST API
XRP (Ripple)	XRPL Cluster (xrplcluster.com)	JSON-RPC
Stellar (XLM)	Horizon API (horizon.stellar.org)	REST API
Algorand (ALGO)	Algonode (algonode.cloud)	REST API
Sui (SUI)	Sui Fullnode RPC, BlastAPI	JSON-RPC
Near Protocol	NEAR RPC (rpc.mainnet.near.org), Lava	JSON-RPC
Liquid Network	Blockstream.info/liquid/api	REST API

5.2. API Pool System and Rate Limiting

To avoid blocks due to excessive requests, the CIE implements an intelligent API management system with the following features:

- Rotating Pool: Multiple APIs are configured for each network, and the system automatically alternates between them.
- Rate Limiting: Each API has a configurable requests-per-second limit, and the system automatically waits when the limit is reached.
- Automatic Failover: If an API returns an error or timeout, the system automatically tries the next API in the pool.
- Optional API Keys: The user can configure paid API keys (Alchemy and TronGrid) to significantly increase request limits and scanning speed. If the paid API fails during use (credits exhausted, timeout, etc.), the program automatically continues using free public APIs without interruption.

6. SYSTEM REQUIREMENTS

Requirement	Minimum	Recommended
Operating System	Windows 10 (64-bit)	Windows 11 (64-bit)
Processor	Intel Core i3 / AMD Ryzen 3	Intel Core i5+ / AMD Ryzen 5+
RAM	4 GB	8 GB or more
Disk Space	100 MB free	500 MB free
Internet Connection	Required for API queries and license verification	Stable broadband
Software	Go 1.18+	Go 1.21+ (latest version)

7. INSTALLATION AND COMPILATION

7.1. Prerequisites

Before compiling the Crypto Hunter Pro - CIE, make sure that Go (Golang) is installed on your system. Go can be downloaded for free at <https://go.dev/dl/>. After installation, verify that Go is accessible from the terminal by running the command 'go version'.

7.2. Compilation Process

The compilation process has been simplified through the compilador.bat script included in the distribution package:

- Step 1: Extract the Crypto Hunter Pro ZIP file to a folder of your choice.
- Step 2: Navigate to the extracted project folder.
- Step 3: Double-click the compilador.bat file.
- Step 4: The script will display a menu with two license options: [1] Lifetime (no expiration) or [2] With expiration date. If you choose option 2, you will be asked for the number of days of validity. Then, the script will download dependencies, compile the source code and generate executables for x64 and x86.
- Step 5: Wait for the 'SUCCESS!' message indicating that compilation has been completed successfully.

After compilation, the executables will be available in the same folder. For lifetime versions: `crypto_hunter_pro_x64.exe` and `crypto_hunter_pro_x86.exe`. For versions with expiration: `crypto_hunter_pro_x64_Expires_in_YYYYMMDD.exe` and `crypto_hunter_pro_x86_Expires_in_YYYYMMDD.exe`.

8. COMPLETE USAGE GUIDE

8.1. Initial Screen and Language Selection

When starting the program, the first screen displays the ASCII logo of Crypto Hunter Pro and requests the interface language selection. The user can choose between Portuguese (PT-BR) and English (EN). All menus have input validation: if the user types an invalid option, the program displays an error message and asks again until a valid option is entered. All messages, menus and instructions will be displayed in the selected language.

8.2. Main Menu

The main menu offers the following options:

- 1. Enter seed phrase manually: To scan a single seed phrase entered via keyboard.
- 2. Import Excel files from Unmixer Seed: To scan multiple seeds imported from .xlsx files generated by the Unmixer Seed Search module.
- Before the main menu, the program displays the API Configuration menu, where the user can choose to continue with free public APIs or configure paid API keys (Alchemy and/or TronGrid) for greater speed.
- 0. Exit: Closes the program.

8.3. Manual Seed Phrase Input

When selecting option 1, the program asks the user to enter the complete seed phrase (12 to 24 words separated by spaces). The program automatically validates each word against the BIP39 dictionary and verifies the seed checksum. If any word is invalid, the program suggests the closest word from the dictionary.

8.4. Excel File Import (Unmixer Seed)

When selecting option 2, the program asks for the path to the .xlsx file generated by the Unmixer Seed Search. The CIE automatically reads all valid seed phrases from the file and adds them to the scanning queue. This functionality allows batch processing of hundreds or thousands of seeds in an automated manner.

8.5. API Key Configuration

Before the main menu, the program displays the API Configuration menu with two options: [1] Continue with free public APIs (default) or [2] Configure API keys (paid). The program works perfectly with free public APIs. However, for large-scale searches (thousands of seeds over consecutive days), the user can configure paid API keys for greater speed and without rate-limit interruptions. Supported paid APIs are:

Service	Network	How to Obtain
Alchemy (Recomendada)	16 EVM networks + Solana	Register at alchemy.com/pricing and generate an API key

TronGrid	Tron (TRX + TRC-20)	Register at trongrid.io and generate an API key
----------	---------------------	---

Alchemy covers: Ethereum, BSC, Polygon, Arbitrum, Avalanche, Optimism, Base, Linea, Scroll, Gnosis, zkSync, Blast, Celo, Berachain, Sonic, Mantle and Solana. Networks not covered by Alchemy (Cronos, Flare, Bitcoin, Bitcoin Cash, Tron, Litecoin, Dogecoin, TON, Zcash, XRP, Stellar, Algorand, Sui, Near and Liquid Network) automatically use free public APIs.

TronGrid covers: Tron (TRX + all TRC-20 tokens). All other networks automatically use free public APIs.

IMPORTANT: The user can configure 1 or both APIs. If a paid API fails during scanning (credits exhausted, timeout, connection error, etc.), the program automatically detects this and continues the search using free public APIs, without interruption and without loss of results.

8.6. Network Selection

After entering the seed phrase, the program displays the list of 14 available network groups. The user can select individual networks (e.g., 1,3,5), a range (e.g., 1-5) or all networks (by typing 'all'). Only selected networks will be scanned, saving time when the user knows which networks to search.

8.7. Derivation Configuration (BTC/BCH/LTC)

For networks with multiple address formats (Bitcoin, Bitcoin Cash and Litecoin), the program displays an additional submenu allowing the selection of desired formats. For example, for Bitcoin, the user can choose between Legacy (1...), SegWit (3...), Native SegWit (bc1q...) and Taproot (bc1p...), or select all.

8.8. Index Range

The program asks for the derivation index range to be verified. The default is 0-20 (21 addresses per derivation). For broader searches, the user can increase the range (e.g., 0-100 or 0-500). Larger ranges increase scanning time but also the chances of finding addresses used at higher indices. The program validates the entered range: if the final index is less than the initial one (e.g., 3000-2900), an error message is displayed and the program asks again until a valid range is entered.

8.9. Optional Passphrase (BIP39)

BIP39 allows the addition of an optional passphrase (also called the '25th word') to the seed phrase. If the user used a passphrase when creating the original wallet, it must be entered here for the derived addresses to be correct. Otherwise, just leave it blank.

8.10. Real-Time Scanning

During scanning, the program displays in real-time each address being verified, with the status of each query:

- [empty] - Address with no balance and no transaction history.
- [BALANCE: X.XX SYMBOL] - Address with current balance found.
- [HISTORY: N tx] - Address with no current balance, but with transaction history.
- [ERROR: message] - API query error (timeout, rate limit, etc.).
- [duplicate - same address] - Address already verified in another derivation (e.g., BCH CashAddr vs Legacy).

The complete seed phrase is displayed without truncation, and each address is shown in full, facilitating visual verification.

8.11. Results and Excel Report

At the end of scanning, the program displays a summary with total time, number of addresses verified, addresses with balance and addresses with history. If any results were found, an Excel file is automatically generated with the name in the format 'Relatorio_Saldos_YYYYMMDD_HHMMSS.xlsx'.

9. EXCEL REPORTS

Reports are generated in .xlsx (Microsoft Excel) format and contain 3 organized tabs to facilitate results analysis.

9.1. Summary Tab

The 'Summary' tab contains ALL addresses found with balance or history, regardless of type. This is the consolidated view of all scan results.

9.2. With Balance Tab

The 'With Balance' tab contains only addresses that have current balance (native or in tokens). These are addresses with immediately recoverable funds.

9.3. With History Tab

The 'With History' tab contains addresses that have transaction history but do NOT have current balance. These addresses indicate that the wallet has been used, but funds have been moved.

9.4. Detailed Columns

Column	Description
Network	Blockchain network name (e.g., Ethereum, BSC, Bitcoin)
Derivation	Derivation path used (e.g., m/44'/60'/0'/0/0)
Index	Address derivation index
Address	Complete wallet address
Private Key	Corresponding private key (hex or WIF)
Native Balance	Network native token balance
Symbol	Native token symbol (ETH, BNB, SOL, etc.)
Tokens	List of tokens found with balances
Transaction Count	Total number of address transactions
Last Activity Date	Date of last recorded transaction
Seed Phrase	Source seed phrase of the address

10. LICENSE SYSTEM AND ANTI-BYPASS PROTECTION

The Crypto Hunter Pro - CIE includes a real-time license verification system, designed to control the software usage period in versions with expiration dates. Lifetime versions have no verification and work indefinitely.

10.1. License Types

The compilador.bat allows generating two types of executable:

Lifetime: The executable has no expiration date and works indefinitely. No license verification is performed when starting the program. Executables are named `crypto_hunter_pro_x64.exe` and `crypto_hunter_pro_x86.exe`.

With Expiration: The executable has a functioning deadline embedded in the binary at compilation time. At startup, the program verifies the real time via internet and blocks access if the license has expired. Executables are named `crypto_hunter_pro_x64_Expires_in_YYYYMMDD.exe` and `crypto_hunter_pro_x86_Expires_in_YYYYMMDD.exe`.

10.2. Anti-Bypass Time Verification

The verification system uses three layers of protection to prevent system clock manipulation:

Layer 1 - NTP via Direct IP: The program queries 8 NTP servers (Google, Cloudflare, NIST, Apple) using their direct IP addresses instead of domain names. This prevents the Windows hosts file from being used to redirect NTP queries to a fake server.

Layer 2 - Cross Validation: The program collects time from multiple independent sources and compares results. If there is a divergence greater than 2 minutes between any two sources, the program detects manipulation and displays the message 'Time manipulation detected!' blocking execution.

Layer 3 - HTTPS as Backup: In addition to the NTP protocol, the program performs HTTPS requests to reliable servers (Google, Cloudflare, Microsoft) and extracts the time from the HTTP Date header. Since the HTTPS connection is protected by SSL certificate, it is virtually impossible to falsify the response without possessing the server's private certificate.

The program uses the median of collected times for greater precision and resistance to outliers.

10.3. Behavior in Different Scenarios

Valid license: The program displays remaining days and continues execution normally.

Expired license: The program displays the expiration date, the current date verified via NTP/HTTPS and a message requesting contact with the team for renewal. The program does not allow execution.

No internet connection: The program cannot verify the license and displays a message requesting the user to check their connection. The program does not allow execution without verification.

Manipulation detected: If time sources diverge significantly, the program detects the bypass attempt and blocks execution with a specific warning message.

11. SECURITY AND BEST PRACTICES

Security is a fundamental concern when working with seed phrases and private keys. The Crypto Hunter Pro - CIE was designed with security in mind, but the user should also follow best practices to protect their data.

Security Recommendations:

- Isolated Environment: Whenever possible, run the CIE on a dedicated computer, without internet connection during result handling. The connection is only needed during scanning to query the APIs.
- Result Protection: Treat the generated Excel files with the same level of security as you would treat the seed phrases themselves. They contain private keys that grant direct access to funds.
- Post-Recovery: After finding a wallet with balance, immediately move the funds to a new secure wallet and securely delete all result files (using secure deletion tools).
- Antivirus and Malware: Make sure the computer is free of malware, keyloggers and other malicious software before running the CIE.
- Secure Backup: If you need to keep the results, store them on encrypted media (e.g., VeraCrypt) and in a secure location.

12. FREQUENTLY ASKED QUESTIONS (FAQ)

Q: Does the program need internet to work?

A: Yes, the CIE requires an internet connection to query blockchain APIs and verify balances. Without internet, address derivation works, but balance verification is not possible.

Q: Does the program send my seed phrases to any server?

A: No. Seed phrases are processed locally. API queries only send derived addresses (public), never private keys or seed phrases.

Q: Can I scan 12 and 24-word seeds?

A: Yes, the CIE supports seeds of 12, 15, 18, 21 and 24 words, according to the BIP39 standard.

Q: Why does scanning take long?

A: The time depends on the number of selected networks, the index range and the API speed. Free APIs have request limits that can cause delays. Configuring paid API keys (Alchemy and/or TronGrid) can significantly speed up the process, especially for large-scale searches.

Q: What does 'With History' mean in the report?

A: It means the address has received or sent transactions in the past, but currently has no balance. This indicates that the wallet was used and the funds were moved.

Q: Can I use the CIE together with the Unmixer Seed Search?

A: Yes! The ideal flow is: (1) use the Unmixer to recover lost seeds, (2) export results to Excel, (3) import the Excel into the CIE to verify balances across all networks.

Q: What happens when the license expires?

A: The program displays a message informing the expiration date and the current date verified via NTP/HTTPS, and requests the user to contact the Crypto Hunter Pro team for renewal. The program does not allow execution while the license is expired.

Q: Is it possible to bypass the license verification by changing the system clock?

A: No. The system uses three layers of protection: NTP via direct IP (immune to hosts file), cross-validation between multiple sources (detects fake NTP) and HTTPS as backup (protected by SSL certificate). Any manipulation attempt is detected and the program blocks execution.

13. CONCLUSION

The Crypto Hunter Pro - CIE is a powerful and indispensable tool for anyone managing multiple digital assets. By automating the complex task of verifying thousands of addresses across dozens of blockchains, the software not only saves valuable time, but also exponentially increases the chances of recovering funds that could be considered lost forever.

With support for 32 blockchain networks, 170+ tokens, multiple derivation formats and detailed Excel reports, the CIE offers the most comprehensive coverage on the market for cryptocurrency wallet recovery and auditing. The native integration with the Unmixer Seed Search module creates a complete recovery ecosystem, from seed phrase reconstruction to balance verification across all supported networks.

Crypto Hunter Pro Team

August / 2026

14. NEW FEATURES (v2.0 - Inspired by BTCRecover)

14.1. Automatic Multi-Derivation Paths

The CIE now offers the option to automatically test ALL derivation paths for networks that have multiple address formats (BTC, LTC, BCH). Inspired by BTCRecover, which tests multiple paths by default, this feature significantly increases the chance of finding funds that may be in any address format.

How It Works:

When the user selects networks that have multiple derivation paths (BTC, LTC or BCH), the program presents a new screen asking:

[1] Yes - Test ALL paths for each network (recommended)

[2] No - Manually choose which paths to test

If the user chooses option 1, all derivation paths are automatically enabled and the individual derivation selection screen is skipped, streamlining the process.

Automatically Tested Paths:

BTC: Legacy (m/44'/0'/0'/0'/0/x) + SegWit (m/49'/0'/0'/0'/0/x) + Native SegWit (m/84'/0'/0'/0'/0/x) + Taproot (m/86'/0'/0'/0'/0/x)

LTC: Legacy (m/44'/2'/0'/0'/0/x) + SegWit (m/49'/2'/0'/0'/0/x) + Native SegWit (m/84'/2'/0'/0'/0/x)

BCH: CashAddr (m/44'/145'/0'/0'/0/x) + Legacy (m/44'/145'/0'/0'/0/x)

When to Use:

This feature is especially useful when you don't know in which type of wallet the funds were originally stored. For example, if you used an old wallet that generated Legacy addresses (1...) but now use a modern wallet that generates Native SegWit addresses (bc1q...), the Multi-Derivation mode ensures that both formats will be verified automatically.

14.2. Integration with Unmixer Seed Search (Pipeline)

The CIE now has enhanced integration with the Unmixer Seed Search module. After the Unmixer generates valid seeds in Excel files, the user can import them directly into the CIE for automatic balance verification across multiple blockchains.

Integrated Workflow:

1. Run the Unmixer Seed Search and generate valid seeds (Excel files)
2. Copy the Excel files to the CIE 'Importar_Seeds' folder
3. In the CIE, select the 'Import Excel from Unmixer Seed' option
4. The CIE will automatically test the balance of each seed across 32 networks
5. Results with balance or history are saved in a detailed Excel report

This pipeline eliminates the need to manually test each seed in different wallets, fully automating the fund verification process.