Lambda Script Cheatsheet

August 2025 - v1.0

CLI Commands

```
lambda                    # Start REPL
// REPL Commands: :quit, :help, :clear
lambda script.ls          # Run script
lambda --transpile-only script.ls # Transpile only
lambda --help             # Show help
```

Validation:

```
lambda validate file.json -s schema.ls  # With schema
lambda validate file.json             # Default schema
```

Type System

Scalar Types:

```
null  bool  int  float  decimal
string  symbol  binary  datetime
```

Container Types:

```
1 to 10           // Range
[int]             // Array of integers
(int, string)     // List/tuple
{key: string}     // Map
<tag attr: int>   // Element
```

Type Operators:

```
int | string     // Union type
int & number     // Intersection
int?             // Optional (int | null)
int*             // Zero or more
int+             // One or more
(a: int, b: string) => bool   // Function Type
```

Literals

Numbers:

```
42        // Integer
3.14      // Float
1.5e-10   // Scientific notation
123.45n   // Decimal (arbitrary precision)
inf  nan  // Special values
```

Strings & Symbols:

```
"hello"           // String
"multi-line       // Multi-line string
string"
'symbol           // Symbol
```

Binary & DateTime:

```
b'\xDEADBEEF'     // Hex binary
b'\64QUVGRw=='    // Base64 binary
t'2025-01-01'     // Date
t'14:30:00'       // Time
t'2025-01-01T14:30:00Z'  // DateTime
```

Collections:

```
[1, 2, 3]         // Array
(1, "two", 3.0)   // List
{a: 1, b: 2}      // Map
<div id: "main">  // Element
```

Variables & Declarations

Let Expressions:

```
(let x = 5, x + 1, x * 2)      // Single binding
(let a = 1, let b = 2, a + b)  // Multiple bindings
```

Let Statements:

```
let x = 42;               // Variable declaration
let y : int = 100;        // With type annotation
let a = 1, b = 2;         // Multiple variables
```

Public Declarations:

```
pub PI = 3.14159;         // Export variable
pub fn square(x) => x * x; // Export function
```

Operators

Arithmetic: addition, subtraction, multiplication, division, integer division, modulo, exponentiation

```
+  -  *  /  _/  %  ^
```

Comparison: equal, not equal, less than, less equal, greater than, greater equal

```
==  !=  <  <=  >  >=
```

Logical: logical and, or, not

```
and  or  not
```

Type & Set: type check, membership, range, union, intersection, exclusion

```
is  in  to  |  &  !
```

Control Flow

If Expressions (require else):

```
if (x > 0) "positive" else "non-positive"
if (score >= 90) "A"
else if (score >= 80) "B" else "C"
```

If Statements (optional else):

```
if (x > 0) { "positive" }
if (condition) { something() } else { otherThing() }
```

For Expressions:

```
for (x in [1, 2, 3]) x * 2     // Array iteration
for (i in 1 to 5) i * i        // Range iteration
for (x in data) if (x > 0) x else 0  // Conditional
```

For Statements:

```
for item in collection { transform(item) }
```

Functions

Function Declaration:

```
// Function with statement body
fn add(a: int, b: int) -> int { a + b }
// Function  with expression body
fn multiply(x: int, y: int) => x * y
// Anonymous function
let square = (x) => x * x;
```

Function Calls:

```
add(5, 3)         // Function call
```

System Functions

Type Conversion:

```
int("42")         // String to int
float("3.14")     // String to float
string(42)        // Value to string
symbol("text")    // String to symbol
```

Type Inspection:

```
type(value)       // Get type of value
len(collection)   // Get length
```

Math Functions:

```
abs(x)            // Absolute value
min(a, b, c)      // Minimum value
max(a, b, c)      // Maximum value
sum([1, 2, 3])    // Sum of array
avg([1, 2, 3])    // Average of array
round(x)  floor(x)  ceil(x)  // Rounding
```

Date/Time Functions:

```
datetime()        // Current date/time
today()           // Current date
justnow()         // Current time
date(dt)          // Extract date part
time(dt)          // Extract time part
```

Collection Functions:

```
slice(arr, start, end)    // Array slice
set(arr)                  // Remove duplicates
all([true, false])        // All true?
any([false, true])        // Any true?
```

I/O Functions:

```
input(file, format)       // Parse file
print(value)              // Print to console
format(data, type)        // Format output
error(message)            // Create error
```

Input/Output Formats

Supported Input Types: `json`, `xml`, `yaml`, `markdown`, `csv`, `html`, `latex`, `toml`, `rtf`, `css`, `ini`, `math`, `pdf`

```
input("path/file.md", 'markdown')   // Input Markdown
```

Input with Flavors: e.g. math flavors: `latex`, `typst`, `ascii`

```
input("math.txt", {'type':'math', 'flavor':'ascii'})
```

Output Formatting: `json`, `yaml`, `xml`, `html`, `markdown`

```
format(data, 'yaml')                // Format as YAML
```

Modules & Imports

Import Syntax:

```
import module_name;               // Basic import
import .relative_module;          // Relative import
import alias: module_name;        // Import with alias
import mod1, mod2, alias: mod3;   // Multiple imports
```

Module Usage Example:

```
// In math_utils.ls:
pub PI = 3.14159;
pub fn square(x) => x * x;

// In main.ls:
import math: .math_utils;
let area = math.PI * math.square(radius);
```

Error Handling

Creating Errors:

```
error("Something went wrong")   // Create error value
```

Error Checking:

```
let result = risky_operation();
if (result is error) { print("Error:", result) }
else { print("Success:", result) }
```

Advanced Features

Type Declarations:

```
type User = {name: string, age: int};   // Object type
type Point = (float, float);            // Tuple type
type Result = int | error;              // Union type
```

Comprehensions - Complex data processing:

```
(let data = [1, 2, 3, 4, 5],
 let filtered = (for (x in data)
   if (x % 2 == 0) x else 0),
 let doubled = (for (x in filtered) x * 2), doubled)
```

Operator Precedence (High to Low)

1. `() [] .` - Primary expressions
2. `- + not` - Unary operators
3. `^` - Exponentiation
4. `* / _/ %` - Multiplicative
5. `+ -` - Additive
6. `< <= > >=` - Relational
7. `== !=` - Equality
8. `and` - Logical AND
9. `or` - Logical OR
10. `to` - Range
11. `| & !` - Set operations
12. `is in` - Type operations

Quick Examples

Data Processing:

```
let data = input("sales.json", 'json')
let total = sum(
  (for (sale in data.sales) sale.amount))
let report = {total: total,
  count: len(data.sales)}
format(report, 'json')
```

Function Definition:

```
fn factorial(n: int) -> int {
    if (n <= 1) 1 else n * factorial(n - 1)
}
```

Element Creation:

```
let article = <article title:"My Article"
    <h1 "Introduction">
    <p "Content goes here.">
>
format(article, 'html')
```