

COSC 444/544 - Computer Vision

Project Part I, Research Notes

January 27, 2025

Research Papers

1. Riley Eaton

- 1.1. *Visual Object Tracking using Adaptive Correlation Filters*
- 1.2. *Online Object Tracking: A Benchmark*

2. Wanju Luo

- 2.1. *Paper #1 Name*
- 2.2. *Paper #2 Name*

3. Dichen Feng

- 3.1. *Moving Object Tracking and Detection in Videos using MATLAB: A Review*
- 3.2. *Robust visual tracking method based on Harris Hawks algorithm*

4. Henry Pak

- 4.1. *Paper #1 Name*
- 4.2. *Paper #2 Name*

5. Santam

- 5.1. *Paper #1 Name*
- 5.2. *Paper #2 Name*

Research Summary

The following are summaries of the papers selected by each group member.

1.1 *Visual Object Tracking using Adaptive Correlation Filters*

Reviewer: Riley Eaton

Summary:

Key Points & Concepts:

- **Template matching** is one of the simplest object tracking approaches. A single patch of an image, called a *template*, is chosen. Then, in each new frame the template is slid across the entire image and a similarity measure is computed at each location. Whatever position has the highest similarity score is the new estimated position of the object.
- **Convolution** involves flipping the kernel (or filter) and sliding it across the image. The dot product of the kernel and the image is computed at each location. This is similar to the similarity measure in template matching.

- **Correlation** by contrast does not flip the filter, and is usually used to measure similarity between images or image patches. This can be used to find how closely a test patch in a new frame matches a template patch from a previous frame.
- **Frequency Domain Computations** are used to speed up the computation of the correlation between the filter and the image. A Fast Fourier Transform (FFT) is used to convert the image and filter into the frequency domain, where some computation is performed. The inverse FFT (iFFT) is then used to convert the result back to the spatial domain. This is computationally more efficient than the spatial domain computation, and speeds up matching for high frame rate applications.
- **MOSSE** stands for the Minimum Output Sum of Squared Error. It's a method for training a filter to track an object. The filter is trained on a single frame, and then used to track the object in subsequent frames. The filter is updated at each frame to account for changes in the object's appearance. It's trained by computing the FFT of the image and the FFT of the desired output, and then dividing the two to get the filter. The filter is then updated at each frame by computing the FFT of the image, multiplying it by the filter, and then computing the iFFT to get the output. The filter is then updated by comparing the output to the desired output, and adjusting the filter to minimize the error. And as noted in the paper, "despite the simplicity of the approach, tracking based on [modifications of this filter] perform well under changes in rotation, scale, lighting, and partial occlusion."

1.2 *Online Object Tracking: A Benchmark*

Reviewer: Riley Eaton

Summary:

Key Points & Concepts:

- **Point** Description

2.1 *Paper Name*

Reviewer: Wanju Luo

Summary:

Key Points & Concepts:

- **Point** Description

2.2 *Paper Name*

Reviewer: Wanju Luo

Summary:

Key Points & Concepts:

- **Point** Description

3.1 *Moving Object Tracking and Detection in Videos using MATLAB: A Review*

Reviewer: Dichen Feng

Summary: This paper implemented a single object tracking system using MATLAB which focusing on handling the poor light conditions and occlusions.

Key Points & Concepts:

- **Color Recognition:** Use RGB and HSV color space to process video frames. HSV model is very effective on handling lighting variations.
- **Noise Reduction:** Uses a median filter to remove noise from images.
- **Approximate Median Filter:** Extract moving object from video.
- **Kalman Filter:** Predicts and refines the position of the moving object in frames.
- **Dynamic Template Matching:** Adjust the object template if its shape changes during tracking.

3.2 Paper Name

Reviewer: Dichen Feng

Summary: The Harris Hawks Optimization (HHO) algorithm is a nature-inspired metaheuristic that mimics the cooperative hunting strategy of Harris hawks to solve optimization problems by dynamically switching between exploration and exploitation phases.

Key Points & Concepts:

- **Harris Hawks Optimization (HHO):** Inspired by the cooperative hunting strategies of Harris hawks.
 - **Exploration Phase:** Hawks search randomly for the target.
 - **Transition Phase:** Adjusts strategy based on the target's energy and location.
 - **Exploitation Phase:** Hawks converge on the prey's position through coordinated movements.
- **Object Representation:** Uses color-weighted histogram in the HSV color space to describe the object's appearance. Also uses the Bhattacharyya distance for matching the object between frames.
- **Tracking Process:** Target initialized in the first frame using a bounding box. Then the color-weighted histogram of the object is computed as a feature descriptor in the HSV color space to make the algorithm less sensitive to lighting changes.
- **Pseudo Code:**
 - 1. Initialize the position of N Hawks.
 - 2. While $i < IterMax$, do:
 - 3. Evaluate fitness values of N Hawks.
 - 4. Set P_{rabbit} as the best position of the rabbit from the best fitness value.
 - 5. For $j = 1$ to N , do:
 - 6. Update E , E_0 , and J using Eq. (2).
 - 7. Update E using Eq. (3).
 - 8. If $|E| \geq 1$, update Hawks position using Eq. (1).
 - 9. If $|E| < 1$, then:
 - 10. If $|E| \geq 0.5$ and $r \geq 0.5$, update Hawks position using Eq. (3).
 - 11. Else if $|E| < 0.5$ and $r \geq 0.5$, update Hawks position using Eq. (5).
 - 12. Else if $|E| \geq 0.5$ and $r < 0.5$, update Hawks position using Eq. (8).
 - 13. Else if $|E| < 0.5$ and $r < 0.5$, update Hawks position using Eq. (9).
 - 14. Return P_{rabbit} .

4.1 *Paper Name*

Reviewer: Henry Pak

Summary:

Key Points & Concepts:

- **Point** Description

4.1 *Recent advances of single-object tracking methods: A brief survey*

Reviewer: Henry Pak

Summary: Published in 2021, this paper is a survey providing an overview of the advancements in single-object tracking methods. It focuses on the past decades progress, especially in algorithms based on **correlation filters** and **deep learning**, which have significantly improved the performance of object trackers.

Key Points & Concepts:

- **Categorization of Methods:** It categorizes single-object tracking algorithms into correlation filters-based and deep learning-based methods, also discussing earlier methods such as optical flow, filter methods, and kernel-based methods.
- **Performance Comparison:** It compares the performance of algorithms on OTB2015, VOT2016, and LaSOT datasets based on speed, accuracy, and robustness.
- **Classification of Deep Learning Methods:** It classifies deep learning methods into those based on feature extraction and those that are end-to-end methods.

4.2 *Paper Name*

Reviewer: Henry Pak

Summary:

Key Points & Concepts:

- **Point** Description

5.1 *Paper Name*

Reviewer: Santam

Summary:

Key Points & Concepts:

- **Point** Description

5.2 *Paper Name*

Reviewer: Santam

Summary:

Key Points & Concepts:

- **Point** Description