2026 [redacted]

10kV-35kV[redacted]([redacted]/[redacted])[redacted]/ABB[redacted]

Company: Shenyang Feichi Electrical Equipment Co., Ltd.
Headquarters & Manufacturing Plant: 63,000 m² Modernized Industrial Base, Shenyang High-Tech Zone, Liaoning, China.
Certifications & Licenses: ISO 9001:2015, ISO 14001:2015, ISO 45001:2018, IEC 62271-202, [redacted] 14695-80, Schneider Electric Blokset Official License, ABB UniSafe / MDmax Official Strategic License, Ex d I Mb Mining Explosion-Proof.
Global Track Record: 80+ Major Power Grid & Heavy Industrial Projects Across 40+ Countries.

1. 10kV–35kV Prefabricated Compact Box-Type Substations (2[redacted] / [redacted])

Engineered to IEC 62271-202 and [redacted] 14695-80. Packaged outdoor substation integrating medium-voltage switchgear, hermetic/cast resin transformer (50kVA-3150kVA), and low-voltage distribution boards. Options for -60°C Siberian Arctic permafrost operation (100mm PU insulation + automated PTC heating).

Model / Type	Rated Voltage	Capacity Range	Enclosure & Climate Protection
YB-10/0.4 European	10 kV / 0.4 kV	50 - 2500 kVA	IP54 / Composite / Landscape Style
ZGS-35/0.4 Pad-Mount	35 kV / 0.4 kV	200 - 3150 kVA	Dead-front, compact oil-submerged switch
2[redacted]-35/10 Arctic	35 kV / 10 kV / 0.4 kV	630 - 2500 kVA	09[redacted]2[redacted] Cor-Ten steel, -60°C [redacted]1, 100mm PU
Solar PV Skid 35kV	35 kV / 0.8 kV	1000 - 3150 kVA	1500V Inverter Integration, C5-M Anti-Corrosion

2. MV/LV Switchgear & Official Schneider / ABB Authorized Panels

Four-compartment segregated metal-clad switchgear assemblies with 5-prevention mechanical interlocking, IAC AFLR 31.5kA internal arc classification, and ultrafast optical arc protection (<7ms).

Equipment Type	Standard / License	Rated Ratings	Key Features & Protection
KYN28A-12 Switchgear	IEC 62271-200 / GB	12 kV / 4000A / 31.5kA	LSC2B-PM, withdrawable VS1/VD4 cassette
Schneider Blokset LV	Schneider Official Lic.	0.4-0.69 kV / Up to 6300A	Form 4b segregation, MCC draw-out, Smart SCADA
ABB UniSafe MV Panel	ABB Authorized Lic.	12-24 kV / 4000A / 31.5kA	Air-insulated, VD4 circuit breaker, AFLR arc safe
ABB MDmax Digital LV	ABB Strategic Partner	0.4 kV / Up to 6300A	Wireless busbar temp monitoring, cloud diagnostics

3. Power Transformers (Cast Resin Dry-Type & Hermetic Oil)

Vacuum quartz-sand thin-insulation epoxy casting plant guaranteeing partial discharge < 5pC (Nomex Class H 180°C), and corrugated hermetically sealed oil transformers (S13-S22).

Series / Standard	Type	Rated Capacity	Performance & Guarantee
SCB14 / SCB18 Dry	Epoxy Cast Resin	50 - 3150 kVA	Partial discharge < 5pC, Grade-1/2 Efficiency
■■■ / S13-S22 Oil	Hermetic Corrugated	30 - 2500 kVA	Zero moisture ingress, 30+ yr maintenance-free
Mining KBSGZY	Flameproof Dry	100 - 1600 kVA	Ex d I Mb certified, underground mobile skid

4. FC-N2 Smart Mining & Industrial PSA Nitrogen Systems

Proprietary Pressure Swing Adsorption (PSA) nitrogen generators for underground coal mine inerting (MT/T 750 / Ex d I Mb) and petrochemical pipeline purging.

Model Series	Flow Capacity	N2 Purity	Safety & Application
FC-N2 Mining Mobile	100 - 2500 Nm³/h	95% - 99.0%	Ex d I Mb explosion-proof, goaf fire suppression
FC-N2 Industrial Skid	50 - 1500 Nm³/h	99.0% - 99.999%	Petrochemical purging, metallurgical laser cutting

24H SLD REVIEW & TENDER DOSSIER

GLOBAL ENGINEERING CONTACT & INQUIRIES

Technical Director: Henry | **Email:** henry@feichipower.com
Tel / WhatsApp / Telegram: +86 155 6620 6930 | **Official Portal:** https://feichipower.com