2026■ ■■■■

■■■■

Vacuum quartz-sand thin-insulation epoxy casting plant guaranteeing partial discharge < 5pC (Nomex Class H 180°C), and corrugated hermetically sealed oil transformers (S13-S22).

Series / Standard	Type	Rated Capacity	Performance & Guarantee
SCB14 / SCB18 Dry	Epoxy Cast Resin	50 - 3150 kVA	Partial discharge < 5pC, Grade-1/2 Efficiency
■■■ / S13-S22 Oil	Hermetic Corrugated	30 - 2500 kVA	Zero moisture ingress, 30+ yr maintenance-free
Mining KBSGZY	Flameproof Dry	100 - 1600 kVA	Ex d I Mb certified, underground mobile skid

4. FC-N2 Smart Mining & Industrial PSA Nitrogen Systems

Proprietary Pressure Swing Adsorption (PSA) nitrogen generators for underground coal mine inerting (MT/T 750 / Ex d I Mb) and petrochemical pipeline purging.

Model Series	Flow Capacity	N2 Purity	Safety & Application
FC-N2 Mining Mobile	100 - 2500 Nm³/h	95% - 99.0%	Ex d I Mb explosion-proof, goaf fire suppression
FC-N2 Industrial Skid	50 - 1500 Nm³/h	99.0% - 99.999%	Petrochemical purging, metallurgical laser cutting

24H SLD REVIEW & TENDER DOSSIER

GLOBAL ENGINEERING CONTACT & INQUIRIES

Technical Director: Henry | **Email:** henry@feichipower.com
Tel / WhatsApp / Telegram: +86 155 6620 6930 | **Official Portal:** https://feichipower.com