

2925. Maximum Score After Applying Operations on a Tree

[My Submissions \(/contest/weekly-contest-370/problems/maximum-score-after-applying-operations-on-a-tree/submissions/\)](#)

[Back to Contest \(/contest/weekly-contest-370/\)](#)

There is an undirected tree with n nodes labeled from 0 to $n - 1$, and rooted at node 0 . You are given a 2D integer array `edges` of length $n - 1$, where `edges[i] = [ai, bi]` indicates that there is an edge between nodes a_i and b_i in the tree.

You are also given a **0-indexed** integer array `values` of length n , where `values[i]` is the **value** associated with the i^{th} node.

You start with a score of 0 . In one operation, you can:


- Pick any node i .
- Add `values[i]` to your score.
- Set `values[i]` to 0 .

A tree is **healthy** if the sum of values on the path from the root to any leaf node is different than zero.

Return the **maximum score** you can obtain after performing these operations on the tree any number of times so that it remains **healthy**.

User Accepted:	2391
User Tried:	3379
Total Accepted:	2512
Total Submissions:	6653
Difficulty:	Medium

Example 1:




Input: `edges = [[0,1],[0,2],[0,3],[2,4],[4,5]]`, `values = [5,2,5,2,1,1]`

Output: 11

Explanation: We can choose nodes 1, 2, 3, 4, and 5. The value of the root is non-zero. Hence, the sum of values on the path from the root to any leaf node is different than zero. It can be shown that 11 is the maximum score obtainable after any number of operations on the tree.

Example 2:



Input: edges = [[0,1],[0,2],[1,3],[1,4],[2,5],[2,6]], values = [20,10,9,7,4,3,5]

Output: 40

Explanation: We can choose nodes 0, 2, 3, and 4.

- The sum of values on the path from 0 to 4 is equal to 10.
- The sum of values on the path from 0 to 3 is equal to 10.
- The sum of values on the path from 0 to 5 is equal to 3.
- The sum of values on the path from 0 to 6 is equal to 5.

Therefore, the tree is healthy and the score is values[0] + values[2] + values[3] + values[4] = 40.

It can be shown that 40 is the maximum score obtainable after any number of operations on the tree.

Constraints:

- $2 \leq n \leq 2 * 10^4$
- edges.length == n - 1
- edges[i].length == 2
- $0 \leq a_i, b_i < n$
- values.length == n
- $1 \leq values[i] \leq 10^9$
- The input is generated such that edges represents a valid tree.

[Discuss \(https://leetcode.com/problems/maximum-score-after-applying-operations-on-a-tree/discuss/\)](https://leetcode.com/problems/maximum-score-after-applying-operations-on-a-tree/discuss/)

JavaScript



```

1  const initializeGraph = (n) => { let g = []; for (let i = 0; i < n; i++) { g.push([]); } return g; };
2  const packUG = (g, edges) => { for (const [u, v] of edges) { g[u].push(v); g[v].push(u); } };
3  const sm = (a) => a.reduce(((x, y) => x + y), 0);
4
5  let g, vals, res;
6  const maximumScoreAfterOperations = (edges, values) => {
7    let n = values.length;
8    g = initializeGraph(n), vals = values, res = sm(vals);
9    packUG(g, edges);
10   res -= tree_dp(0, -1);
11   return res;
12 };
13
14 const tree_dp = (cur, par) => { // 计算以cur为根的子树是健康时, 失去的最小分数
15   if (cur !== 0 && g[cur].length === 1) return vals[cur]; // cur is leaf, cur !== 0 避免误把根节点当作叶子
16   let subTreeSum = 0; // loss 不选vals[x]
17   for (const child of g[cur]) {
18     if (child !== par) {
19       subTreeSum += tree_dp(child, cur); // 计算以child为根的子树是健康时, 失去的最小分数
20     }
21   }
22   return Math.min(vals[cur], subTreeSum); // 选/不选vals[x], 取最小值
23 };
24
  
```

☐ Custom Testcase

Use Example Testcases

Run

Submit


Submission Result: **Accepted** (/submissions/detail/1097184709/) ?

More Details > (/submissions/detail/1097184709/)

Share your acceptance!

Copyright © 2023 LeetCode

[Help Center \(/support\)](#) | [Jobs \(/jobs\)](#) | [Bug Bounty \(/bugbounty\)](#) | [Online Interview \(/interview/\)](#) | [Students \(/student\)](#) | [Terms \(/terms\)](#) | [Privacy Policy \(/privacy\)](#)

 [United States \(/region\)](#)