



# 5744. Rotating the Box


My Submissions (/contest/biweekly-contest-52/problems/rotating-the-box/submissions/)

Back to Contest (/contest/biweekly-contest-52/)

You are given an m x n matrix of characters box representing a side-view of a box. Each cell of the box is one of the following:

- A stone '#'
- A stationary obstacle '\*'
- Empty '.'


The box is rotated 90 degrees clockwise, causing some of the stones to fall due to gravity. Each stone falls down until it lands on an obstacle, another stone, or the bottom of the box. Gravity does not affect the obstacles' positions, and the inertia from the box's rotation does not affect the stones' horizontal positions.



It is guaranteed that each stone in box rests on an obstacle, another stone, or the bottom of the box.


Return an n x m matrix representing the box after the rotation described above.

### Example 1:




```
Input: box = [["#",".","#"]]
Output: [["."],
         ["#"],
         ["#"]]
```

## Example 2:



```
Input: box = [["#",".","*","."],
               ["#","#","*","."]]
Output: [["#","."],
         ["#","#"],
          ["*","*"],
          [".","."]]
```

### Example 3:



### **Constraints:**

```
m == box.length
n == box[i].length
1 <= m, n <= 500</li>
box[i][j] is either '#', '*', or '.'.
```

```
€ 🗘
JavaScript
 1 v const rotateTheBox = (b) ⇒ {
 2
        b = rotate90Clock(b);
 3
        let n = b.length;
 4
        let m = b[0].length;
 5 ▼
        for (let i = n - 1; \sim i; i--) {
 6 ▼
            for (let j = 0; j < m; j++) {
                 for (let d = i; d + 1 < n \&\& b[d][j] == '#' \&\& b[d + 1][j] == '.'; d++) {
 7 ▼
 8
                     [b[d][j], b[d + 1][j]] = [b[d + 1][j], b[d][j]];
9
10
            }
        }
11
12
        return b;
13
    };
14
15 v const rotate90Clock = (matrix) ⇒ {
16
        let n = matrix.length;
17
        let m = matrix[0].length;
18
        let res = initialize2DArrayNew(m, n);
19 ▼
        for (let i = 0; i < n; i++) {
            for (let j = 0; j < m; j++) {
20 🔻
                 res[j][n - i - 1] = matrix[i][j];
21
22
23
        }
24
        return res;
25
    };
26
27 v const initialize2DArrayNew = (m, n) ⇒ {
28
        let data = [];
29 •
        for (let i = 0; i < m; i++) {
30
            let tmp = new Array(n).fill(0);
31
            data.push(tmp);
```

```
Rotating the Box - LeetCode Contest
 32
 33
           return data;
 34
      };
☐ Custom Testcase
                        Use Example Testcases
                                                                                                                  Run
                                                                                                                             △ Submit
Submission Result: Accepted (/submissions/detail/493549890/) ?
                                                                                   More Details > (/submissions/detail/493549890/)
Share your acceptance!
               1
Copyright © 2021 LeetCode
Help Center (/support) | Jobs (/jobs) | Bug Bounty (/bugbounty) | Students (/student) | Terms (/terms) | Privacy Policy (/privacy)
United States (/region)
```