

## 5781. Remove All Occurrences of a Substring

[My Submissions \(/contest/biweekly-contest-55/problems/remove-all-occurrences-of-a-substring/submissions/\)](/contest/biweekly-contest-55/problems/remove-all-occurrences-of-a-substring/submissions/)

[Back to Contest \(/contest/biweekly-contest-55/\)](/contest/biweekly-contest-55/)

Given two strings `s` and `part`, perform the following operation on `s` until **all** occurrences of the substring `part` are removed:

- Find the **leftmost** occurrence of the substring `part` and **remove** it from `s`.

Return `s` after removing all occurrences of `part`.

A **substring** is a contiguous sequence of characters in a string.

User Accepted:	0
User Tried:	0
Total Accepted:	0
Total Submissions:	0
Difficulty:	Medium

### Example 1:

**Input:** `s = "daabcbaabcbc"`, `part = "abc"`

**Output:** `"dab"`

**Explanation:** The following operations are done:

- `s = "daabcbaabcbc"`, remove `"abc"` starting at index 2, so `s = "dabaabcbc"`.
  - `s = "dabaabcbc"`, remove `"abc"` starting at index 4, so `s = "dababc"`.
  - `s = "dababc"`, remove `"abc"` starting at index 3, so `s = "dab"`.
- Now `s` has no occurrences of `"abc"`.

### Example 2:

**Input:** `s = "axxyxyxyy"`, `part = "xy"`

**Output:** `"ab"`

**Explanation:** The following operations are done:

- `s = "axxyxyxyy"`, remove `"xy"` starting at index 4 so `s = "axxyxyy"`.
  - `s = "axxyxyy"`, remove `"xy"` starting at index 3 so `s = "axxyy"`.
  - `s = "axxyy"`, remove `"xy"` starting at index 2 so `s = "axy"`.
  - `s = "axy"`, remove `"xy"` starting at index 1 so `s = "a"`.
- Now `s` has no occurrences of `"xy"`.

### Constraints:

- `1 <= s.length <= 1000`
- `1 <= part.length <= 1000`
- `s` and `part` consists of lowercase English letters.

JavaScript




```
1 const removeOccurrences = (s, p) => {
2   while (1) {
3     let idx = s.indexOf(p);
4     let end = idx + p.length - 1;
5     if (idx == -1) {
6       break;
7     } else {
8       s = s.slice(0, idx) + s.slice(end + 1);
9     }
10  }
11  return s;
12 };
```

☐ Custom Testcase[Use Example Testcases](#)[Run](#)[Submit](#)**Submission Result: Accepted** (</submissions/detail/513459354/>) ?[More Details > \(/submissions/detail/513459354/\)](/submissions/detail/513459354/)

Share your acceptance!

Copyright © 2021 LeetCode

[Help Center \(/support/\)](/support/) | [Jobs \(/jobs/\)](/jobs/) | [Bug Bounty \(/bugbounty/\)](/bugbounty/) | [Online Interview \(/interview/\)](/interview/) | [Students \(/student/\)](/student/) | [Terms \(/terms/\)](/terms/) |[Privacy Policy \(/privacy/\)](/privacy/) [United States \(/region/\)](/region/)