

2584. Split the Array to Make Coprime Products

My Submissions (/contest/weekly-contest-335/problems/split-the-array-to-make-coprime-products/submissions/)

Back to Contest (/contest/weekly-contest-335/)

You are given a **0-indexed** integer array `nums` of length `n`.

A **split** at an index `i` where $0 \leq i \leq n - 2$ is called **valid** if the product of the first `i + 1` elements and the product of the remaining elements are coprime.

- For example, if `nums = [2, 3, 3]`, then a split at the index `i = 0` is valid because 2 and 9 are coprime, while a split at the index `i = 1` is not valid because 6 and 3 are not coprime. A split at the index `i = 2` is not valid because $i == n - 1$.

Return the *smallest index i at which the array can be split validly* or `-1` if there is no such split.

Two values `val1` and `val2` are coprime if `gcd(val1, val2) == 1` where `gcd(val1, val2)` is the greatest common divisor of `val1` and `val2`.

User Accepted:	985
User Tried:	6602
Total Accepted:	1065
Total Submissions:	17645
Difficulty:	Hard

Example 1:

index	prefixproduct	suffixproduct	gcd
0	4	12600	4
1	28	1800	4
2	224	225	1
3	3360	15	15
4	10080	5	5

Input: `nums = [4,7,8,15,3,5]`
Output: 2
Explanation: The table above shows the values of the product of the first `i + 1` elements, the remaining elements, and their gcd. The only valid split is at index 2.

Example 2:

index	prefixproduct	suffixproduct	gcd
0	4	12600	4
1	28	1800	4
2	420	120	60
3	3360	15	15
4	10080	5	5

Input: `nums = [4,7,15,8,3,5]`
Output: -1
Explanation: The table above shows the values of the product of the first `i + 1` elements, the remaining elements, and their gcd. There is no valid split.

Constraints:

- `n == nums.length`
- $1 \leq n \leq 10^4$
- $1 \leq \text{nums}[i] \leq 10^6$

Discuss (https://leetcode.com/problems/split-the-array-to-make-coprime-products/discuss)

JavaScript



```

1 const findValidSplit = (a) => {
2   let N = Math.max(...a), n = a.length, first = Array(N + 1).fill(-1), last = Array(N + 1).fill(0);
3   let lpf = enumLowestPrimeFactors(N), imos = Array(n + 1).fill(0);
4   for (let i = 0; i < n; i++) {
5     let f = factorFast(a[i], lpf);
6     for (const e of f) {
7       if (first[e[0]] == -1) {
8         first[e[0]] = i;
9       }
10      last[e[0]] = i;
11    }
12  }
13  for (let i = 1; i <= N; i++) {
14    if (first[i] != -1 && first[i] != last[i]) {
15      imos[first[i]]++;
16      imos[last[i]]--;
17    }
18  }
19  for (let i = 0; i < n; i++) imos[i + 1] += imos[i];
20  for (let i = 0; i < n - 1; i++) {
21    if (imos[i] == 0) return i;
22  }
23  return -1;
24 };
25
26 const enumLowestPrimeFactors = (n) => {
27   let tot = 0, lpf = Array(n).fill(0), u = n + 32, lu = Math.log(u);
28   let d = u / lu, dt = d / lu, len = parseInt(d + dt * 1.5), primes = Array(len).fill(0);
29   for (let i = 2; i <= n; i++) lpf[i] = i;
30   for (let p = 2; p <= n; p++) {
31     if (lpf[p] == p) primes[tot++] = p;
32     for (let i = 0, tmp; i < tot && primes[i] <= lpf[p] && (tmp = primes[i] * p) <= n; i++) lpf[tmp] = primes[i];
33   }
34   return lpf;
35 };
36
37 const factorFast = (n, lpf) => {
38   let f = Array(9), q = 0;
39   while (lpf[n] > 0) {
40     let p = lpf[n];
41     if (q == 0 || p != f[q - 1][0]) {
42       f[q++] = [p, 1];
43     } else {
44       f[q - 1][1]++;
45     }
46     n /= p;
47   }
48   return f.slice(0, q);
49 };

```

☐ Custom Testcase[Use Example Testcases](#)[Run](#)[Submit](#)Submission Result: **Accepted** (/submissions/detail/913168280/) ?[More Details](#) (/submissions/detail/913168280/)

Share your acceptance!

Copyright © 2023 LeetCode

[Help Center](#) (/support) | [Jobs](#) (/jobs) | [Bug Bounty](#) (/bugbounty) | [Online Interview](#) (/interview/) | [Students](#) (/student) | [Terms](#) (/terms) | [Privacy Policy](#) (/privacy) [United States](#) (/region)